

**BellSouth Interconnection Services**

675 West Peachtree Street  
Atlanta, Georgia 30375

**Carrier Notification  
SN91085007**

Date: January 14, 2005

To: Competitive Local Exchange Carriers (CLEC)

Subject: CLECs – (Documentation/Guides) - Update to the BellSouth Local Ordering Handbook (LOH) Version **18.0a**, New Local Service Ordering Guide 6 (LSOG 6) and EDI Local Mechanization Specifications 6 (ELMS 6) for Release 18.0

This is to advise that BellSouth has identified the following documentation defects in the LOH Version **18.0a** for ELMS 6, Release 18.0.

CCP Number	Description Of The Change
2110	REQTYP E ISDN/BRI Resale Service: Modify LOCNUM fields in the LOH R/C/O tables.
2111	CIC field LSR section: Update verbiage for the CIC field in the Data Dictionary (LSR-Local Service Ordering section).  Update LOH Data Dictionary in TOS section for REQTY C Complex when RPON is populated: Revise Note 9 and add a following Note to indicate that for LNP Complex Services REQTY C when the RPON field is populated the RPON LSRs must reflect the TOS of record.
2119	Ordering Procedures for requesting BellSouth® PreferredPack® Plan: CLEC need to provide the required components associated with BellSouth PreferredPack Plan [to correctly process requests for this discounted pricing plan].
2120	BI1 and BI2 fields: Modify R/C/O tables for BAN2 and BI2 field to remove BI2/BAN2 from specified R/C/O tables, also modify Data Dictionary for BI1/BI2.
2121	LPIC & PIC fields: Modify Valid Entry Notes and add new manual Business Rule for LPIC and PIC fields on the PS-Port Service and Resale Service forms in the Data Dictionary.

Please refer to the attachments for specific details of the changes listed above.

These changes will be reflected in the next update of the ELMS 6 Release 18.0/LOH Version **18.0a**, scheduled to be posted on Friday, March 4, 2005.

A summary of all changes within this document will be listed in the **Summary of Changes** section. This update can be found on the BellSouth Interconnection Services Web site in the Customer Guides Section at:

<http://www.interconnection.bellsouth.com/guides/html/leo.html>

Please contact your BellSouth local support manager with any questions.

Sincerely,

**ORIGINAL SIGNED BY JERRY HENDRIX**

Jerry Hendrix – Assistant Vice President  
BellSouth Interconnection Services

Attachments

**CCP 2110 Attachment Listed Below****ELMS6****RCO Tables**

*The following tables show the Required, Conditional and Optional (R/C/O) fields on the valid forms/screens for this product. All unmentioned fields are either invalid, not applicable, prohibited or not supported. When fields are populated which are not supported by BellSouth, these not supported fields will be ignored. Populating any other fields may result in a fatal reject or a clarification of the service request.*

*Please note the following codes:*

- Optional fields marked with an asterisk (\*) force at least one of the conditional fields to become required when populated.
- Fields used only for manual orders are followed by (M).
- Fields used only for electronic orders are followed by (E).
- For fields marked with a DOUBLE asterisk (\*\*) please refer to the Data Dictionary for clarification.

*See the Data Dictionary Section for additional information on each field.*

ACT Tables: Reqtyp E, ISDN-BRI Resale Service

**ACT= C: LSR****Required**

ACT	BAN1	BCS (E)
CC	CCNA	D/TSENT
DDD	IMPCON	IMPCON-TEL NO.
INIT	INIT-FAX NO.	INIT-TEL NO.
LSO	PG_OF_ (M)	PON
REQTYP	SC	TOS

**Conditional**

AN	ATN	BI1
CUST	DFDT	NOR
PROJECT	RCC (E)	RPON
SUP	VER	

**Optional**

ALBR	APPTIME-DDD	BAN2
BI2	EXP	LSCP
REMARKS	RORD	SCA
SPEC	VTA	

**ACT= C: EU**



Attachment  
SN91085007

<div>Required</div> <div>LOCNUM</div>		LOCNUM HEADER (E)	NAME
PG_OF_ (M)		PON (M)	

ACT Tables: Reqtyp E, ISDN-BRI Resale Service**Conditional**

AAI	ACC	AN (M)
ATN (M)	BI1	CITY
DNUM	DQTY	EUA
IWBAN	IWCON	IWCON-TEL NO.
IWO	LD1	LD2
LD3	LV1	LV2
LV3	SANO	SASD
SASF	SASN	SASS
SATH	STATE	TC NAME
TC OPT	TC PER	TC TO PRI
TC TO SEC	TCID	VER (M)
ZIP	LOCNUM (M)	LOCNUM DETAIL (E)

**Optional**

DISC NBR*	IBT	LCON-NAME
LCON-TEL NO.	LOCNUM DETAIL (E)	NCON*
LOCNUM HEADER (E)		

**ACT= D: LSR****Required**

ACT	BAN1	BCS (E)
CC	D/TSENT	DDD
INIT	INIT-FAX NO.	INIT-TEL NO.
LSO	PG_OF_ (M)	PON
REQTYP	SC	TOS

**Conditional**

ALT-IMPCON-TEL NO.	AN	ATN
CUST	IMPCON-TEL NO.	NOR
RCC (E)	RPON	SUP
VER		

**Optional**

ALT-IMPCON*	DDDO	DFDT
IBT	IMPCON*	REMARKS
RORD	VTA	

ACT Tables: Reqtyp E, ISDN-BRI Resale Service**ACT= D: EU****Required**

<b>LOCNUM HEADER</b>	NAME	PG_OF_ (M)
PON (M)		

**Conditional**

AAI	AN (M)	ATN (M)
CITY	DNUM	DQTY (M)
EUA	LD1	LD2
LD3	LV1	LV2
LV3	SANO	SASD
SASF	SASS	SATH
STATE	TC NAME	TC OPT
TC PER	TC TO PRI	TC TO SEC
TCID	VER (M)	ZIP

<b>LOCNUM (M)</b>	<b>LOCNUM DETAIL (E)</b>
-------------------	--------------------------

**Optional**

DISC NBR*	LCON-NAME	LCON-TEL NO.
<b>LOCNUM DETAIL (E)</b>	REMARKS (M)	SASN*

<b>LOCNUM HEADER (E)</b>
--------------------------

**ACT= N: LSR****Required**

ACT (M)	BAN1 (M)	CC (M)
D/TSENT (M)	DDD (M)	IMPCON (M)
IMPCON-TEL NO. (M)	INIT (M)	INIT-FAX NO. (M)
INIT-TEL NO. (M)	LSO (M)	PG_OF_ (M)
PON (M)	REQTYP (M)	SC (M)
TOS (M)		

**Conditional**

ALT-IMPCON-TEL NO. (M)	AN (M)	ATN (M)
BI1 (M)	CUST (M)	DFDT (M)
NOR (M)	PROJECT (M)	RPON (M)
SUP (M)	VER (M)	

ACT Tables: Reqtyp E, ISDN-BRI Resale Service**Optional**

ALBR (M)	ALT-IMPCON* (M)	APPTIME-DDD (M)
BAN2 (M)	BI2 (M)	EXP (M)
LSCP (M)	REMARKS (M)	RORD (M)
SCA (M)	SPEC (M)	VTA (M)

**ACT= N: EU****Required**

CITY (M)	LOCNUM (M)	NAME (M)
PG_OF_ (M)	PON (M)	SASN (M)
STATE (M)	ZIP (M)	

**Conditional**

AAI (M)	ACC (M)	AN (M)
ATN (M)	EUA (M)	IWCON (M)
IWCON-TEL NO. (M)	LD1 (M)	LD2 (M)
LD3 (M)	LV1 (M)	LV2 (M)
LV3 (M)	SANO (M)	SASD (M)
SASF (M)	SASS (M)	SATH (M)
VER (M)	LOCNUM (M)	

**Optional**

IBT (M)	IWBAN (M)	IWO* (M)
LCON-NAME (M)	LCON-TEL NO. (M)	LOCNUM (M)
NCON* (M)	REMARKS (M)	

**ACT= T: LSR****Required**

ACT (M)	BAN1 (M)	CC (M)
D/TSENT (M)	DDD (M)	DDDO (M)
IMPCON (M)	IMPCON-TEL NO. (M)	INIT (M)
INIT-FAX NO. (M)	INIT-TEL NO. (M)	LSO (M)
PG_OF_ (M)	PON (M)	REQTYP (M)
SC (M)	TOS (M)	

ACT Tables: Reqtyp E, ISDN-BRI Resale Service**Conditional**

ALT-IMPCON-TEL NO. (M)	AN (M)	ATN (M)
BI1 (M)	CUST (M)	DFDT (M)
NOR (M)	PROJECT (M)	RPON (M)
SUP (M)	VER (M)	

**Optional**

ALBR (M)	ALT-IMPCON* (M)	APPTIME-DDD (M)
EXP (M)	LSCP (M)	REMARKS (M)
RORD (M)	SCA (M)	SPEC (M)
VTA (M)		

**ACT= T: EU****Required**

CITY (M)	<b>LOCNUM (M)</b>	NAME (M)
PG_OF_ (M)	PON (M)	SASN (M)
STATE (M)	ZIP (M)	

**Conditional**

AAI (M)	ACC (M)	AN (M)
ATN (M)	DNUM (M)	DQTY (M)
EUA (M)	IWCON (M)	IWCON-TEL NO. (M)
LD1 (M)	LD2 (M)	LD3 (M)
LV1 (M)	LV2 (M)	LV3 (M)
SANO (M)	SASD (M)	SASF (M)
SASS (M)	SATH (M)	TC NAME (M)
TC OPT (M)	TC PER <b>(M)</b>	TC TO PRI (M)
TC TO SEC (M)	TCID <b>(M)</b>	VER (M)
<b>LOCNUM (M)</b>		

**Optional**

DISC NBR* (M)	IBT (M)	IWBAN (M)
IWO* (M)	LCON-NAME (M)	LCON-TEL NO. (M)
NCON* (M)	REMARKS (M)	



ACT Tables: Reqtyp E, ISDN-BRI Resale Service**ACT= V: LSR**Required

ACT	BAN1	BCS (E)
CC	D/TSENT	DDD
IMPCON	IMPCON-TEL NO.	INIT
INIT-FAX NO.	INIT-TEL NO.	LSO
MI	PG_OF_ (M)	PON
REQTYP	SC	TOS

Conditional

ALT-IMPCON-TEL NO.	AN	ATN
BI1	CUST	DFDT
LSCP	NOR	PROJECT
RCC (E)	RPON	SUP
VER		

Optional

ALBR	ALT-IMPCON*	APPTIME-DDD
EXP	REMARKS	RORD
SCA	SPEC	VTA

**ACT= V: EU**Required

ELT	LOCNUM (M)	NAME
PG_OF_ (M)	PON (M)	

Conditional

AAI	ACC	AN (M)
ATN (M)	CITY	DNUM
DQTY (M)	EATN	EUA
EUMI	FB-BILLCON	FB-BILLCON TEL NO.
FB-BILLNM	FB-CITY	FB-FLOOR
FBI	FB-ROOM	FB-SBILLNM
FB-STATE	FB-STREET	FB-ZIP
IWBAN	IWCON	IWCON-TEL NO.
IWO	LD1	LD2
LD3	LV1	LV2
LV3	SANO	SASD
SASF	SASN	SASS
SATH	STATE	TC NAME
TC OPT	TC PER	TC TO PRI
TC TO SEC	TCID	VER (M)
ZIP	LOCNUM (M)	LOCNUM DETAIL (E)

ACT Tables: Reqtyp E, ISDN-BRI Resale ServiceOptional

DISC NBR*	IBT	LCON-NAME
LCON-TEL NO.	LOCNUM DETAIL (E)	NCON*
REMARKS (M)	VTA	LOCNUM HEADER (E)

**ACT= W: LSR**Required

ACT	BAN1	BCS (E)
CC	D/TSENT	DDD
INIT	INIT-FAX NO.	INIT-TEL NO.
LSO	PG_OF_ (M)	PON
REQTYP	SC	TOS

Conditional

AN	ATN	BI1
CUST	IMPCON-TEL NO.	NOR
PROJECT	RCC (E)	RPON
SUP	VER	

Optional

APPTIME-DDD	EXP	IMPCON*
REMARKS	RORD	VTA

ACT Tables: Reqtyp E, ISDN-BRI Resale Service**ACT= W: EU****Required**

DQTY (M)	LOCNUM DETAIL (E)	NAME
PG_OF_ (M)	PON (M)	

**Conditional**

AAI	AN (M)	ATN (M)
CITY	EUA (E)	FB-BILLCON
FB-BILLCON TEL NO.	FB-BILLNM	FB-CITY
FB-FLOOR	FB-ROOM	FB-STATE
FB-STREET	FB-ZIP	LD1
LD2	LD3	LV1
LV2	LV3	SANO
SASD	SASF	SASS
SATH	STATE	VER (M)
ZIP	LOCNUM DETAIL (E)	LOCNUM (M)

**Optional**

FBI*	IBT	LCON-NAME
LCON-TEL NO.	LOCNUM (M)	LOCNUM HEADER (E)
REMARKS (M)	SASN*	

**ELMS6****RCO Tables**

*The following tables show the Required, Conditional and Optional (R/C/O) fields on the valid forms/screens for this product. All unmentioned fields are either invalid, not applicable, prohibited or not supported. When fields are populated which are not supported by BellSouth, these not supported fields will be ignored. Populating any other fields may result in a fatal reject or a clarification of the service request.*

*Please note the following codes:*

- Optional fields marked with an asterisk (\*) force at least one of the conditional fields to become required when populated.
- Fields used only for manual orders are followed by (M).
- Fields used only for electronic orders are followed by (E).
- For fields marked with a DOUBLE asterisk (\*\*) please refer to the Data Dictionary for clarification.

*See the Data Dictionary Section for additional information on each field.*

ACT Tables: Reqtyp M, UNE-P/WLP 2-wire ISDN-BRI UNE Combo

**ACT= C: LSR****Required**

ACT (M)	BAN1 (M)	CC (M)
CCNA (M)	D/TSENT (M)	DDD (M)
INIT (M)	INIT-FAX NO. (M)	INIT-TEL NO. (M)
LSO (M)	PG_OF_ (M)	PON (M)
REQTYP (M)	SC (M)	TOS (M)

**Conditional**

ALT-IMPCON-TEL NO. (M)	AN (M)	ATN (M)
BI1 (M)	CUST (M)	DFDT (M)
IMPCON-TEL NO. (M)	LSO (M)	NOR (M)
PROJECT (M)	RPON (M)	SUP (M)
VER (M)		

**Optional**

ALBR (M)	ALT-IMPCON* (M)	APPTIME-DDD (M)
BAN2 (M)	BI2 (M)	EXP (M)
IMPCON* (M)	LSCP (M)	REMARKS (M)
RORD (M)	SCA (M)	SPEC (M)
VTA (M)		

ACT Tables: Reqtyp M, UNE-P/WLP 2-wire ISDN-BRI UNE Combo**ACT= C: EU****Required**

<b>LOCNUM (M)</b>	NAME (M)	PG_OF_ (M)
PON (M)		

**Conditional**

AAI (M)	ACC (M)	AN (M)
ATN (M)	BI1 (M)	CITY (M)
DNUM (M)	DQTY (M)	EUA (M)
IWCON (M)	IWCON-TEL NO. (M)	LD1 (M)
LD2 (M)	LD3 (M)	LV1 (M)
LV2 (M)	LV3 (M)	SANO (M)
SASD (M)	SASF (M)	SASS (M)
SATH (M)	STATE (M)	TC NAME (M)
TC OPT (M)	TC PER (M)	TC TO PRI (M)
TC TO SEC (M)	TCID (M)	VER (M)
ZIP (M)	<b>LOCNUM (M)</b>	

**Optional**

DISC NBR* (M)	IBT (M)	IWBAN (M)
IWO* (M)	LCON-NAME (M)	LCON-TEL NO. (M)
<b>LOCNUM (M)</b>	REMARKS (M)	SASN* (M)

**ACT= D: LSR****Required**

ACT (M)	BAN1 (M)	CC (M)
D/TSENT (M)	DDD (M)	INIT (M)
INIT-FAX NO. (M)	INIT-TEL NO. (M)	LSO (M)
PG_OF_ (M)	PON (M)	REQTYP (M)
SC (M)	TOS (M)	

**Conditional**

ALT-IMPCON-TEL NO. (M)	AN (M)	ATN (M)
CUST (M)	IMPCON-TEL NO. (M)	NOR (M)
RPON (M)	SUP (M)	VER (M)

**Optional**

ALT-IMPCON* (M)	DDDO (M)	DFDT (M)
IMPCON* (M)	REMARKS (M)	RORD (M)
VTA (M)		

ACT Tables: Reqtyp M, UNE-P/WLP 2-wire ISDN-BRI UNE Combo**ACT= D: EU**Required

<b>LOCNUM (M)</b>	NAME (M)	PG_OF_ (M)
PON (M)		

Conditional

AAI (M)	AN (M)	ATN (M)
CITY (M)	DNUM (M)	DQTY (M)
EUA (M)	LD1 (M)	LD2 (M)
LD3 (M)	LV1 (M)	LV2 (M)
LV3 (M)	SANO (M)	SASD (M)
SASF (M)	SASS (M)	SATH (M)
STATE (M)	TC NAME (M)	TC OPT (M)
TC PER (M)	TC TO PRI (M)	TC TO SEC (M)
TCID (M)	VER (M)	ZIP (M)

**LOCNUM (M)**Optional

DISC NBR* (M)	IBT (M)	LCON-NAME (M)
LCON-TEL NO. (M)	REMARKS (M)	SASN* (M)

**ACT= N: LSR**Required

ACT (M)	BAN1 (M)	CC (M)
D/TSENT (M)	DDD (M)	IMPCON (M)
IMPCON-TEL NO. (M)	INIT (M)	INIT-FAX NO. (M)
INIT-TEL NO. (M)	LSO (M)	PG_OF_ (M)
PON (M)	REQTYP (M)	SC (M)
TOS (M)		

Conditional

ALT-IMPCON-TEL NO. (M)	AN (M)	ATN (M)
BI1 (M)	BLOCK (M)	CUST (M)
DFDT (M)	NOR (M)	PROJECT (M)
RORD (M)	RPON (M)	SUP (M)
VER (M)		

Optional

ALBR (M)	ALT-IMPCON* (M)	APPTIME-DDD (M)
BA* (M)	BAN2 (M)	BI2 (M)
EXP (M)	LSCP (M)	REMARKS (M)
SCA (M)	SPEC (M)	VTa (M)

ACT Tables: Reqttyp M, UNE-P/WLP 2-wire ISDN-BRI UNE Combo**ACT= N: EU****Required**

CITY (M)	LOCNUM (M)	NAME (M)
PG_OF_ (M)	PON (M)	SASN (M)
STATE (M)	ZIP (M)	

**Conditional**

AAI (M)	ACC (M)	AN (M)
ATN (M)	EUA (M)	IWCON (M)
IWCON-TEL NO. (M)	LD1 (M)	LD2 (M)
LD3 (M)	LV1 (M)	LV2 (M)
LV3 (M)	SANO (M)	SASD (M)
SASF (M)	SASS (M)	SATH (M)
VER (M)	LOCNUM (M)	

**Optional**

IBT (M)	IWBAN (M)	IWO* (M)
LCON-NAME (M)	LCON-TEL NO. (M)	NCON* (M)
REMARKS (M)		

**ACT= V: LSR****Required**

ACT (M)	BAN1 (M)	CC (M)
D/TSENT (M)	DDD (M)	IMPCON (M)
IMPCON-TEL NO. (M)	INIT (M)	INIT-FAX NO. (M)
INIT-TEL NO. (M)	LSO (M)	PG_OF_ (M)
PON (M)	REQTYP (M)	SC (M)
TOS (M)		

**Conditional**

ALT-IMPCON-TEL NO. (M)	AN (M)	ATN (M)
BI1 (M)	CUST (M)	DFDT (M)
NOR (M)	PROJECT (M)	RPON (M)
SUP (M)	VER (M)	

**Optional**

ALBR (M)	ALT-IMPCON* (M)	APPTIME-DDD (M)
EXP (M)	LSCP (M)	REMARKS (M)
RORD (M)	SCA (M)	SPEC (M)
VTA (M)		

ACT Tables: Reqtyp M, UNE-P/WLP 2-wire ISDN-BRI UNE Combo**ACT= V: EU****Required**

ELT (M)	NAME (M)	PG_OF_ (M)
PON (M)		

**Conditional**

AAI (M)	ACC (M)	AN (M)
ATN (M)	CITY (M)	DNUM (M)
DQTY (M)	EAN (M)	EATN (M)
ELT (M)	EUA (M)	FB-BILLCON (M)
FB-BILLCON TEL NO. (M)	FB-BILLNM (M)	FB-CITY (M)
FBI (M)	FB-ROOM (M)	FB-ROOM (M)
FB-SBILLNM (M)	FB-STATE (M)	FB-STREET (M)
FB-ZIP (M)	IWCON (M)	IWCON-TEL NO. (M)
LD1 (M)	LD2 (M)	LD3 (M)
LOCNUM (M)	LV1 (M)	LV2 (M)
LV3 (M)	SANO (M)	SASD (M)
SASF (M)	SASN (M)	SASS (M)
SATH (M)	STATE (M)	TC NAME (M)
TC OPT (M)	TC PER (M)	TC TO PRI (M)
TC TO SEC (M)	TCID (M)	VER (M)
ZIP (M)		

**Optional**

DISC NBR* (M)	IBT (M)	IWBAN (M)
IWO* (M)	LCON-NAME (M)	LCON-TEL NO. (M)
NCON* (M)	REMARKS (M)	VTA (M)



**CCP 2111 Attachment Listed Below****ELMS6****CIC – Carrier Identification Code****LSR Form/Screen, NA Section**

(LSOG6 / ELMS6 map)

**Definition:**

Identifies the numeric code of the initiating local service provider.

Definition Notes:

NOTE 1: This code is identical to the CIC code specified on the local interconnection trunks.

**NOTE 2: CIC code is separate and distinct from the ACNA, CCNA, and CC codes.****Valid Entries:**

None

Valid Entry Notes:

None

**Data Characteristics:**

4 numeric characters

**Examples:**

5124

**Conditional Usage Notes:**

Note 1: Required when the REQ TYP is A and the 2nd character of the TOS is P or R.

Note 2: [Bulk] Required for UNE to UNE Bulk Migration.

**Business Rules****Rule 1: CIC code is separate and distinct from the ACNA, CCNA, and CC codes, however, in the case of REQ TYPs A and B/NPT is D (LNP), or REQ TYP C/NPT is D (LNP), this field may be populated with the same code used in the CC (Company Code) field.****None**

**ELMS6****TOS – Type of Service****LSR Form/Screen, NA Section**

(LSOG6 / ELMS6 map)

**Definition:**

Identifies the type of service for the line ordered.

**Definition Notes:**

NOTE 1: The type of service identifies the end user account as business, residential or government.

**Valid Entries:**

1st Character (type)

1 = Business

2 = Residence

3 = Government

4 = Coin

2nd Character (product)

A = Multi-Line (Not Applicable for Complex Service.)

B = Single Line (Not Applicable for Complex Service.)

C = Coin

D = All other complex services

E = BellSouth® Centrex®, ESSX®, and MultiServ®, and UNE-P/WLP Centrex

H = ISDN-BRI

J = PBX Trunk

P = LINE SPLITTING

Q = DID

R = Line Share

9 = EELs

- (hyphen) = not applicable

3rd Character (class)

M = Measured

F = Flat Rate

G = Message

- (hyphen) = not applicable

4th Character

N = CO Based Line Share DLEC Owned Splitter

W = WATS

S = Toll Free Dialing  
R = Remote Call Forwarding  
F = FXS (Foreign Exchange Service)  
Y = Hotel/Motel  
Z = Hospital  
- (hyphen) = not applicable

Valid Entry Notes:

NOTE 1: The 4th character of TOS values of W, or S is not valid for electronic ordering.

NOTE 2: The 3rd character of this field must not be F when the REQTYPE is F.

NOTE 3: The 2nd character of TOS must be a (Hyphen) when the REQTYPE is J.

NOTE 4: The 3rd character of TOS must be a (Hyphen) when the REQTYPE is J or A.

NOTE 5: When the 1st character of TOS is 2, the only valid entry for the 2nd character is A, B, H, J, P, R or Hyphen.

NOTE 6: When the 1st character of the TOS is 3 the 2nd character of TOS must not be R.

NOTE 7: When 1st character of the TOS is 1, 2 or 3, the 2nd character must not be C.

NOTE 8: When the 1st character of the TOS is '4', then the 2nd character must be C.

NOTE 9: (Excluding REQTYPE C-Complex LNP) If a request is submitted and the RPON field is populated, the TOS must be as follows:

- 1st character 1, 2 or 4
- 2nd character A, B, C, H, J, P or R
- 3rd character M, F, G or – (Hyphen)
- 4th Character – (Hyphen) (For Line Share DLEC owned Splitter 4th character can be N)

NOTE ##: For REQTYPE C- Complex LNP Services, when the RPON field is populated, the RPON LSRs must reflect the TOS of record. For example, if the service type is BRI the 1<sup>st</sup> two characters of TOS is 1H.

NOTE 10: When the REQTYPE is A (Excluding Line Share DLEC Owned Splitter), the valid TOS entries are:

- 1st character 1 or 2
- 2nd character is A, B, R, P or 9
- 3rd – (Hyphen)
- 4th Character – (Hyphen)

NOTE 11: The 3rd character of the TOS must be a – (HYPHEN) when the REQTYPE is N and the 4th character of the TOS field is Y or Z.

NOTE 12: When the 4th character of the TOS field is F, the 2nd character must be A, B, H or J.

NOTE 13: When the 1st character of the TOS field is 4, the 4th character must be a – (Hyphen)

NOTE 14: The 4th character of the TOS field must be a – (Hyphen) when the REQ TYP is J.

NOTE 15: When both PBX and DID trunks are on the same request the 2nd character of the TOS must be Q.

NOTE 16: When the 4th character of this field is N, 2nd character of the TOS must be R or P.

NOTE 17: When the LSR request is for Remote Call Forwarding (RCF) the valid values for TOS must be as specified below:

- 1st character: 1, 2, or 3
- 2nd character: A or B
- 3rd character: F or M
- 4th character: R

NOTE 18: When the 4th character of this field is R the REQ TYP must be E or M.

NOTE 19: The TOS must be one of the following when changing from a residence class of service to a business class of service and the REQ TYP is E (Non-Complex) or M (Switched Combination RES/BUS)

- 1AM-
- 1BM-
- 1AF-
- 1BF-

NOTE 20: The TOS must be one of the following when changing from a business class of service to a residence class of service and the REQ TYP is E (Non-Complex) or M (Switched Combination RES/BUS):

- 2AM-
- 2BM-
- 2AF-
- 2BF-

NOTE 21: The TOS must be one of the following when changing from a business class of service to a residence class of service or from a residence to a business class of service and the REQ TYP is J:

- 1---
- 2---

NOTE 22: When the 2nd character of TOS is – (hyphen) the REQ TYP must be JB

Manual:

NOTE 23: When the REQ TYP is P the 2nd character of the TOS field must be E.

NOTE 24: When the 2nd character of the TOS field is E, the 1st character must not be 2 or 4.

NOTE 25: When the REQ TYP is M (UNE-P/WLP Centrex) the 2nd character of the TOS must be E, the 3rd must be M, and the 4th must be a hyphen (-).

NOTE 26: When the REQ TYP is E (WATS), the 2nd character of the TOS must be D, and the 4th character must be W.

NOTE 27: When the REQ TYP is E (Toll Free Dialing), the 2nd character of the TOS must be D and the 4th character must be S.

NOTE 28: The 4th character of the TOS must be F when the request is for foreign exchange (FX) or foreign central office (FCO).

NOTE 29: The 4th character of the TOS must be Y when the request is for Hotel/Motel service.

NOTE 30: The 4th character of the TOS must be Z when the request is for Hospital Service.

NOTE 31: When the 2nd character of the TOS is P and the splitter is DLEC owned, the 4th character of the TOS must be N.

Electronic:

NOTE 32: For REQ TYP = C, when the 4th character of TOS is F, then the 2nd character of TOS = D is prohibited.

**Data Characteristics:**

4 alpha/numeric characters

**Examples:**

1AM-

1R-N

**Conditional Usage Notes:**

None

**Business Rules**

Rule 1: For REQ TYP A, Designed and Non-Designed Loops, the 2nd character of the TOS should indicate multi-line or single line based on the number of circuits being requested on the LSR, except for Line Sharing, Line Splitting and EELs.

Rule 2: For REQ TYP B and C, the TOS field must reflect the service that is currently on the BellSouth CSR.

Rule 3: If the data in the LNECLS SVC field is a business class of service then the first character of the TOS must be 1.

Rule 4: If the data in the LNECLS SVC field is a residence class of service, then the first character of the TOS must be 2.

Rule 5: The Third and Fourth Characters of this field must be a hyphen (-) for REQ TYPs B and C, NPT = D (LNP/WLNP).

Rule 6: [BULK] For UNE to UNE BULK Ordering, TOS (Default) field is required once for every UNE to UNE.

BULK request. Note: If there is a mixture of account classes of service, TOS (Override) may be shown per EATN.

Rule 7: [BULK] TOS (Default) For UNE to UNE BULK Ordering Note: If TOS entered at the BULK [Header] level, then all EATNs on BULK request will default to this TOS value.

Rule 8: [BULK] TOS (Override) is optional for UNE BULK Ordering. Note: Overridable at the Account level.

Manual:

Rule 9: If REQ TYP = M (for UNE-P Centrex) the 2nd character of the TOS field must be "E" and the 3rd character must be "M".

\*\*\*\*\* End of definition for TOS / LSR form screen \*\*\*\*\*

**ELMS6****CCP 2119 Attachment Listed Below**

BellSouth Local Ordering Handbook  
Section 3 – Ordering

**ELMS6****Ordering Guidelines for BellSouth® PreferredPack® Plan**

The new BellSouth PreferredPack plan provides a flat rate access line equipped with Touch-tone capability, and Caller ID Deluxe. The plan also includes the choice of the following specific features/services listed in the chart below:

Minimum & Maximum = 1	
Product/Feature	USOC
Unlimited Residential Line with Touch tone	1F1CL*
Unlimited Residential Line with Touch tone – North Carolina only	PS1CL**
Minimum & Maximum = 1	
Caller ID Deluxe – Name and Number Delivery	NXM
Caller ID Deluxe – Name and Number Delivery with Anonymous Call Rejection	NXMCR
Minimum = 2, Maximum = 4	
Call Waiting Deluxe	ESXDC
Call Waiting Deluxe with GCJ/GCJRC	ESXD9
Call Return	NSS
3 Way Calling	ESC
Privacy Director	PMX1R
Minimum = 0, Maximum = 4	
Call Forwarding Busy Line	GCE
Call Forwarding Don't Answer	GCJ
Call Forwarding Don't Answer Ring Control	GCJRC
Message Waiting Indicator-Audio Visual	MWWAV
Message Waiting – Stutter Dial tone	MWW
*98 Access to BellSouth or IndustrialVoice Mail	S98VM
*98 Access to Enhanced Service Provider Voicemail	S98AF



Attachment  
SN91085007

<b>Basic Class of Service options:</b>
* <b>1F1CL</b> – available in all 9 states (In the following NPA/NXX in North Carolina: Gatewood 336/388 and Milton 336/234)
** <b>PS1CL</b> – available in North Carolina (except in Gatewood and Milton exchanges)

Package Plan	USOC	Package FIDs
BellSouth PreferredPack plan	PAMA5	COS-WW-PAMA5

## Ordering Considerations

### *Availability*

The new BellSouth<sup>®</sup> PreferredPack<sup>®</sup> plan is available in all nine (9) states.

### *Restrictions*

The new BellSouth PreferredPack plan (**PAMA5**) **must be ordered manually**.

This service offering is available for **Residential customers only**.

### **LSR Requirements**

Valid REQ TYP is E (non-complex Resale)

All ACT TYPs are valid

All LNAs

Applicable TOS 2BF-

REMARKS – “Bill SOME C Charge”

**NOTE: The Basic Class of Service (1F1CL or PS1CL), the Package USOC (PAMA5) and the desired features/services associated with the plan must be provided on the Resale Service Request form in the Features Detail Section.**

The following forms are used to submit a request for the new BellSouth PreferredPack Plan:

- LSR
- EU
- Resale
- Directory (Optional)



## CCP 2120 Attachment Listed Below

### ELMS6

Reqtyp	Product	ACT	Form / Screen	Field	Status	Change To	Manual
E	TFD	C	LSR	BAN2	C	Remove	M
E	TFD	D	LSR	BAN2	C	Remove	M
E	TFD	V	LSR	BAN2	C	Remove	M
E	TFD	W	LSR	BAN2	C	Remove	M
E	WATS	C	LSR	BAN2	C	Remove	M
E	WATS	D	LSR	BAN2	C	Remove	M
E	WATS	V	LSR	BAN2	C	Remove	M
E	WATS	W	LSR	BAN2	C	Remove	M
E	Uniserv UAN / CSA / ANI	D	LSR	BAN2	C	Remove	M
M	UNE-P/WLP DDITS - Trunk Service	C	LSR	BAN2	C	Remove	M
M	UNE-P/WLP DDITS - Trunk Service	D	LSR	BAN2	C	Remove	M
M	UNE-P/WLP DDITS - Trunk Service	N	LSR	BAN2	C	Remove	M
M	UNE-P/WLP DDITS - Trunk Service	V	LSR	BAN2	C	Remove	M
M	UNE-P/WLP 4-wire DS1 Loop with Channelization with Port (Trunk Service)	C	LSR	BAN2	C	Remove	M
M	UNE-P/WLP 4-wire DS1 Loop with Channelization with Port (Trunk Service)	D	LSR	BAN2	C	Remove	M
M	UNE-P/WLP 4-wire DS1 Loop with Channelization with Port (Trunk Service)	N	LSR	BAN2	C	Remove	M
M	UNE-P/WLP 4-wire DS1 Loop with Channelization with Port (Trunk Service)	V	LSR	BAN2	C	Remove	M
M	UNE-P/WLP Centrex	V	LSR	BAN2	C	Remove	M
E	TFD	C	LSR	BI2		Remove	M
E	TFD	D	LSR	BI2		Remove	M
E	TFD	V	LSR	BI2		Remove	M
E	TFD	W	LSR	BI2		Remove	M
E	WATS	C	LSR	BI2		Remove	M
E	WATS	D	LSR	BI2		Remove	M
E	WATS	V	LSR	BI2		Remove	M
E	WATS	W	LSR	BI2		Remove	M
E	Uniserv UAN / CSA / ANI	D	LSR	BI2		Remove	M
M	UNE-P/WLP DDITS - Trunk Service	C	LSR	BI2		Remove	M

M	UNE-P/WLP DDITS - Trunk Service	D	LSR	BI2		Remove	M
M	UNE-P/WLP DDITS - Trunk Service	N	LSR	BI2		Remove	M
M	UNE-P/WLP DDITS - Trunk Service	V	LSR	BI2		Remove	M
M	UNE-P/WLP 4-wire DS1 Loop with Channelization with Port (Trunk Service)	C	LSR	BI2		Remove	M
M	UNE-P/WLP 4-wire DS1 Loop with Channelization with Port (Trunk Service)	D	LSR	BI2		Remove	M
M	UNE-P/WLP 4-wire DS1 Loop with Channelization with Port (Trunk Service)	N	LSR	BI2		Remove	M
M	UNE-P/WLP 4-wire DS1 Loop with Channelization with Port (Trunk Service)	V	LSR	BI2		Remove	M
M	UNE-P/WLP Centrex	V	LSR	BI2		Remove	M
A	Channelized DS1, DS3, STS1 Local Channel	N	LSR	BAN2	C	Remove	M
A	EELs	C	LSR	BAN2	C	Remove	
A	EELs	N	LSR	BAN2	C	Remove	
A	EELs	T	LSR	BAN2	C	Remove	
A	Non-Channelized DS3 and STS1	N	LSR	BAN2	C	Remove	M
A	Unbundled Dark Fiber (UDF)	N	LSR	BAN2	C	Remove	M
A	Ordinarily Combined UNEs (OCU)	C	LSR	BAN2	C	Remove	M
A	Ordinarily Combined UNEs (OCU)	N	LSR	BAN2	C	Remove	M
A	Ordinarily Combined UNEs (OCU)	T	LSR	BAN2	C	Remove	M
A	Non-Channelized IOC	C	LSR	BAN2	C	Remove	
A	Non-Channelized IOC	N	LSR	BAN2	C	Remove	
A	Channelized DS1, DS3, STS1 Local Channel	N	LSR	BI2		Remove	M
A	EELs	C	LSR	BI2		Remove	
A	EELs	N	LSR	BI2		Remove	
A	EELs	T	LSR	BI2		Remove	
A	Non-Channelized DS3 and STS1	N	LSR	BI2		Remove	M
A	Unbundled Dark Fiber (UDF)	N	LSR	BI2		Remove	M
A	Ordinarily Combined UNEs (OCU)	C	LSR	BI2		Remove	M
A	Ordinarily Combined UNEs (OCU)	N	LSR	BI2		Remove	M
A	Ordinarily Combined UNEs (OCU)	T	LSR	BI2		Remove	M
A	Non-Channelized IOC	C	LSR	BI2		Remove	
A	Non-Channelized IOC	N	LSR	BI2		Remove	

**ELMS6****BI1 – Billing Account Number Identifier 1****LSR Form/Screen, NA Section**

(LSOG6 / ELMS6 map)

**Definition:**

Identifies the service type of Billing Account Number (BAN).

**Definition Notes:**

None

**Valid Entries:**

Entry	Description
D	Directory Listings
L	Loop
N	Number Portability
P	Port
R	Resale
M	Port Switched Combination

**Valid Entry Notes:**

NOTE 1: When REQ TYP is B or C and NPT is D (LNP), valid entry can only be "L" or "N" for REQ TYP B, or "N" for REQ TYP C.

NOTE 2: When the REQ TYP is A and the 2nd character of the TOS is P, the only valid entry allowed in this field is "M".

NOTE 3: When the request is for WLNP and this field is populated the only valid value is "N".

NOTE 4: [BULK] For Reqtyp B UNE to UNE Bulk, populate the BI1 field as "L".

**NOTE #:** When the REQ TYP is A, and the 2<sup>nd</sup> character of the TOS is not P, the valid value for this field is "L".

**NOTE #:** When the REQ TYP is E or P, the valid value for this field is "R".

**NOTE #:** When the REQ TYP is M, the valid value for this field is "M".

**NOTE #:** When the REQ TYP is F, the valid value for this field is "P".

**NOTE #:** When the REQ TYP is J, the valid values for this field is "D", "R" or "M".

**NOTE #:** When the REQ TYP is N and the P field is populated with "A" the valid value for this field is "R".

**NOTE #:** When the REQ TYP is N and the P field is populated with "B" the valid value for this field is "P".

**NOTE #:** When the REQTP is N and the P field is populated with "C" the valid value in this field is "M".

**Data Characteristics:**

1 alpha character

**Examples:**

L

**Conditional Usage Notes:**

Note 1: Required when more than one BAN field (e.g., BAN1 and BAN2) is populated, otherwise optional.

Note 2: [BULK] When populated an entry is required once for each EATN on Reqtyp B UNE to UNE Bulk requests.

**Business Rules**

Rule 1: The BI1 and the BI2 field must not match.

Manual:

Note 2: (ULUE) Required once per ECCKT.

\*\*\*\*\* End of definition for BI1 / LSR form screen \*\*\*\*\*

## BI2 – Billing Account Number Identifier 2

### LSR Form/Screen, NA Section

(LSOG6 / ELMS6 map)

#### Definition:

Identifies the service type of Billing Account Number (BAN).

#### Definition Notes:

None

#### Valid Entries:

Entry	Description
D	Directory Listings
L	Loop
N	Number Portability
P	Port
R	Resale
M	Port Switched Combination

#### Valid Entry Notes:

NOTE 1: When REQTP is B and NPT is D (LNP), valid entry can only be "L" or "N".

NOTE 2: [BULK] For Reqtyp B UNE to UNE Bulk, populate the BI2 field as "N".

**NOTE #: When the REQTP is F, the valid value for this field is "P".**

#### Data Characteristics:

1 alpha character

#### Examples:

L

#### Conditional Usage Notes:

Note 1: Required when more than one BAN field (e.g., BAN1 and BAN2) is populated, otherwise optional.

Note 2: Prohibited when the REQTP is C.

Note 3: [Bulk] When populated an entry is required once per EATN when the ELT field is populated with A on Reqtyp B UNE to UNE Bulk requests.



Attachment  
SN91085007

### **Business Rules**

Rule 1: The BI1 and BI2 fields must not match.

\*\*\*\*\* End of definition for BI2 / LSR form screen \*\*\*\*\*

**CCP 2121 Attachment Listed Below****ELMS6****LPIC – IntraLATA Presubscription Indicator Code****RS Form/Screen, NA Section**

(LSOG6 / ELMS6 map)

**Definition:**

Identifies the Presubscription Indicator Code (LPIC) for the carrier the customer has selected for IntraLATA traffic.

**Definition Notes:**

None

**Valid Entries:**

Entry	Description
XXXX	Valid LPIC Code (4 Numerics)
NONE	No LPIC chosen (Customer does not want to presubscribe.)
NC	No Change
UNDC	Undecided (Customer has not decided which presubscribed carrier to select.)
blank	No Change/Not populated

Additional Valid Entry for Manual:

NA Not Applicable - Service may not require a LPIC or used in a conversion 'As Is' scenario.

**Valid Entry Notes:**

Note 1: Excluding RCF (4th character TOS=R), when the LNA is N, G, or T, the only valid entries are NONE, UNDC or a 4 numeric valid LPIC code.

~~Note 2: When the LNA is P, the only valid entries are NONE, UNDC, a 4 numeric valid LPIC code, NC or blank.~~

Note **3 #**: Excluding RCF (4TH character TOS=R), when the LNA is V, C or X the only valid entries are NONE, UNDC, a 4 numeric valid LPIC code or when the LPIC is not changing, this field must be populated with NC (No Change) or left Blank.

**Electronic:**

Note #: When the LNA is P, the only valid entries are NONE, UNDC or a 4 numeric valid LPIC code.

**Manual:**

**Note#:** When the LNA is P, the only valid entries are NONE, UNDC, a 4 numeric valid LPIC code, NC or blank.

**Data Characteristics:**

2 or 4 alpha characters or 4 numeric characters

**Examples:**

NC

NONE

0288

**Conditional Usage Notes:**

Note 1: Excluding RCF this field is required when the LNA field is N, T, G or P.

Note 2: Excluding RCF this field is prohibited when the LNA is W, L or B.

Electronic:

Note 3: Required when the 1st character of TOS is 2 and the 4th character of the TOS is R and the LNECLS SVC field is populated with RCFRS or RCFRU

Note 4: Prohibited when the 1st character of the TOS is 2 and the 4th character of the TOS is R and one of the LNECLS SVC field is populated with RCFRF, RD5RF, RCFWS, RCFWE, RCF7S, RCF7E, RCFRQ, RCFRE, RCFRG or RCFRN.

Note 5: Required when the 1st character of the TOS is 1 or 3 and the 4th character of the TOS is R and the LNECLS SVC field is populated with RCFVS or RCFVU.

Note 6: Prohibited when the 1st character of the TOS is 1 or 3 and the 4th character of the TOS is R and the LNECLS SVC field is populated with RCFVF, RD5VF, RCFVJ, RCFVQ, RCFVE, RCFVG, RCFVD, RCFLB, RCFVN, RCFWS, RCFWE, RCFWU, RCFWQ, RCFWG, RCF7S, RCF7E, RCF7Q or RCF7G.

Manual

Note 7: Required when the 1st character of TOS is 2 and the 4th character of the TOS is R and the FEATURE field is populated with RCFRS or RCFRU

Note 8: Prohibited when the 1st character of the TOS is 2 and the 4th character of the TOS is R and one of the FEATURE field is populated with RCFRF, RD5RF, RCFWS, RCFWE, RCF7S, RCF7E, RCFRQ, RCFRE, RCFRG or RCFRN.

Note 9: Required when the 1st character of the TOS is 1 or 3 and the 4th character of the TOS is R and the FEATURE field is populated with RCFVS or RCFVU.

Note 10: Prohibited when the 1st character of the TOS is 1 or 3 and the 4th character of the TOS is R and the FEATURE field is populated with RCFVF, RD5VF, RCFVJ,





Attachment  
SN91085007

RCFVQ, RCFVE, RCFVG, RCFVD, RCFLB, RCFVN, RCFWS, RCFWE, RCFWU,  
RCFWQ, RCFWG, RCF7S, RCF7E, RCF7Q or RCF7G.

### Business Rules

None

Manual

Rule # When the LNA is P and this field is blank (not populated), the PIC field must not be blank (not populated).

\*\*\*\*\* End of definition for LPIC / RS form screen \*\*\*\*\*

**PIC – InterLATA Presubscription Indicator Code****RS Form/Screen, NA Section**

(LSOG6 / ELMS6 map)

**Definition:**

Identifies the Presubscription Indicator Code (PIC) for the carrier the customer has selected for InterLATA traffic.

**Definition Notes:**

None

**Valid Entries:**

Entry	Description
XXXX	Valid PIC Code of four (4) numerics
NONE	No PIC chosen (Customer does not want to presubscribe.)
NC	No Change
UNDC	Undecided (Customer has not decided which presubscribed carrier to select.)
blank	No Change/Not populated

Additional Valid Entry for Manual:

NA Not Applicable - Service may not require a PIC or used in a conversion 'As Is' scenario.

**Valid Entry Notes:**

Note 1: Excluding RCF (4TH Character TOS=R), when the LNA is N, G, or T, the only valid entries are NONE, UNDC or a 4 numeric valid PIC code.

Note 2: When the LNA is P, the only valid entries are NONE, UNDC, a 4 numeric valid PIC code, NC, or blank.

Note 3 #: Excluding RCF (4th character TOS=R), when the LNA is V, C or X the only valid entries are NONE, UNDC, a 4 numeric valid PIC code or when the PIC is not changing, this field must be populated with NC (No Change) or left Blank.

Note 4 #: When the 2nd character of the TOS is "H" and the Data PIC Code is different from the PIC Code, the Data PIC Code FID (DPIC XXXX) must be populated in the Feature Detail Section.

**Electronic:**

Note #: When the LNA is P, the only valid entries are NONE, UNDC or a 4 numeric valid PIC code.

**Manual:**

Note #: When the LNA is P, the only valid entries are NONE, UNDC, a 4 numeric valid PIC code, NC, or blank.

**Data Characteristics:**

2 or 4 alpha characters or 4 numeric characters

**Examples:**

NC

NONE

0288

**Conditional Usage Notes:**

Note 1: Excluding RCF, this field is required when the LNA field is N, G, T or P.

Note 2: Excluding RCF, this field is prohibited when the ACT is W, L or B.

Electronic:

Note 3: Required when the 1st character of the TOS is 2 and the 4th character of the TOS is R and the LNECLS SVC field is populated with RCFRQ, RCFRE or RCFRN.

Note 4: Prohibited when the 1st character of the TOS is 2 and the 4th character of the TOS is R and the LNECLS SVC field is populated with RCFRF, RD5RF, RCFWS, RCFWE, RCF7S, RCF7E, RCFRS, RCFRU or RCFRG.

Note 5: Required when the 1st character of the TOS is 1 or 3 and the 4th character of the TOS is R and the LNECLS SVC field is populated with RCFVQ, RCFVE, RCFVN, RCF7E, or RCF7Q.

Note 6: Prohibited when the 1st character of the TOS is 1 or 3 and the 4th character of the TOS is R and the LNECLS SVC field is populated with RCFVF, RD5VF, RCFVJ, RCFVU, RCFVG, RCFVD, RCFLB, RCFVS, RCFWS, RCFWE, RCFWU, RCFWQ, RCFWG, RCF7S or RCF7G.

Manual

Note 7: Required when the 1st character of the TOS is 2 and the 4th character of the TOS is R and the FEATURE field is populated with RCFRQ, RCFRE or RCFRN.

Note 8: Prohibited when the 1st character of the TOS is 2 and the 4th character of the TOS is R and the FEATURE field is populated with RCFRF, RD5RF, RCFWS, RCFWE, RCF7S, RCF7E, RCFRS, RCFRU or RCFRG.

Note 9: Required when the 1st character of the TOS is 1 or 3 and the 4th character of the TOS is R and the FEATURE field is populated with RCFVQ, RCFVE, RCFVN, RCF7E, or RCF7Q.

Note 10: Prohibited when the 1st character of the TOS is 1 or 3 and the 4th character of the TOS is R and the FEATURE field is populated with RCFVF, RD5VF, RCFVJ,



Attachment  
SN91085007

RCFVU, RCFVG, RCFVD, RCFLB, RCFVS, RCFWS, RCFWE, RCFWU, RCFWQ, RCFWG, RCF7S or RCF7G.

### Business Rules

Manual:

None

Rule #: When the LNA is P and this field is blank (not populated) the LPIC field must not be blank (not populated).

\*\*\*\* End of definition for PIC / RS form screen \*\*\*\*

## LPIC – IntraLATA Presubscription Indicator Code

### PS Form/Screen, NA Section

(LSOG6 / ELMS6 map)

#### Definition:

Identifies the Presubscription Indicator Code (LPIC) for the carrier the customer has selected for IntraLATA traffic.

#### Definition Notes:

None

#### Valid Entries:

Entry	Description
XXXX	Valid LPIC Code of four (4) numerics
NONE	No LPIC chosen (Customer does not want to presubscribe).
NC	No Change
UNDC	Undecided (Customer has not decided which presubscribed carrier to select.)
blank	No Change/Not populated

Additional Valid Entry for Manual:

NA	Not Applicable - Service may not require a LPIC or used in a conversion 'As Is' scenario.
----	-------------------------------------------------------------------------------------------

#### Valid Entry Notes:

Note 1: Excluding RCF (4th character TOS=R), when the LNA is N, G, or T, the only valid entries are NONE, UNDC or a 4 numeric valid LPIC code.

Note 2: When the LNA is P, the only valid entries are NONE, UNDC, a 4 numeric valid LPIC code, NC or blank.

Note 3 #: For REQ TYP M excluding RCF (4th character TOS=R), when the LNA is V, C or X the only valid entries are NONE, UNDC, a 4 numeric valid LPIC code or when the LPIC is not changing, this field must be populated with NC (No Change) or left blank.

Note 4 #: For REQ TYP F when the LNA is V, C or X the only valid entries are NONE, UNDC, a 4 numeric valid LPIC code or when the LPIC is not changing, this field must be populated with NC (No Change).

**Electronic:**

Note #: When the LNA is P, the only valid entries are NONE, UNDC or a 4 numeric valid LPIC code.

**Manual:**

Note #: When the LNA is P, the only valid entries are NONE, UNDC, a 4 numeric valid LPIC code ,NC or Blank.

**Data Characteristics:**

2 or 4 alpha characters or 4 numeric characters

**Examples:**

NC

NONE

0288

**Conditional Usage Notes:**

Note 1: Excluding RCF (4th character TOS=R), required when the REQ TYP is M and the LNA field is populated with N, G, T or P and the 4th character of the TOS is not R.

Note 2: Excluding RCF (4th character TOS=R), prohibited when the LNA is populated with W, L or B.

Note 3: Required when the REQ TYP is F and the LNA is N, G, P or V.

**Electronic**

Note 4: Required when the 4th character of the TOS is R and the LNECLS SVC field is populated with UERTR or UERTE.

Note 5: Prohibited when the 4th character of the TOS is R and the LNECLS SVC field is populated with UERLC, UERAC or UERVJ.

**Manual**

Note 6: Required when the 4th character of the TOS is R and the FEATURE field is populated with UERTR or UERTE.

Note 7: Prohibited when the 4th character of the TOS is R and the FEATURE field is populated with UERLC, UERAC or UERVJ.

**Business Rules**

**None**

**Manual:**



Attachment  
SN91085007

Rule #: When the LNA is P and this field is Blank (not populated), the PIC field must not be Blank (not populated).

\*\*\*\*\* End of definition for LPIC / PS form screen \*\*\*\*\*

## PIC – InterLATA Presubscription Indicator Code

### PS Form/Screen, NA Section

(LSOG6 / ELMS6 map)

#### Definition:

Identifies the Presubscription Indicator Code (PIC) for the carrier the customer has selected for the InterLATA traffic.

#### Definition Notes:

None

#### Valid Entries:

Entry	Description
XXXX	Valid PIC Code of four (4) numerics
NONE	No PIC chosen (Customer does not want to presubscribe.)
NC	No Change
UNDC	Undecided (Customer has not decided which presubscribed carrier to select.)
blank	No Change/Not populated

Additional Valid Entry for Manual:

NA Not Applicable - Service may not require a PIC or used in a conversion 'As Is' scenario.

#### Valid Entry Notes:

Note 1: Excluding RCF (4th character TOS=R), when the LNA is N, G, or T, the only valid entries are NONE, UNDC or a 4 numeric valid PIC code.

Note 2: When the LNA is P, the only valid entries are NONE, UNDC, a 4 numeric valid PIC code, NC, or blank.

Note 3 #: For REQ TYP M excluding RCF (4th character TOS=R), when the LNA is V, C or X the only valid entries are NONE, UNDC, a 4 numeric valid PIC code or when the PIC is not changing, this field must be populated with NC (No Change) or left Blank

Note 4 #: For REQ TYP F when the LNA is V, C or X the only valid entries are NONE, UNDC, NC or a valid PIC code or when the PIC is not changing, this field must be populated with NC (No Change).

Note 5 #: When the 2nd character of the TOS is "H" and the Data PIC Code is different from the PIC Code, the Data PIC Code FID (DPIC XXXX) must be populated in the Feature Detail Section.

#### Electronic:

Note #: When the LNA is P, the only valid entries are NONE, UNDC or a 4 numeric valid PIC code.

**Manual:**

Note #: When the LNA is P, the only valid entries are NONE, UNDC, a 4 numeric valid PIC code, NC or Blank.

**Data Characteristics:**

2 or 4 alpha characters or 4 numeric characters

**Examples:**

NC

NONE

0288

**Conditional Usage Notes:**

Note 1: Required when the LNA field is N, G, X, V or P; and the REQ TYP is F.

Note 2: Excluding RCF (4th character TOS=R), required when the REQ TYP is M and the LNA is N, P, T, G or P and the 4th character of the TOS is not R.

Note 3: Excluding RCF (4th character TOS=R), prohibited when the LNA is W, L or B.

Electronic:

Note 4: Required when the 4th character of the TOS is R and the LNECLS SVC field is populated with UERTR or UERTE.

Note 5: Prohibited when the 4th character of the TOS is R and the LNECLS SVC field is populated with UERLC, UERAC or UERVJ.

Manual:

Note 6: Required when the 4th character of the TOS is R and the FEATURE field is populated with UERTR or UERTE.

Note 7: Prohibited when the 4th character of the TOS is R and the FEATURE field is populated with UERLC, UERAC or UERVJ

**Business Rules**

**None**

**Manual:**

Rule #: When the LNA is P and this field is Blank (not populated), the LPIC field must not be Blank (not populated).