

Business Markets 675 West Peachtree Street Atlanta, Georgia 30375

Carrier Notification SN91086065

Date: March 30, 2006

To: Competitive Local Exchange Carriers (CLEC)

Subject: CLECs – (Documentation/Guides) - Update to the BellSouth Local Ordering Handbook (LOH) Version 22.0, New Local Service Ordering Guide 10 (LSOG 10) and EDI Local Mechanization Specifications 10 (ELMS 10) for Release 22.0

This is to advise that BellSouth will implement the following changes to update documentation in the LOH Version 22.0 for ELMS 10, Release 22.0.

CCP Number	Description Of The Change
	Star98 Access: Update Situation exhibit #1 to remove 'RCYC#' entry associated with the FEATURE DETAIL entries in the General Local Ordering chapter.
2358	Partial Move: Update the Partial Moves information in the General Local Ordering chapter under LSR Considerations to add "The Existing Account Telephone Number field must be populated with the current main account number" and update existing note to reference the "AN field" instead of 'REMARKS Section'. Combining REQTYP CB and BB When NPT=D: Add new header for "Combining REQTYP CB and BB When NPT=D" in the General Local Ordering chapter.
2359	Remove Jack Code USOCs: Remove all Jack values from IWJK and JKCODE fields in
2000	DIDDODPBX, LS, LSNP, PS and RS Forms/Screens sections in the Data Dictionaries.
2360	Fields on LSR 'Supplements': Add a Business Rule in the LOH Data Dictionary for the CC, SC, NC. NCI, SECNCI, EAN and EATN fields indicating that each of these fields cannot be changed on a supplement (ie: The 'field name' The CC field cannot be changed on a supplement).
2361	EUA field: Update Conditional Usage Note 1 to remove the wording 'otherwise prohibited'.

Please refer to the attachments for specific details of the changes listed above.

These changes will be reflected in the next update of the ELMS 10, Release 22.0/LOH Version 22.0A, scheduled to be posted on Friday, April 14, 2006.

A summary of all changes within this document will be listed in the **Summary of Changes** section.

This update can be found on the BellSouth Interconnection Services Web site in the Local Exchange Ordering (LEO) Guides located at:

http://interconnection.bellsouth.com/reference_library/guides/html/leo.html#loh

Please contact your BellSouth local support manager with any questions.

Sincerely,

ORIGINAL SIGNED BY KRISTEN E. SHORE

Kristen E. Shore – Director Business Markets

Attachments

BELLSOUTH®

Attachment SN91086065

CCP 2358 Attachment Listed Below

CRB: 4856 CCP: 2358 Release 22.0A MAP: ELMS10 General Local Ordering

Star 98 Access

Description:

Allows a subscriber to access their local voice mail service when they dial *98 from the phone line on which the voice mail service resides.

The Star 98 access connects the customer to the local voice mail box to which their calls are forwarded via a version of Call Forwarding Don't Answer.

Ordering Considerations:

None

Service Restrictions:

- Applicable to Residential and Business service type
- Provisioned on a per line basis and functions only from a line provisioned with this feature and the appropriate auxiliary calling features
- Not available on ISDN, Prestige®, Foreign Central Office (FCO)/Foreign Exchange (FX), Coin, RCF, Internet Call Waiting, Centrex -type services or DID/DOD/PBX service
- Must have a line equipped with a version of Call Forwarding Don't Answer
- Applicable in all 9 BST states.

LSR Restrictions:

- Limited to Non-Complex REQTYP E or M
- Limited to ACT of N, C, V, W or T
- Utilize the Non-Complex REQTYP E or M R/C/O tables for the applicable service type for completing the LSR.

Service Order Restrictions:

None

Tariff Reference:

A13

USOC References:

The USOC's below are unique to Star 98

• S98AF - Star 98 Access, Residence per line

BELLSOUTH[®]

Attachment SN91086065

- S98CP Star 98 Access, Voice Mail Companion services package, per business line equipped
- S98PK Star 98 Access, Voice Mail Companion Services Package, CSP per line equipped
- S98VM Star 98 Access, to BellSouth Voice Mail, per line
- GCJ Call Forwarding Don't Answer
- GCJRC Call Forwarding Don't Answer Ring Control (Where available).

FID References:

- CFND Call Forward Number Don't Answer
- RCYC Ringing Cycle
- CFNB Call Forward Number Busy
- PKG VM CSP-S98PK
- PKG VM BUS-S98CP.

Situations / Exhibits:

This section includes one or more ordering situations specific or unique to this product/process. The exhibit is not intended to depict an LSR package in its entirety. The situations below do not depict actual field formatting the customer should review the field data dictionary for business rule and field application.

Situation 1:

New residential line (Non-Complete Choice) with MemoryCall® Service (BellSouth voice mail) wants Star98 Access. This situation depicts only what is unique to Star 98. For this scenario we will make the following assumptions: REQTYP E ACT=N LNECLS SVC=1FR LSR/EU has been populated with applicable fields

```
TNS=4045551212

LNA=N

LNECLS SVC=1FR

PIC=XXXX

LPIC=XXXX

LNUM=00001

FA=N

FEATURE=S98VM

FEATURE DETAIL=CFND 404XXXXXXX

FEATURE=GCJ

FEATURE DETAIL = CFND 404XXXXX/RCYC#
```



Situation 2:

Existing residential line (Non-Complete Choice) with Star98 (Non-BellSouth voice mail) access. Request is for new Call Forwarding Numbers. This situation depicts only what is unique to Star 98.

For this scenario we will make the following assumptions: REQTYP E ACT=C LNECLS SVC=1FR

LSR/EU has been populated with applicable fields

TNS=4045551212 LNA=C LNECLS SVC=1FR FA=C FEATURE=S98AF FEATURE DETAIL=CFND 404XXXXXX/RCYC# FEATURE=GCJ FEATURE DETAIL = CFND 404XXXXXX/RCYC#

Related Topics / Information:

Voice Mail Custom Calling



CRB: 4859 CCP: 2358 MAP: ELMS10 RELEASE: 22.0A ELMS10 General Information.

BellSouth Local Ordering Handbook Section 3 - Ordering LSOG10 / ELMS10

Partial Move Order Request - REQTYP E & M, Non-complex

Description:

A partial move request occurs when a customer is requesting to move lines from an existing account at one location to a new location, but wishes to leave at least one (1) working line at the old location.

Ordering Considerations:

None

Service Restrictions

• Limited to manual ordering

• Dual service is not applicable

LSR Considerations

The customer must submit multiple LSR packages and use the RPON and NOR fields to associate the LSRs.

• The first LSR should be submitted with an ACT C, LNA D for all lines that are moving to the new location, or are simply being disconnected at the time of the move.

• The second LSR should be submitted with an ACT N, LNA N for all lines that are being installed at the new service address. Additional lines (that did not exist at the previous address) may also be added on this LSR using LNA N.

• The RPON field should be populated with the PON from the lead LSR, on **all** LSRs involved with the partial move request.

• The NOR field, for the lead PON, must be 01-XX, where XX is equal to the total number of LSRs involved with the partial move request. Each subsequent value for this field must be increased by one digit with XX data remaining the same.

• The customer should follow the REQTYP E (NON-Complex) R/C/O tables for ACT of C and ACT of N for completing an LSR for a partial move order on a resale account.

• The customer should follow the REQTYP M (Non-Complex) R/C/O tables for ACT of C and ACT of N for completing an LSR for a partial move order on Port/Loop combination residence/business.

 The Existing Account Telephone Number field must be populated with the current main account number.

• If the existing Account Telephone Number is moving to the new location, the new Main TN must be indicated in the ATN Field REMARKS section of the LSR.



Service Order Restrictions:

None

Tariff Reference:

None

USOC / FID References:

None

Situations / Exhibits:

None

Related Topics / Information:

None

CRB: 4862 CCP: 2358 Release: 22.0A MAP: ELMS10 General Local Ordering.

Combining REQTY CB and BB when NPT = D

Definition:

Provides a LNP work around process for combining REQTYP CB and BB using a single LSR when the NPT=D. The LNP GUI will not accept fax or electronic (EDI/TAG) Issue 9 or ELMS6 LSRs unless each LNUM includes cable ID and channel pair.

The most common scenario for combining REQTYP CB and BB is a request to port out an account that includes a Ringmaster number. Since there is not a loop associated with the Ringmaster, the porting request cannot be included on the LSR to port out the main telephone number with loop unless the CLEC wants to disconnect the Ringmaster number

Ordering Considerations:

- REQTYP: B
- ACTTYP: V
- MI: A, B, C, D
- LNA: V



• R/C/O Tables: Follow and use the appropriate REQTYP B Product Guidelines

Service Restrictions:

None

LSR Restrictions:

The following section provides detail information to assist you in filling out certain fields on LSR

The following information must be entered on the loop service with number portability tab:

Porting telephone number LNA=V Cable ID and Chan Pair for loop

The information for the telephone number porting out without loop is entered on the loop service with number portability tab:

Porting telephone number(Ringmaster) LNA=V Cable ID= **P000 or V000** Chan Pair= **000**

Service Order Restrictions:

None

Tariff Reference:

None

USOC / FID References:

None

Situations / Exhibits:

None

Related Topics / Information:



None

Attachment SN91086065

BELLSOUTH[®]

Attachment SN91086065

CCP 2359 Attachment Listed Below

CRB: 4858 CCP: 2359 Release: 22.0A MAP: ELMS10 Data Dictionaries.

JK CODE

Jack Code (DIDDODPBX Page)

Definition

Identifies the standard code for the particular registered or non-registered jack used to terminate the service.

Definition Notes

Note 1: Familiarization with the FCC's registration rules is requisite for all parties involved for the determination of the proper jack code for a given registered service.

Note 2: Registered jacks used to terminate category 1 and 3 services begin with the designation "RJ".

Note 3: This field is valid for electronic ordering only in this practice.

Valid Entries

None

Valid Entry Notes

<mark>____None</mark> Data Characteristics

5 alpha/numeric characters

Examples

RJ21X

Conditional Usage Notes

Electronic





Note 1: Prohibited when TACT is W or P.

Note 2: Prohibited when the AD is A.

Note 3: Required when the NIDR is Y.

Business Rules

None



IWJK

Inside Wire Jack Code (DIDDODPBX Page)

Definition

Identifies the standard code for the type of jack requested for inside wiring.

Definition Notes

Note 1: Jacks may be ordered on a line-by-line basis.

Note 2: This field is valid for electronic ordering only in this practice.

Note 3: When multiple lines are terminating in one multi-line jack, the IWJK and IWJQ fields should only be populated for the first line.

Valid Entries

None

Valid Entry Notes

<u>None</u> Data Characteristics

5 alpha/numeric characters

Examples

RJ21X

Conditional Usage Notes

Electronic

Note 1: Prohibited when TACT is W or P.

Note 2: Prohibited when the AD is A.

Note 3: Required when the IWJQ field is populated.

Business Rules

Electronic

Rule 1: When this field is populated the JR field must also be populated with Y.





JK CODE

Jack Code (LS Page)

Definition

Indicates the standard code for the particular registered or non-registered jack used to terminate the service.

Definition Notes

Note 1: Familiarization with the FCC's registration rules is requisite for all parties involved for the determination of the proper jack code for a given registered service.

Note 2: Registered jacks used to terminate category 1 and 3 services begin with the designation RJ.

Valid Entries

None

Valid Entry Notes

<u>None</u> Data Characteristics

5 alpha/numeric characters

Examples

RJ21X

Conditional Usage Notes

Note 1: Required when the NIDR field is populated with Y, otherwise prohibited.

Business Rules

None

Attachment	
SN91086065	

	Deleted: Note 1: The following USOCs are valid for all other REQTYP A
- 1	¶
	Notes 2, 3, 4, & 5: RJ11C, RJ11W, RJ11D, RJ14C, RJ14W, RJ12C, RJ12W,
	RJ13C, 11 RJ13W, RJ17C, RJ18C, RJ18W, RJ19C, RJ19W, RJ25C, RJ61X, RJ31X, RJ32X,
	RJ33X,
	Deleted: RJ34X, RJ35X, RJ36X, RJ37X, RJ38X, RJ71C, RJ2EM, RJ2FM, RJ2MZ, RJ21M, RJ2DM
	Deleted: RI2GM RI2HM RI22X
빏	RJ23X, RJ24X, RJ21X, RJ2DX, RJ2FX, RJ2HX, RJ2GX, RJ41Q,
111	Deleted: RJ41Z, RJ45Z, RJ45Q,
	RJ16X, RJ48Z, RJ41S, RJ45S, RJ26X, RJ26S, RJ27X, RJ48C,
	Deleted: RJ48H, RJ48M, RJ48S,
	RJ48A, RJ48B, RJM3X,
<u>'' (</u>	Deleted: RJM4X, RJ1DC, RJ2EX
77	¶[1]
97	Deleted: service types are: Anal [2]
14	Deleted: Extended Links (EELS [3]
1	Deleted: the JK CODE (Jack Control [4]
{	Deleted: RJ21X [¶] ([5]
	Deleted: service types are: Digit [6]
\geq	Deleted: Designed Basic Rate If [7]
	Deleted: (2W) Designed, HDSL [8]
$\frac{1}{2}$	Deleted: Designed, UCL - Short [9]
	Deleted: populated with 'Y', tl [10]
	Deleted: Type USOCs: RJ14Q [11]
	Deleted: RJ26S, RJ27X, RJ48 [12]
	Deleted: RJ21X¶ ([13]
(14)	Deleted: Note 4: When an LSR [14]
18	Deleted: service types are: Ana [15]
12 (Deleted: Extended Links (EEL [16]
10	Deleted: the JK CODE (Jack ([17]
10	Deleted: USOCs: RJ14Q, RJ4[[18]
12	Deleted: RJ27X, RJ48C, RJ48[[19]
- 16	Deleted: Basic Rate ISDN, Un [20]
	Deleted: Designed, HDSL (4W [21]
Ĩ	Deleted: UCL - Short (4W) Def [22]
	Deleted: 'Y', the JK CODE fie [22]
Ĩ	Deleted: RJ11C, RJ11W, RJ11 [741
ľ	Deleted: RJ17C, RJ18C, RJ18
ſ	Formatted [25]
	[[20]



IWJK

Inside Wire Jack Code (LS Page)

Definition

Indicates the standard code for the type of jack requested for inside wiring.

Definition Notes

Note 1: When multiple lines are terminating in one multi-line jack, the IWJK and IWJQ fields should only be populated for the first line.

Note 2: Jacks may be ordered on a line-by-line basis.

Valid Entries

None

Valid Entry Notes

_None **Data Characteristics**

5 alpha/numeric characters

Examples

RJ21X

Conditional Usage Notes

Note 1: Required when the IWJQ field is populated.

Note 2: Required when the JR field is Y.

Note 3: Prohibited when the JR field is not Y.

Business Rules None



1111

111



JK CODE Jack Code (LSNP Page)

Definition

Indicates the standard code for the particular registered or non-registered jack used to terminate the service.

Definition Notes

Note 1: Familiarization with the FCC's registration rules is requisite for all parties involved for the determination of the proper jack code for a given registered service.

Note 2: Registered jacks used to terminate category 1 and 3 services begin with the designation RJ.

Valid Entries

None

Valid Entry Notes

None Data Characteristics

5 alpha/numeric characters

Examples

RJ21X

Conditional Usage Notes

Note 1: Required when the NIDR field is populated with Y.

Business Rules

None

Attachment SN91086065

į	are valid for all other REQTYP B (INP or LNP) products not listed in
i	Valid Entry Notes 2, 3, 4, & 5: RJ11C, RJ11W, RJ11D, RJ14C, RJ14W, RJ12C, RJ12W,¶
	RJ13C, RJ13W, RJ17C, RJ18C, RJ18W, RJ19C, RJ19W, RJ25C, RJ61X, RJ31X,
	KJ32A, 1 [[27]
1	Deleted: must be submitted with the following: Voice Jack Type USOCs: RJ11C, RJ11W, RJ11D,
	Deleted: RJ14C, RJ14W, RJ1DC, RJ12C, RJ12W, RJ13C, RJ13W, RJ17C, RJ18C, RJ18W,
/	Deleted: RJ19C, RJ19W, RJ25C, RJ61X, RJ31X, RJ21X¶
2	<u> </u>
	Deleted: service types are: LNP - UCL- D, LNP - xDSL, LNP - ISDN, and NIDR field is populated
ĺ	Deleted: with 'Y', the JK CODE field must be submitted with the following: Data Jack Type USOCs:
ĺ	Deleted: RJ14Q, RJ41Z, RJ45Q, RJ45Z, RJ16X, RJ48Z, RJ41S, RJ45S, RJ26X, RJ26S, RJ27X,
1	Deleted: RJ48C, RJ48H, RJ48M,
	RJ48S, RJ48T, RJ48X, RJM3X, RJM4X, RJ26S, RJ21X¶ [29]
	Deleted: where service types are: INP - Designed Anaolg Loop, INP - Non- Designed Anaolg Loop,
	Deleted: INP UCL-ND, LNP - Designed Analog Loop, LNP - Non- Designed Analog Loop, LNP UQ [30]
Ì	Deleted: must be submitted with the following: Data Jack Type USOCs: RJ14Q, RJ41Z, RJ45Q,RJ45Z, R [31]
1	Deleted: DIASS DIAST DIASY
	RJM3X, RJM4X, RJ26S, RJ21X¶
1	
	Deleted: where service types are: INP - UCL-D, INP - xDSL, INP - ISDN, INP - DS0, LNP - UCL-D,
	Deleted: LNP - xDSL, LNP - ISDN; and NIDR field is populated with 'Y', the JK CODE field must be
	Deleted: submitted with the following: Voice Jack Type USOCs: RJ11C, RJ11W, RJ11D, RJ14C,
	Deleted: RJ14W, RJ1DC, RJ12C, RJ12W, RJ13C, RJ13W, RJ17C, RJ18C, RJ18W, RJ19C,
ĺ	Deleted: RJ19W, RJ25C, RJ61X, RJ31X, RJ21X¶
Í	Formatted: Font: Not Italic, Font color: Red

Deleted: Note 1: The following USOCs



IWJK

Inside Wire Jack Code (LSNP Page)

Definition

Indicates the standard code for the type of jack requested for inside wiring.

Definition Notes

Note 1: When multiple lines are terminating in one multi-line jack, the IWJK and IWJQ fields should only be populated for the first line.

Note 2: Jacks may be ordered on a line-by-line basis.

Valid Entries

None

Valid Entry Notes

<mark>.....None</mark> Data Characteristics

5 alpha/numeric characters

Examples

RJ21X

Conditional Usage Notes

Note 1: Required when the IWJQ field is populated.

Business Rules

Rule 1: When this field is populated the JR field must also be populated with Y.





JK CODE

Jack Code (PS Page)

Definition

Indicates the standard code for the particular registered or non-registered jack used to terminate the service.

Definition Notes

Note 1: Familiarization with the FCC's registration rules is requisite for all parties involved for the determination of the proper jack code for a given registered service.

Note 2: Registered jacks used to terminate category 1 and 3 services begin with the designation RJ.

Valid Entries

None

Valid Entry Notes

Note 1: JK CODE is allowed once per LNUM.

Data Characteristics

3 or 5 alpha/numeric characters

Examples

RJ21X

Conditional Usage Notes

Note 1: Required when the NIDR field is populated with Y, otherwise prohibited.

Note 2: Required when the JK NUM field is populated.

Note 3: Required when the JK POS field is populated.

Note 4: Prohibited when the TOS field is not 1AM-, 2AM-, 2BM-, or 1BM-.

Note 5: When REQTYP = M TOS = 1AM- or 1BM-, 2BM-, 2AM-, JK CODE is prohibited when IWO = S.

Business Rules



- 90 1900 y 1900 y 1900 y 1900 y 1900 y

ιhπ.





None

Attachment SN91086065



IWJK

Inside Wire Jack Code (PS Page)

Definition

Indicates the standard code for the type of jack requested for inside wiring.

Definition Notes

Note 1: When multiple lines are terminating in one multi-line jack, the IWJK and IWJQ fields should only be populated for the first line.

Note 2: Jacks may be ordered on a line-by-line basis.

Valid Entries

None

Valid Entry Notes

<u>None</u> Data Characteristics

5 alpha/numeric characters

Examples

RJ21X

Conditional Usage Notes

Note 1: Required when the IWJQ field is populated.

Note 2: Prohibited when the TOS field is not 1AM-, 2AM-, 2BM-, or 1BM-.

Note 3: Required when the JR field is Y.

Note 4: Prohibited when the JR field is not Y.

Note 5: Required when the FEATURE DETAIL field is populated with VCA.

Note 6: When REQTYP = M TOS = 1AM- or 1BM-, 2BM-, 2AM-, IWJK is prohibited when IWO = S.

Deleted: Note 1: For all TOS values except 2AM- or 2BM-, the following USOCs are valid for this field: RJ11C, RJ11W, RJ11D, RJ14C, RJ14W, RJ1DC, RJ12C, RJ12W, RJ13C, RJ13W, RJ17C, RJ18C, RJ18W, RJ19C, RJ19W RJ25C, RJ61X, RJ31X, RJ32X, RJ33X, RJ34X,RJ35X, RJ36X, RJ37X, RJ38X, RJ71C, RJ2EM, RJ2FM, RJ2MZ, RJ21M, RJ2DM, Deleted: RJ2GM, RJ2HM, RJ22X, RJ23X, RJ24X, RJ21X, RJ2DX, RJ2FX RJ2EX, RJ2HX, RJ2GX, Deleted: RJ41Q, RJ41Z, RJ45Q, RJ45Z, RJ16X, RJ48Z, RJ41S, RJ45S, RJ26X, RJ26S, RJ27X, Deleted: RJ48C, RJ48H, RJ48M RJ48S, RJ48T, RJ48X, RJ26M, RJ27M, RJ48Y, RJ48A, RJ48B, Deleted: RJM3X, RJM4X Note 2: When the TOS is 2AM-, or 2BM-, the only valid jack codes are: RJ11C, RJ11D, RJ11V Deleted: RJ14C, RJ14W, RJ15C, R131X, R125C, RLIRW Formatted: Font: Not Italic, Font color: Red

Business Rules



None

Attachment SN91086065



JK CODE

Jack Code (RS Page)

Definition

Indicates the standard code for the particular registered or non-registered jack used to terminate the service.

Definition Notes

Note 1: Familiarization with the FCC's registration rules is requisite for all parties involved for the determination of the proper jack code for a given registered service.

Note 2: Registered jacks used to terminate category 1 and 3 services begin with the designation RJ.

Valid Entries

None

Valid Entry Notes

Note 1: JK CODE is allowed once per LNUM.

Data Characteristics

5 alpha/numeric characters

Examples

RJ21X

Conditional Usage Notes

Note 1: Required when the NIDR field is populated with Y, otherwise prohibited.

Note 2: Prohibited when the REQTYP is E and the LNA is P, L or B.

Note 3: Prohibited when the REQTYP is E and the 2nd character of the TOS field is H, and the LNA is P, L or B.

Note 4: Required when JK NUM or JK POS field is populated

Business Rules



Attachment SN91086065



None

Attachment SN91086065



IWJK

Inside Wire Jack Code (RS Page)

Definition

Indicates the standard code for the type of jack requested for inside wiring.

Definition Notes

Note 1: When multiple lines are terminating in one multi-line jack, the IWJK and IWJQ fields should only be populated for the first line.

Note 2: Jacks may be ordered on a line-by-line basis.

Valid Entries

None

Valid Entry Notes

<mark>____None</mark> Data Characteristics

5 alpha/numeric characters

Examples

RJ21X

Conditional Usage Notes

Note 1: Required when the IWJQ field is populated.

Note 2: Required when the JR field is Y.

Note 3: Prohibited when the JR field is not Y.

Note 4: Prohibited when the REQTYP is E and the LNA is P, L or B.

Business Rules

None



MALA MALA MALA MALA

1014 1014

111.1



CCP 2360 Attachment Listed Below

CRB: 4860 CCP: 2360 Release 22.0A MAP: ELMS10 Data Dictionaries.

CC

Company Code (LSR Page)

Definition

Identifies the Exchange Carrier requesting service.

Definition Notes

Note 1: A four alphanumeric character code structure available for all Exchange Carriers in North America and certain U.S. Territories maintained by National Exchange Carrier Association (NECA).

Valid Entries

None

Valid Entry Notes

Note 1: The numbers 9417 (in this order) are prohibited in this field.

Data Characteristics

4 alpha/numeric characters

Examples

1234

Conditional Usage Notes

None

Business Rules

Rule 1: For REQTYP = A for Non-Designed Loops, and ACT = W, the CC field cannot match the 4 character code following the MAN FID on the CSR.



Rule 2: Also known as the four-digit Operating Company Number (OCN).

Rule 3: Carrier Identification Code (CIC) is prohibited in this field.

Rule 4: The CC (Company Code) on the LSR must always match the CC on the Billing Account Number (BAN).

Rule 5: When the request is for WLNP this field must be populated with the provider NECA OCN when the NECA OCN and the NP (Porting OCN) SPID are the same.

Rule 6: When the request is for WLNP this field must be populated with the provider (Porting) OCN when the NECA OCN and the NP (Porting OCN) SPID are the same.

Rule 7: The CC field cannot be changed on a supplement.



SC Service Center (LSR Page)

Definition

Identifies the Provider's Center.

Definition Notes

None

Valid Entries

LCSC = BellSouth® Local Carrier Service Center LCSL = BellSouth® LNP to Resale UNE-P/WLP Migrations

Valid Entry Notes

Note 1: An entry of "LCSL" is the only valid entry when the REQTYP "E", "M", "N", "P" and the ACT is "V" and the request is for an LNP to Resale UNE-P/WLP Migration

Note 2: An entry of "LCSC" is prohibited when the REQTYP is "E", "M", "N", "P" and the ACT is "V" and the request is for an LNP to Resale UNE-P/WLP Migration

Data Characteristics

4 alpha characters

Examples

LCSC LCSL

Conditional Usage Notes

None

Business Rules

Rule 1: The SC field cannot be changed on a supplement.

Manual

Rule 2: SC is LCSL is valid when requesting an LNP to Resale or UNE-P/WLP migration request for REQTYP E, M, N or P and ACT of V.

Deleted: 1



NC Network Channel Code (LSR Page)

Definition

Identifies the network channel code for the circuit(s) involved.

Definition Notes

Note 1: The network channel code describes the channel being requested.

Valid Entries

First Two Characters = Alpha Characters Third and Fourth Characters = Alpha characters or Hyphen (-)

Valid Entry Notes

Note 1: The first alpha two characters are the channel service code which identify the channel service.

Note 2: The third alpha/numeric character identifies the type of conditioning required on the channel. If there is no conditioning required, then this position has a hyphen (-).

Note 3: The fourth alpha character indicates optional features, such as bridging. If no options are required, then position has a hyphen (-).

Note 4: When the 2nd character of the TOS field is P or R, the only valid entry for this field is SWXX.

Note 5: When the REQTYP is B, this field must begin with TY, LY, LX or TX.

Data Characteristics

4 alpha/numeric characters

Examples

HCE

Conditional Usage Notes

Note 1: Required when the REQTYP is A and the ACT is N, C, D, T, W or V.

Note 2: Required when the REQTYP is B.



Business Rules

Rule 1: When the REQTYP is A (Non-Design Loops) and the ACT is W, the system will validate that the first two characters of the NC field are appropriate for the Class of Service on the CSR.

Rule 2: Designed services must be compatible with NCI and SECNCI when required.

Rule 3: On requests for a non-designed loop, the NC code must match the Loop type for the basic class of service on the CSR.

Rule 4: When the REQTYP is A (Non-Design Loops) and the ACT is D or T, the NC code must match the basic class of service type on the CSR.

Rule 5: When the REQTYP is A (Designed Loops) and the ACT is T or W, the NC code must match the NC code values of the loop on the existing CSR.

Rule 6: When the REQTYP is A (Non-Design Loops) and the ACT is D, the NC code must match the basic class of service type on the CSR.

Rule 7: When the REQTYP is A (Designed Loops) and the ACT is D, the NC code must match the NC code values of the loop being disconnected.

Rule 8: For REQTYP B - EELS the [SPEC / NC / NCI / SECNCI] combination must be one of the following to request EELS: [UNCVX / LY-- / 04QB9.11 / 02LS2] or [UNCVX / LY-- / 04QB9.11 / 02GS2]

Rule 9: The NC field cannot be changed on a supplement.

Electronic

	Rule,10: [Bulk Single LSR Arrangement] The same NC for all Loops is required.	1	Deleted: 9
l	Rule 11: For REQTYP B - EELS ordered in the Single LSR BULK Arrangement the [SPEC / NC / NCI / SECNCI] combination must be one of the following to request EELS: [UNCVX / LY / 04QB9.11 / 02LS2] or [UNCVX / LY / 04QB9.11 / 02GS2]		Deleted: 10



NCI

Network Channel Interface Code (LSR Page)

Definition

Identifies the electrical conditions on the circuit at the ACTL / Primary Location.

Definition Notes

None

Valid Entries

NCI Code Format:

This field consists of up to a twelve character code where the:

First two numeric characters (position 1 and 2) are required and represent the physical conductors, which describe the number of wires that traverse the point of termination (POT).

Next two alpha characters (position 3 and 4) are required and identify signaling and/or transmission characteristics.

Next alpha/numeric character (position 5) is required and describes the impedance with which the customer / end user will terminate the channel for the purpose of evaluating transmission performance or to indicate if the circuit is fiber.

Next character (position 6) is a period (used as a delimiter) only if additional characters will follow.

Next three alpha / numeric (position 7, 8, and 9) describe the protocol options.

Next character (position 10) is a period (used as a delimiter) only if additional characters will follow.

Next alpha character (position 11) describes the transmission level to be received at the customer / end user interface from the provider.

Next alpha character (position 12) describes the transmission level to be transmitted from the customer / end user interface to the provider.

Valid Entry Notes

None

Data Characteristics

Minimum of 5 alpha/numerics and Maximum of 12 alpha/numerics

Examples

02LS2 (This example indicates closed end of local loop at end user location.) 02QC2.00D (This example indicates open end of loop start circuit at central office.)

BELLSOUTH[®]

Attachment SN91086065

04QC2.00E (This example indicates a central office termination (closed end of station) loop start circuit.) C2QA2.10 (This example indicates service is multiplexed at the servicing wire center, DSO local loop to end user.)

Conditional Usage Notes

Note 1: This field is required when the NC field does not begin with TY or TX.

Note 2: This field is required when the SECNCI field is populated.

Note 3: This field is prohibited when the NC field begins with TY or TX.

Business Rules

Rule 1: Transmission Specifications may be described in provider tariffs and/ or in technical reference publications.

Rule 2: This (NCI) field must also be compatible with the NC field on the request.

Rule 3: Currently, two optional features are ordered through the specification of the NCI code set for the protocol option field: S = Sealing Current Conditioning, RR = Selective Signaling Arrangement

Rule 4: When the REQTYP is A (Designed Loops) and the ACT is T or W, the NCI code must match the NCI code values of the loop on the existing CSR.

Rule 5: When the REQTYP is A (Designed Loops) and the ACT is D, the NCI code must match the NCI code values of the Loop being disconnected.

Rule 6: For REQTYP B - EELS the [SPEC / NC / NCI / SECNCI] combination must be one of the following to request EELS: [UNCVX / LY-- / 04QB9.11 / 02LS2] or [UNCVX / LY-- / 04QB9.11 / 02GS2]

Rule 7: The NCI field cannot be changed on a supplement.

Electronic

Rule <u>8</u>: [Bulk Single LSR Arrangement] The same NCI and SECNCI for all Loops is required.

Rule <u>9</u>: For REQTYP B - EELS ordered in the Single LSR BULK Arrangement the [SPEC / NC / NCI / SECNCI] combination must be one of the following to request EELS: [UNCVX / LY-- / 04QB9.11 / 02LS2] or [UNCVX / LY-- / 04QB9.11 / 02GS2]

Deleted: 7

Deleted:	8
	~



SECNCI

Secondary Network Channel Interface Code (LSR Page)

Definition

Identifies the electrical conditions on the circuit at the secondary ACTL or end user location.

Definition Notes

None

Valid Entries

SECNCI Code format:

This field consists of up to a twelve character code where the:

First two numeric characters (position 1 and 2) are required and represent the physical conductors, which describe the number of wires that traverse the secondary ACTL or end user location.

Next two alpha characters (position 3 and 4) are required and identify signaling and/or transmission characteristics.

Next alpha/numeric character (position 5) is required and describes the impedance with which the customer / end user will terminate the channel for the purpose of evaluating transmission performance or to indicate if the circuit is fiber.

Next character (position 6) is a period (used as a delimiter) only if additional characters will follow.

Next three alpha / numeric (position 7, 8, and 9) describe the protocol options.

Next character (position 10) is a period (used as a delimiter) only if additional characters will follow.

Next alpha character (position 11) describes the transmission level to be received at the customer / end user interface from the provider.

Next alpha character (position 12) describes the transmission level to be transmitted from the customer / end user interface to the provider.

Valid Entry Notes

None

Data Characteristics

Minimum of 5 alpha/numeric characters and a Maximum of 12 alpha/numeric characters

Examples

02L02 (This example indicates an open end of loop start circuit at end user location.) 02LS2 (This example indicates closed end of loop start circuit at end user location.)



Conditional Usage Notes

Note 1: When the REQTYP is A this field is: Prohibited when the 4th character of the NC code is M; Prohibited when the NC code begins with TY or TX; Otherwise required.

Note 2: Required when the REQTYP is B and the NCI field is populated.

Business Rules

Rule 1: When the REQTYP is A (Designed Loops) and the ACT is T or W, the SECNCI code must match the SECNCI code values of the loop on the existing CSR.

Rule 2: When the REQTYP is A (Designed Loops) and the ACT is D, the SECNCI code must match the SECNCI code values of the Loop being disconnected.

Rule 3: For REQTYP B - EELS the [SPEC / NC / NCI / SECNCI] combination must be one of the following to request EELS: [UNCVX / LY-- / 04QB9.11 / 02LS2] or [UNCVX / LY-- / 04QB9.11 / 02GS2]

Rule 4: The SECNCI field cannot be changed on a supplement.

Electronic

Rule **5**: [Bulk Single LSR Arrangement] When requesting Designed Loops, the same NCI and SECNCI for all Loops is required.

Rule <u>6</u>: For REQTYP B - EELS ordered in the Single LSR BULK Arrangement the [SPEC / NC / NCI / SECNCI] combination must be one of the following to request EELS: [UNCVX / LY-- / 04QB9.11 / 02LS2] or [UNCVX / LY-- / 04QB9.11 / 02GS2]

Deleted: <mark>4</mark>
Deleted: 5
Deleted: 5



EAN

Existing Account Number (EU Page)

Definition

Identifies the End User's existing account number assigned by the current NSP. It is a non-dialable, non-standard number (e.g., miscellaneous account number).

Definition Notes

None

Valid Entries

None

Valid Entry Notes

None

Data Characteristics

Electronic 10 or 13 alpha/numeric characters

Manual 10 or 13 alpha/numeric characters

Examples

Electronic 404M231234 404M231234123

Manual 404-M23-1234 404-M23-1234-123

Conditional Usage Notes

Note 1: Required when the EATN, LEATN or LEAN field is not populated, and the ACT field is V.

Note 2: Prohibited when EATN, LEATN or LEAN is populated.

BELLSOUTH[®]

Note 3: Required when the EATN is not populated, and request is to change the telephone number(s) published in the Directory when no provisioning required [REQTYP=J/ ACT=R].

Note 4: Required when the REQTYP is N, and the ACT is V, and the EATN field is not populated.

Manual

Note 5: Excluding (REQTYP A Non-Design Loops and Line Share/Line Splitting) this field is required when the EATN is not populated and the request is to change the CABS Billing

Account Number (BAN) for REQTYP A designed loops and the ACT is C.

Note 6: Prohibited when the NATN field is populated.

Business Rules

Rule 1: When the REQTYP= A (Designed Loops) and the ACT = W, the system will validate that the EAN provided is a valid working CABS account.

Rule 2: When the REQTYP= A (Designed Loops), and the ACT = W, the data in the EAN field cannot match the data in the AN field.

Rule 3: When the REQTYP= A (Non-Designed Loops) and the ACT = W, then the first 10 characters of the EAN field must match the first 10 characters of the AN field regardless of the total number of characters.

Rule 4: LEATN, LEAN, EAN and EATN are mutually exclusive and may not appear in any combination on the LSR request.

Rule 5: The EAN field cannot be changed on a supplement.

Formatted: Font: Bold



EATN

Existing Account Telephone Number (EU Page)

Definition

Identifies the End User's existing account telephone number assigned by the current NSP. It is a dialable telephone number.

Definition Notes

None

Valid Entries

None Valid Entry Notes

None

Data Characteristics

Electronic 10 numeric characters

Manual 10 numeric characters (excluding 2 optional hyphens)

Examples

Electronic 2015552000

Manual 2105555200 210-555-5200

Conditional Usage Notes

Note 1: Prohibited when EAN, LEAN or LEATN is populated.

Note 2: Required when the LEAN, LEATN or EAN are not populated and ACT is V.

Note 3: Required when the EAN is not populated, and request is to change the telephone number(s) published in the Directory when no provisioning required [REQTYP=J/ACT=R].

BELLSOUTH[®]

Attachment SN91086065

Note 4: Required when REQTYP is A and ACT is V, conversion from dial tone to EELs.

Note 5: Required when the REQTYP is N and the ACT is V and the EAN field is not populated.

Note 6: Prohibited when ACT = N.

Note 7: When a Wireless Type 1 Provider requests a Port In on a REQTYP C, NPT is D, EATN must not be populated.

Note 8: When REQTYP = J, ACT = R, EATN is prohibited when EUMI = Y.

Electronic

Note 9: Required when the NATN field on the LSR is populated and the ACT=V.

Note 10: Prohibited when the NATN field is populated and the ACT=C.

Note 11: Required when the NAN field is populated.

Business Rules

Rule 1: When porting type 1 wireless numbers, for WLNP LSRs, the EATN and the PORTED TN values must not be the same.

Rule 2: When the request is REQTYP E (Non-Complex) or M (Switched Combination RES/BUS) with ACT of V and the request is to migrate and change the class of service from business to residence the EATN field must not match the ATN field.

Rule 3: LEATN, LEAN, EAN and EATN are mutually exclusive and may not appear in any combination on the LSR request.

Rule 4: When REQTYP = J and ACT = V or W, the EATN must match the ATN.

Rule 5: The EATN field cannot be changed on a supplement.

Electronic

Rule <u>6</u>: When NAN is populated, the number populated in the EATN field must be migrating to another account or disconnected in conjunction with the migration request.

Deleted: 5

BELLSOUTH®

Attachment SN91086065

CCP 2361 Attachment Listed Below

CRB: 4861 CCP: 2361 Release: 22.0A MAP: ELMS10 EU Data Dictionary.

EUA

End User Activity (EU Page)

Definition

Identifies the activity at a location when multiple end user locations exist for a service.

Definition Notes

None

Valid Entries

A = Add new location B = Recap existing location C = Changes at existing location D = Remove an existing location

Valid Entry Notes

Manual

Note 1: C is the only valid value for this field when the REQTYP is E, M or N with ACT of R when the request is submitted for address correction.

Data Characteristics

1 alpha character

Examples

A

Conditional Usage Notes

Manual



Note 1: Required when the MEU field on the LSR is populated.	 Deleted: , otherwise prohibited.

Note 2: Prohibited when the REQTYP is A, and the 2nd character of the TOS is P or R.

Note 3: Prohibited when the REQTYP is N and the 2nd character of the TOS is Q and the ACT is V or W.

Note 4: Prohibited when the REQTYP is E and the 2nd character of the TOS is H and the ACT is V.

Note 5: Prohibited for REQTYP B or C.

Note 6: Required when the REQTYP is E, M or N with ACT of R when the request is submitted for address correction.

Business Rules

None

Page 11: [1] Deleted	Licensed User	3/22/2006 10:50 AM
RJM4X, RJ1DC, RJ2EX		
<u>Electronic</u>		
Note 2: When an LSR is su	ubmitted electronically for REQTY	P A with LNAs of N, C, T
or V, where		
Page 11: [2] Deleted	Licensed User	3/22/2006 10:50 AM
service types are: Analog V	Voice Non-Designed, Analog Voic	e Designed, Enhanced
Page 11: [3] Deleted	Licensed User	3/22/2006 10:50 AM
Extended Links (EELS), U	CL - (2W) Non-Designed; the NII	OR field is populated with
Ϋ́,		
Page 11: [4] Deleted	Licensed User	3/22/2006 10:50 AM
the JK CODE (Jack Code)	field must be submitted with the fe	ollowing:
Voice Jack Type USOCs: 1	RJ11C, RJ11W, RJ11D, RJ14C, R	J14W, RJ1DC, RJ12C,
RJ12W, RJ13C, RJ13W, <mark>R</mark>	J17C, RJ18C, RJ18W, RJ19C, RJ	<mark>19W, RJ25C, RJ61X,</mark>
<mark>RJ31X,</mark>		
Page 11: [5] Deleted	Licensed User	3/22/2006 10:50 AM
RJ21X		
Note 3: When an LSR is su	ubmitted electronically for REQTY	P A with LNAs N, C, T or
V, where		
Page 11: [6] Deleted	Licensed User	3/22/2006 10:50 AM
service types are: Digital D	Data Designed (DS0), Digital Data	Designed (DS1), Digital
Page 11: [7] Deleted	Licensed User	3/22/2006 10:50 AM
Designed Basic Rate ISDN	I, Universal Digital Channel (UDC), ADSL (2W) Designed,
HDSL		
Page 11: [8] Deleted	Licensed User	3/22/2006 10:50 AM
(2W) Designed, HDSL (4W	N) Designed, UCL - Short (2W) D	esigned, UCL - Long (2W)
Page 11: [9] Deleted	Licensed User	3/22/2006 10:50 AM
Designed, UCL - Short (4)	W) Designed, UCL - Long (4W) De	esigned; and NIDR field is
Page 11: [10] Deleted	Licensed User	3/22/2006 10:50 AM
populated with 'Y', the JK	CODE field must be submitted wi	th the following: Data Jack
Page 11: [11] Deleted	Licensed User	3/22/2006 10:50 AM
Type USOCs: RJ14Q, RJ4	1Z, RJ45Q, RJ45Z, RJ16X, RJ48Z	, RJ41S, RJ45S, RJ26X,
Page 11: [12] Deleted		3/22/2006 10:50 AM
RJ26S RJ27X RJ48C RL	48H RJ48M RJ48S RJ48T RJ48	X RJM3X RIM4X
RJ26S,		
Page 11: [13] Deleted	licensed liser	3/22/2006 10·50 AM
RJ21X		5, 22, 2000 10.50 AM
x xy an 1 / 3		
Manual		

Page 11: [14] DeletedLicensed User3/22/2006 10:50 AMNote 4: When an LSR is submitted manually for REQTYP A with LNAs of N, C, T or V,
where

Page 11: [15] Deleted	Licensed User	3/22/2006 10:50 AM
service types are: Analog Voice	e Non-Designed, Analog Voi	ce Designed, Enhanced
Page 11: [16] Deleted	Licensed User	3/22/2006 10:50 AM
Extended Links (EELS), UCL -	- (2W) Non-Designed; the NI	DR field is populated with
<mark>'Y',</mark>		
Page 11: [17] Deleted	Licensed User	3/22/2006 10:50 AM
the JK CODE (Jack Code) field	l must be submitted with the	following:Data Jack Type
Page 11: [18] Deleted	Licensed User	3/22/2006 10:50 AM
USOCs: RJ14Q, RJ41Z, RJ45Q	<mark>), RJ45Z, RJ16X, RJ48Z, RJ</mark> 4	<mark>41S, RJ45S, RJ26X, RJ26S,</mark>
Page 11: [19] Deleted	Licensed User	3/22/2006 10:50 AM
<mark>RJ27X, RJ48C, RJ48H, RJ48M</mark>	I, RJ48S, RJ48T, RJ48X, RJ1	M3X, RJM4X, RJ26S,
RJ21X		
Noto 5: When on LOD is sub-	ttad manually for DEOTVD	with INA N. C. T. or W.
where service types are: Digital	Data Designed (DS0), Digi	tal Data Designed (DS1)
Digital Designed	Data, Designed (DSU), Digi	iai Data, Designeu (DS1),
Digital Designed		2/22/2006 10-50 AM
Basic Rate ISDN Universal Di	gital Channel (UDC) ADSL	(2W) Designed HDSL (2W)
Dage 11: [21] Deleted		2/22/2006 10:50 AM
Designed HDSL (4W) Designed	-d UCL - Short (2W) Design	ed UCL - Long (2W)
Designed, IDSE (4W) Design		icu, OCL Long (211)
Page 11, [22] Deleted		
	Licensed User	3/22/2006 10:50 AM
UCL - Short (4W) Designed, U	Licensed User CL - Long (4W) Designed; a	3/22/2006 10:50 AM and NIDR field is populated
UCL - Short (4W) Designed, U with	Licensed User ICL - Long (4W) Designed; a	3/22/2006 10:50 AM and NIDR field is populated
VCL - Short (4W) Designed, U with Page 11: [23] Deleted	Licensed User CL - Long (4W) Designed; a Licensed User	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM
VCL - Short (4W) Designed, U with Page 11: [23] Deleted 'Y', the JK CODE field must b	Licensed User ICL - Long (4W) Designed; a Licensed User e submitted with the followin	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs:
Page 11: [22] Deleted UCL - Short (4W) Designed, U with Page 11: [23] Deleted 'Y', the JK CODE field must b Page 11: [24] Deleted	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM
VCL - Short (4W) Designed, U with Page 11: [23] Deleted 'Y', the JK CODE field must b Page 11: [24] Deleted RJ11C, RJ11W, RJ11D, RJ14C	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followir Licensed User C, RJ14W, RJ1DC, RJ12C, R	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W,
VCL - Short (4W) Designed, U with Page 11: [23] Deleted 'Y', the JK CODE field must b Page 11: [24] Deleted RJ11C, RJ11W, RJ11D, RJ14C Page 11: [25] Deleted	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM
VCL - Short (4W) Designed, U with Page 11: [23] Deleted 'Y', the JK CODE field must b Page 11: [24] Deleted RJ11C, RJ11W, RJ11D, RJ14C Page 11: [25] Deleted RJ17C, RJ18C, RJ18W, RJ19C	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM (31X, RJ21X
Page 11: [22] Deleted UCL - Short (4W) Designed, U with Page 11: [23] Deleted 'Y', the JK CODE field must b Page 11: [24] Deleted RJ11C, RJ11W, RJ11D, RJ14C Page 11: [25] Deleted RJ17C, RJ18C, RJ18W, RJ19C Page 11: [26] Formatted	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM (31X, RJ21X) 3/22/2006 10:50 AM
Page 11: [22] Deleted UCL - Short (4W) Designed, U with Page 11: [23] Deleted 'Y', the JK CODE field must b Page 11: [24] Deleted RJ11C, RJ11W, RJ11D, RJ14C Page 11: [25] Deleted RJ17C, RJ18C, RJ18W, RJ19C Page 11: [26] Formatted Font: Not Italic, Font color: Red	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followir Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User d	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 3/22/2006 10:50 AM
Page 11: [22] DeletedUCL - Short (4W) Designed, UwithPage 11: [23] Deleted'Y', the JK CODE field must bPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [25] DeletedRJ17C, RJ18C, RJ18W, RJ19CPage 11: [26] FormattedFont: Not Italic, Font color: RealPage 13: [27] Deleted	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User d Licensed User	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 3/22/2006 10:50 AM
Page 11: [22] Deleted UCL - Short (4W) Designed, U with Page 11: [23] Deleted 'Y', the JK CODE field must b Page 11: [24] Deleted RJ11C, RJ11W, RJ11D, RJ14C Page 11: [25] Deleted RJ17C, RJ18C, RJ18W, RJ19C Page 11: [26] Formatted Font: Not Italic, Font color: Red Page 13: [27] Deleted Note 1: The following USOCs and the second seco	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followir Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User d Licensed User are valid for all other REQTY	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 3/22/2006 10:50 AM 3/22/2006 10:51 AM YP B (INP or LNP) products
Page 11: [22] DeletedUCL - Short (4W) Designed, UwithPage 11: [23] Deleted'Y', the JK CODE field must bPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [25] DeletedRJ17C, RJ18C, RJ18W, RJ19CPage 11: [26] FormattedFont: Not Italic, Font color: RealPage 13: [27] DeletedNote 1: The following USOCs anot listed in	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User d Licensed User are valid for all other REQTY	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 3/22/2006 10:50 AM 3/22/2006 10:51 AM YP B (INP or LNP) products
Page 11: [22] DeletedUCL - Short (4W) Designed, UwithPage 11: [23] DeletedY', the JK CODE field must bPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [25] DeletedRJ17C, RJ18C, RJ18W, RJ19CPage 11: [26] FormattedFont: Not Italic, Font color: RedPage 13: [27] DeletedNote 1: The following USOCs and listed inValid Entry Notes 2, 3, 4, & 5:	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User d Licensed User are valid for all other REQTY RJ11C, RJ11W, RJ11D, RJ1	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 3/22/2006 10:50 AM 3/22/2006 10:51 AM YP B (INP or LNP) products 4C, RJ14W, RJ12C, RJ12W,
Page 11: [22] DeletedUCL - Short (4W) Designed, UwithPage 11: [23] Deleted'Y', the JK CODE field must bPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [25] DeletedRJ17C, RJ18C, RJ18W, RJ19CPage 11: [26] FormattedFont: Not Italic, Font color: RealPage 13: [27] DeletedNote 1: The following USOCs anot listed inValid Entry Notes 2, 3, 4, & 5:RJ13C, RJ13W, RJ17C, RJ18C	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User d Licensed User are valid for all other REQTY RJ11C, RJ11W, RJ11D, RJ1 C, RJ18W, RJ19C, RJ19W, R	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 3/22/2006 10:50 AM 3/22/2006 10:51 AM YP B (INP or LNP) products 4C, RJ14W, RJ12C, RJ12W, J25C, RJ61X, RJ31X,
Page 11: [22] Deleted UCL - Short (4W) Designed, U with Page 11: [23] Deleted 'Y', the JK CODE field must b Page 11: [24] Deleted RJ11C, RJ11W, RJ11D, RJ14C Page 11: [25] Deleted RJ17C, RJ18C, RJ18W, RJ19C Page 11: [26] Formatted Font: Not Italic, Font color: Real Page 13: [27] Deleted Note 1: The following USOCs and listed in Valid Entry Notes 2, 3, 4, & 5: RJ13C, RJ13W, RJ17C, RJ18C RJ32X, PL32Y, PL34Y, PL35Y, PL36Y	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User d Licensed User are valid for all other REQTY RJ11C, RJ11W, RJ11D, RJ1 C, RJ18W, RJ19C, RJ19W, R	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 3/22/2006 10:50 AM 3/22/2006 10:51 AM 7P B (INP or LNP) products 4C, RJ14W, RJ12C, RJ12W, J25C, RJ61X, RJ31X,
Page 11: [22] DeletedUCL - Short (4W) Designed, UwithPage 11: [23] Deleted'Y', the JK CODE field must bPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [25] DeletedRJ17C, RJ18C, RJ18W, RJ19CPage 11: [26] FormattedFont: Not Italic, Font color: RealPage 13: [27] DeletedNote 1: The following USOCs anot listed inValid Entry Notes 2, 3, 4, & 5:RJ13C, RJ13W, RJ17C, RJ18CRJ32X,RJ33X, RJ34X, RJ35X, RJ36XP11M	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User d Licensed User are valid for all other REQTY RJ11C, RJ11W, RJ11D, RJ1 C, RJ18W, RJ19C, RJ19W, R C, RJ37X, RJ38X, RJ71C, RJ2	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 3/22/2006 10:50 AM 3/22/2006 10:51 AM (P B (INP or LNP) products 4C, RJ14W, RJ12C, RJ12W, J25C, RJ61X, RJ31X, 2EM, RJ2FM, RJ2MZ,
Page 11: [22] DeletedUCL - Short (4W) Designed, UwithPage 11: [23] DeletedY', the JK CODE field must bPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [25] DeletedRJ17C, RJ18C, RJ18W, RJ19CPage 11: [25] DeletedRJ17C, RJ18C, RJ18W, RJ19CPage 11: [26] FormattedFont: Not Italic, Font color: RealPage 13: [27] DeletedNote 1: The following USOCs anot listed inValid Entry Notes 2, 3, 4, & 5:RJ13C, RJ13W, RJ17C, RJ18CRJ33X, RJ34X, RJ35X, RJ36XRJ21M,RI2DM, RI2GM, RI2HM, RI2	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User d Licensed User are valid for all other REQTY RJ11C, RJ11W, RJ11D, RJ1 C, RJ18W, RJ19C, RJ19W, R C, RJ37X, RJ38X, RJ71C, RJ2 2X, RJ23X, RJ24X, RJ21X	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 3/22/2006 10:50 AM 3/22/2006 10:51 AM (P B (INP or LNP) products 4C, RJ14W, RJ12C, RJ12W, J25C, RJ61X, RJ21X, 2EM, RJ2FM, RJ2MZ, R I2DX, R I2FX, R I2HX
Page 11: [22] DeletedUCL - Short (4W) Designed, UwithPage 11: [23] Deleted'Y', the JK CODE field must bPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [25] DeletedRJ17C, RJ18C, RJ18W, RJ19CPage 11: [25] DeletedRJ17C, RJ18C, RJ18W, RJ19CPage 11: [26] FormattedFont: Not Italic, Font color: RedPage 13: [27] DeletedNote 1: The following USOCs anot listed inValid Entry Notes 2, 3, 4, & 5:RJ13C, RJ13W, RJ17C, RJ18CRJ32X,RJ33X, RJ34X, RJ35X, RJ36XRJ20M, RJ2GM, RJ2HM, RJ2RJ2GX.	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User d Licensed User are valid for all other REQTY RJ11C, RJ11W, RJ11D, RJ1 C, RJ18W, RJ19C, RJ19W, R C, RJ37X, RJ38X, RJ71C, RJ2 2X, RJ23X, RJ24X, RJ21X,	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 31X, RJ21X 3/22/2006 10:50 AM 3/22/2006 10:51 AM (P B (INP or LNP) products 4C, RJ14W, RJ12C, RJ12W, J25C, RJ61X, RJ21X, 2EM, RJ2FM, RJ2MZ, RJ2DX, RJ2FX, RJ2HX,
Page 11: [22] DeletedUCL - Short (4W) Designed, UwithPage 11: [23] DeletedY', the JK CODE field must bPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [24] DeletedRJ11C, RJ11W, RJ11D, RJ14CPage 11: [25] DeletedRJ17C, RJ18C, RJ18W, RJ19CPage 11: [26] FormattedFont: Not Italic, Font color: RealPage 13: [27] DeletedNote 1: The following USOCs anot listed inValid Entry Notes 2, 3, 4, & 5:RJ13C, RJ13W, RJ17C, RJ18CRJ33X, RJ34X, RJ35X, RJ36XRJ2DM, RJ2GM, RJ2HM, RJ2RJ2GX,RJ41Q, RJ41Z, RJ45Z, RJ45O.	Licensed User CL - Long (4W) Designed; a Licensed User e submitted with the followin Licensed User C, RJ14W, RJ1DC, RJ12C, R Licensed User C, RJ19W, RJ25C, RJ61X, RJ Licensed User d Licensed User are valid for all other REQTY RJ11C, RJ11W, RJ11D, RJ1 C, RJ18W, RJ19C, RJ19W, R C, RJ37X, RJ38X, RJ71C, RJ 2X, RJ23X, RJ24X, RJ21X, , RJ16X, RJ48Z, RJ41S, RJ4	3/22/2006 10:50 AM and NIDR field is populated 3/22/2006 10:50 AM ag: Voice Jack Type USOCs: 3/22/2006 10:50 AM J12W, RJ13C, RJ13W, 3/22/2006 10:50 AM 3/22/2006 10:50 AM 3/22/2006 10:51 AM (P B (INP or LNP) products 4C, RJ14W, RJ12C, RJ12W, J25C, RJ61X, RJ12C, RJ12W, J25C, RJ61X, RJ21X, 2EM, RJ2FM, RJ2MZ, RJ2DX, RJ2FX, RJ2HX, 5S, RJ26X, RJ26S, RJ27X.

RJM3X, RJM4X, RJ1DC, RJ2EX

<u>Electronic</u>

Note 2: When an LSR is submitted electronically for REQTYP B (LNP) with LNAs of N, or V, where service types are: LNP - Designed Analog Loop, LNP - Non-Designed Analog Loop, LNP UCL-ND, LNP - EELS, the NIDR field is populated with 'Y', the JK CODE (Jack Code) field

 Page 13: [28] Deleted
 Licensed User
 3/22/2006 10:51 AM

 RJ19C, RJ19W, RJ25C, RJ61X, RJ31X, RJ21X

Note 3: When an LSR is submitted electronically for REQTYP B (LNP) with LNAs N, or V, where

 Page 13: [29] Deleted
 Licensed User
 3/22/2006 10:51 AM

 RJ48C, RJ48H, RJ48M, RJ48S, RJ48T, RJ48X, RJM3X, RJM4X, RJ26S, RJ21X
 3/22/2006 10:51 AM

<u>Manual</u>

Note 4: When an LSR is submitted manually for REQTYP B (INP and LNP) with LNAs of N, or V,

Page 13: [30] DeletedLicensed User3/22/2006 10:51 AMINP UCL-ND, LNP - Designed Analog Loop, LNP - Non-Designed Analog Loop, LNPUCL-ND, LNP - EELS; the NIDR field is populated with 'Y', the JK CODE (Jack Code)field

Page 13: [31] DeletedLicensed User3/22/2006 10:51 AMmust be submitted with the following: Data Jack Type USOCs: RJ14Q, RJ41Z,RJ45Q,RJ45Z, RJ16X, RJ48Z, RJ41S, RJ45S, RJ26X, RJ26S, RJ27X, RJ48C, RJ48H,RJ48M,

Page 13: [32] DeletedLicensed UserRJ48S, RJ48T, RJ48X, RJM3X, RJM4X, RJ26S, RJ21X

3/22/2006 10:51 AM

Note 5: When an LSR is submitted manually for REQTYP B (INP and LNP) with LNAs N, or V,