

**BellSouth Business Markets** 675 West Peachtree Street Atlanta, Georgia 30375

# Carrier Notification SN91086195

Date: August 30, 2006

To: Competitive Local Exchange Carriers (CLEC)

Subject: CLECs – (Documentation/Guides) - Update to the BellSouth Local Ordering Handbook (LOH) Version 23.0A, New Local Service Ordering Guide 10 (LSOG 10) and EDI Local Mechanization Specifications 10 (ELMS 10) for Release 23.0

This is to advise that BellSouth will implement the following changes to update documentation in the LOH Version 23.0A ELMS10 for Release 23.0.

CCP Number	Description Of The Change
2418	Remove 'Combining REQTYP CB and BB when NPT = D' and add "Handling Accounts that contain numbers with and without facilities" information in the General Local Service Ordering Information chapter in Section 3: Ordering of the LOH.

Please refer to the attachments for specific details of the changes listed above.

These changes will be reflected in the next update of the ELMS 10 Release 23.0/LOH Version 23.0B, scheduled to be posted on Friday, September 29, 2006.

A summary of all changes within this document will be listed in the Summary of Changes section.

This update can be found on the BellSouth Interconnection Services Web site in the Local Exchange Ordering Guides (LEO) at:

http://interconnection.bellsouth.com/reference library/guides/html/leo.html#loh

Please contact your BellSouth local support manager with any questions.

Sincerely,

#### **ORIGINAL SIGNED BY KRISTEN E. SHORE**

Kristen E. Shore – Director Business Markets

Attachments



ELMS 10, Release 23.0

### CCP 2418 Attachment Listed Below

Handling Accounts that contain numbers with and without facilities (Formerly Combining REQTY CB and BB when NPT = D)

Combining REQTY CB and BB when NPT = D is no longer valid for ordering within BellSouth. See Carrier Notification <u>SN91086168</u> dated August 8, 2006 indicating that leading zeros are prohibited for the CHAN/PAIR and CHAN/PAIR 2 fields of the LSNP Form/Screen.

#### **Definition:**

This process provides information for Handling Accounts that contain numbers with and without facilities. The most common scenario is a request to port out an account that includes a Ringmaster number. Since there is not a loop associated with the Ringmaster, the porting request cannot be included on the LSR to port out the main telephone number with loop unless the CLEC wants to disconnect the Ringmaster number.

Due to porting situation in which TNs with no facilities (i.e. Ringmaster, Remote Call forwarding etc...) result in leading zeros being prohibited for the CHAN/PAIR and CHAN/PAIR 2 fields of the LSNP Form/Screen. A REQTYP C must be sent in to handle the ringmaster portion and a subsequent REQTYP B should be sent to port the Account Number with a UNE Loop as desired.

#### **Ordering Considerations:**

To Port Ringmaster:

• REQTYP: C

• ACTTYP: V

• MI: A, B

• LNA: V

• R/C/O Tables: Follow and use the appropriate REQTYP C Product Guidelines

For Porting the Main Account Telephone Number and requesting UNE Loop • REQTYP: B

• ACTTYP: V



#### • MI: C

• LNA: V

• R/C/O Tables: Follow and use the appropriate REQTYP B Product Guidelines

#### Service Restrictions:

None

#### LSR Restrictions:

The following section provides detail information to assist you in filling out certain fields on LSR

The following information must be entered on the loop service with number portability tab:

Porting telephone number LNA=V Cable ID and Chan Pair for loop

Service Order Restrictions: None

Tariff Reference: None

USOC / FID References: None

Situations / Exhibits: None

**Related Topics / Information:** 

None

#### <del>Definition:</del>

Provides a LNP work around process for combining REQTYP CB and BB using a single LSR when the NPT=D. The LNP GUI will not accept fax or electronic (EDI/TAG) Issue 9 or ELMS6 LSRs unless each LNUM includes cable ID and channel pair.

The most common scenario for combining REQTYP CB and BB is a request to port out an account that includes a Ringmaster number. Since there is not a loop associated with the Ringmaster, the porting request cannot be included

## **BELLSOUTH**<sup>®</sup>

Attachment SN91086195

on the LSR to port out the main telephone number with loop unless the CLEC wants to disconnect the Ringmaster number

Ordering Considerations:

<mark>● REQTYP: B</mark>

• ACTTYP: V

• <del>MI: A, B, C, D</del>

• LNA: V

• R/C/O Tables: Follow and use the appropriate REQTYP B Product Guidelines

#### Service Restrictions:

None

#### LSR Restrictions:

The following section provides detail information to assist you in filling out certain fields on LSR

The following information must be entered on the loop service with number portability tab:

Porting telephone number LNA=V Cable ID and Chan Pair for loop

The information for the telephone number porting out without loop is entered on the loop service with number portability tab:

Porting telephone number(Ringmaster) LNA=∨ Cable ID= P000 or V000 Chan Pair= 000

<del>Service Order Restrictions:</del> None

<del>Tariff Reference:</del> None

<del>USOC / FID References:</del> <sup>None</sup>



Attachment SN91086195

## <del>Situations / Exhibits:</del>

None

Related Topics / Information:

None