



Date: May 7, 2007			Number:	SN91087081		
Effective Da	ate: In	nmediately	Category:	oss		
Subject: CLECs - (Documentation/Guides) - Update to the Local Ordering Handbook (LOH), Version 24.0D, New Local Service Ordering Guide 6 (LSOG 6) and EDI Local Mechanization Specifications 06 (ELMS 06) for Release 24.0						
Related Lett	ters: N	Α	Attachmer	nt: YES		
States Impacted: Alabama, Florida, Georgia, Kentucky, Louisiana, Mississippi, North Carolina, South Carolina and Tennessee						
Issuing ILECS: AT&T Alabama, AT&T Florida, AT&T Georgia, AT&T Kentucky, ALouisiana, AT&T Mississippi, AT&T North Carolina, AT&T South AT&T Tennessee (collectively referred to for purposes of this Acceletter as "AT&T Southeast Region")				orth Carolina, AT&T South Carolina,		
Response Deadline:		e: NA	Contact:	ocal Support Manager		

The AT&T Southeast Region will implement the following changes to update documentation in the LOH Version 24.0D, ELMS 06 for Release 24.0.

CCP Number	Description Of The Change		
2490	Move RESID field REQ B, ACT = V, INP & LNP (UCL-ND) R/C/O tables: This request is to move the RESID field from 'Required' to 'Optional' (row).		
2491	IWT field for RS-Resale Service and PS-Port Service (Forms/Screens): Add Business Rule that reads "When IWT is populated with a valid entry of A or B then the applicable non-basic USOC is required in the feature field."		

Please refer to the attachments for specific details of the changes listed above.

These changes will be reflected in the next update of the ELMS 06, Release 24.0/LOH Version 24.0E, scheduled to be posted on Friday, May 25, 2007.

A summary of all changes within this document will be listed in the **Summary of Changes** section.

This update can be found on the AT&T Southeast Wholesale Web site in the Local Exchange Ordering (LEO) Guides at:

http://interconnection.bellsouth.com/reference_library/guides/html/leo.html#loh

Please contact your AT&T local support manager with any questions.

AT&T reserves the right to make any modifications to the information set forth herein and/or to cancel the information set forth herein. In the event of any modifications to or cancellation of the information set forth herein, CLECs will be notified via a subsequent Accessible Letter. AT&T shall incur no liability to any CLEC if the information set forth herein is modified or cancelled by AT&T.



CCP 2490 Attachment Listed Below

24.0-ELMS06

ACT Tables: Regtyp B, INP, Unbundled Copper Loop - Non-Designed (UCL-ND)

ACT= V: LSR

Required

ACNA (M) ACT (M) ACTL (M) AN (M) ATN (M) BAN1 (M) BAN2 (M) BI1 (M) BI2 (M) CC (M) CCNA (M) CIC (M) D/TSENT (M) IMPCON (M) DDD (M) IMPCON-TEL NO. (M) INIT (M) INIT-FAX NO. (M)

 INIT-TEL NO. (M)
 LSO (M)
 MI (M)

 NC (M)
 PG_OF_ (M)
 PON (M)

 REQTYP (M)
 RESID (M)
 SC (M)

TOS (M)

Optional

ALT-IMPCON* (M) CHC (M) CNO (M)

 $\mathsf{DRC}^*\left(\mathsf{M}\right)$ $\mathsf{EXP}\left(\mathsf{M}\right)$ LSP AUTH $\mathsf{NAME}\left(\mathsf{M}\right)$

REMARKS (M) RORD (M) SLI (M)

RESID (M)

ACT Tables: Reqtyp B, LNP, Unbundled Copper Loop – Non-Designed (UCL-ND)

ACT= V: LSR

Required

ACNA ACTL
AN BAN1 BAN2
BI1 BI2 CC
CCNA CIC D/TSENT

DDD IMPCON IMPCON-TEL NO.

INIT INIT-FAX NO. INIT-TEL NO.

LSO MI NC

 PG_OF_ (M)
 PON
 REQTYP

 RESID
 SC
 TOS

Optional

ALT-IMPCON* CHC CNO

DRC* EXP LSP AUTH NAME

REMARKS RORD SLI

RESID



CCP 2491 Attachment Listed Below

CRB: 5014 CCP: 2491 MAP: ELMS06 Release: 24

PS and RS Data Dictionaries

IWT

Inside Wire Type PS Form / Screen LSOG6 / ELMS6

Definition

Identifies the type of inside wiring to be used.

Definition Notes

Note 1: This field is repeatable per LNUM.

Valid Entries

A = Plenum 4 pair or less

B = Non-Plenum 4 pair or less

C = Plenum 25 pair

D = Non Plenum 25 pair

E = Reuse and test existing wiring

Valid Entry Notes

None

Data Characteristics

1 alpha character

Examples

Α

С

Conditional Usage Notes

Note 1: Required when the IWTQ field is populated.

Note 2: Prohibited when the TOS field is not 1AM- or 1BM-. Note 3: Prohibited when the IWO field is not populated.

Note 4: For REQTYP = M, TOS = 1AM- or 1BM-, IWT is required when IWO = W. Note 5: For REQTYP = M, TOS = 1AM- or 1BM-, IWT is prohibited when IWO = S or U.

Note 6: At least one IWT is required when the IWO field is populated with W.

Business Rules

Rule 1: When IWT is populated with a valid entry of A or B then the applicable non-basic USOC is required in the feature field.



IWT

Inside Wire Type RS Form / Screen LSOG6 / ELMS6

Definition

Identifies the type of inside wiring to be used.

Definition Notes

Note 1: This field is repeatable per LNUM.

Valid Entries

A = Plenum 4 pair or less

B = Non-Plenum 4 pair or less

C = Plenum 25 pair

D = Non Plenum 25 pair

E = Reuse and test existing wiring

Valid Entry Notes

None

Data Characteristics

1 alpha character

Examples

Α

С

Conditional Usage Notes

Note 1: Required when the IWO field is populated and the 2nd character of the TOS is H.

Note 2: Prohibited when the 2nd character of the TOS is not H.

Note 3: Prohibited when the IWO field is not populated.

Business Rules

None

Rule 1: When IWT is populated with a valid entry of A or B then the applicable non-basic USOC is required in the feature field.

* * * * * * * * * End of definition for field IWT * * * * * * * *