



[Home](#) > Wholesale

## FIDS

- 28.7 Standard Selectable Features with required FIDs
- 1A Standard Selectable Features that require FID information from CLEC

Feature	USOC	FID	Format
Automatic Line/Direct Connect	M4BAC	HLN	Followed by a seven or ten digit number.  If the number is long distance the format should be a ten digit number preceded by a 1 (one).
Call Forward Don't Answer	M4NFC M4NFC CENLK M4NPF	CFND/RCYC	Consists of the actual digits the subscriber dials to reach the forward number
Call Forward Busy Line-Fixed	CENLA M4JFC	CFNB	Consists of the actual digits the subscriber dials to reach the forward number
Call Forwarding Multiple Simultaneous	M2JR4	SFG,GSZ info provided by Bellsouth	Must provide number between one (1) and ten (10), indicating the number of calls to be forwarded simultaneously. Maximum paths=ten (10)
Call Pickup	M4UBC	CPG	Indicates Group Number
Call Pickup	M4UBC	CPG	Indicates the Group Number
Speed Calling Long	M3YAA M3Y30	SCG	Floated Group Numbers one to ninety-nine (1-99) may be used

5ESS Standard Selectable Features that require FID information from the CLEC

Feature	USOC	FID	Format
Automatic Line/Direct Connect	M4BAC	HLN	Followed by a two to twenty-three characters consist of actual digits dialed.

			If the number is long distance the format should be a ten digit number preceded by a 1 (one), and separated by a comma..
Call Forward Don't Answer	M4NFC M4NFC CENLK M4NPF	CFND/RCYC	Consists of the actual digits the subscriber dials to reach the forward number
Call Forward Busy Line-Fixed	CENLA M4JFC	CFNB	Consists of the actual digits the subscriber dials to reach the forward number
Call Forwarding Multiple Simultaneous	M2JR4	SFG, GSZ info provided by Bellsouth	CLEC must provide number between two (2) and ten (10), indicating the number of calls to be forwarded simultaneously. Maximum paths=ten (10)
Call Pickup	M4UBC	CPG	Indicates Group Number. CPG can be a one or two digit number. When number is in more than one group separate group by comma.
Call Pickup	M4UBC	CPG	Indicates the Group Number can be a one or two digit number. When number is in more than one group separate group by comma.
Speed Calling Long - Per Controlling Line (30-number shared)	M3Y30	SCG	SCG - followed by TN of controlling station link
Speed Calling Long - Per Additional Line	M3YAA	SCG	
Speed Calling Long - Per Controlling Line (40-number list)	M3Y40	SCG	SCG - followed by TN of controlling station link
Speed Calling Long - Per Controlling Line (50-number list)	M3Y50	SCG	SCG - followed by TN of controlling station link
Speed Calling Long - Per Controlling Line (60-number list)	M3Y60	SCG	SCG - followed by TN of controlling station link
Speed Calling Long - Per Controlling Line		SCG	SCG - followed by TN of controlling

(70-number list)	M3Y70		station link
Speed Calling Long - Per Controlling Line	M3Y80	SCG	SCG - followed by TN of controlling station link
(80-number list)			
Station Restriction - Full Denied Origination	M5ROC	TGS <sub>2</sub>	2Station Restrictions are done showing data following the FID TGS after the station link. This data may have three elements: Character Definition FID ***1st*** Originating Station Restriction U = Unrestricted F = Fully S = Semi ***2nd *** Termination Station Restriction U = Unrestricted F = Fully S = Semi ***3rd*** Error Treatment - Optional T = Tone A = Announcement N = Overflow Number
Station Restriction - Full Denied Termination		TGS <sub>2</sub>	
Station Restriction - Full Incoming	M5LTC		
Station Restriction - Full Incoming and Outgoing	M3RC2	TGS <sub>2</sub>	
Station Restriction - Full Outgoing	M3RF2		
Station Restriction - Semi-incoming	M3RG2	TGS <sub>2</sub>	
Station Restriction - Semi-Incoming and Outgoing	M3RH2		
Station Restriction - Semi-Outgoing	M3RJ2	TGS <sub>2</sub>	
	M3RK2		
		TGS <sub>2</sub>	

DMS Standard Selectable Features that require FID information from the CLEC

Feature	USOC	FID	Format
---------	------	-----	--------

Automatic Line/Direct Connect	M4BAC	AUL	FID AUL followed by the destination number. The destination number can be an internal or external number. The FID data can be 1-23 characters. Characters * and # are not allowed.
Call Forward Don't Answer	M4NFC M4NFC CENLK M4NPF	CFND/RCYC	Consists of the actual digits the subscriber dials to reach the forward number.  RCYC can be 2-5
Call Forward Busy Line-Fixed	CENLA M4JFC	CFNB	Consists of the actual digits the subscriber dials to reach the forward number
Call Forwarding Multiple Simultaneous	M2JR4	SFG, GSZ info provided by Bellsouth	The FID CFSO is required. The values that will follow this FID is one of the codesets below  NCFU: Number of Calls to be forwarded through call forwarding variable  NCFB: Number of Calls to be forwarded through call forwarding busy  NCFD : Number of Calls to be forwarded through call forwarding don't answer.
Call Pickup	M4UBC	CPG	Indicates Group Number. CPG can be a one or two digit number. When number is in more than one group separate group by comma.
Call Pickup	M4UBC	CPG	Indicates the Group Number can be a ten digit number.
Speed Calling Long	M3YAA M3Y30	SCG	The data following will include the telephone number of the controlling station link.
Call Transfer	CENDS	CXRO(originating) ,CXRT (terminating)	Data following both FIDs are:  AC : Calls to attendant  Inter: Intergroup.

			Intra: Intragroup Trater: Inter or Intragroup NOCXFER : No Call Transfer
Call Transfer	CENDS	CXRR	The codeset following this FID is:  Y = Yes N = No  12 to 120 = # of seconds
Calling Name Display	M2NDD	CNDI	First 1-15 characters represent the calling Name

## DCO Standard Selectable Features that require FID information from CLEC

Feature	USOC	FID	Format
Automatic Line/Direct Connect	M4BAC	HLN	Followed by a seven or ten digit number.  If the number is long distance the format should be a ten digit number preceded by a 1 (one).
Call Forward Don't Answer	M4NFC M4NFC CENLK M4NPF	CFND/RCYC	Consists of the actual digits the subscriber dials to reach the forward number
Call Forward Busy Line-Fixed	CENLA M4JFC	CFNB	Consists of the actual digits the subscriber dials to reach the forward number
Call Forwarding Multiple Simultaneous	M2JR4	SFG,GSZ info provided by Bellsouth	Must provide number between one (1) and ten (10), indicating the number of calls to be forwarded simultaneously. Maximum paths=ten (10)
Call Pickup	M4UBC	CPG	Indicates Group Number
Call Pickup	M4UBC	CPG	Indicates the Group Number
Speed Calling Long	M3YAA M3Y30	SCG	Floated Group Numbers one to ninety-nine (1-99) may be used

## EWSD Standard Selectable Features that require FID information from CLEC

Feature	USOC	FID	Format
Automatic Line/Direct Connect	M4BAC	HLN	<p>Data following is actual digits dialed, 2-23 characters.</p> <p>The #(pound sign) is allowed when a customer has assumed dial 9 and the number is within the Centrex.</p> <p>A space must be between the # and TN following the FID HLN.</p> <p>A 7 digit TN is allowed within the Centrex.</p> <p>Where 9+1 is required to dial a long distance number the data must be separated by a comma following the Fid HLN.</p>
Call Forward Don't Answer	M4NFC M4NFC CENLK M4NPF	CFND/RCYC	<p>Data following must be minimum of two characters maximum of 23</p> <p>Must be a 10 digit number (Area Code, NPA,NXX)</p> <p>* and # are allowed to indicate intra-system dialing</p> <p>Must be terminal 1 in a multiline hunt group.</p> <p>In a multiline hunt group allowed on terminal 1 only</p>
Call Forward Busy Line-Fixed	CENLA M4JFC	CFNB	<p>Data following must be minimum of two characters maximum of 23</p> <p>Must be a 10 digit</p>

			<p>number (Area Code, NPA,NXX)</p> <p>* and # are allowed to indicate intra-system dialing</p> <p>Must be terminal 1 in a multilane hunt group.</p> <p>In a multilane hunt group allowed on terminal 1 only</p>
Call Forwarding Multiple Simultaneous	M2JR4	SFG,GSZ info provided by Bellsouth	<p>The GSZ is followed by a numeric character between 1 &amp; 10 indicating the number of calls to be simultaneously forwarded.</p> <p>Maximum number of paths allowed is 10.</p>
Call Pickup	M4UBC	CPG	<p>Indicates Group Number</p> <p>In a multilane hunt group cll pickup is allowed on terminal 1 only.</p>
Speed Calling Long	M3YAA M3Y30	SCG	<p>The data following SCG should be 7-10 digit TN (no hyphen)</p>

[Terms & Conditions](#) [Privacy Policy](#) [Contact Us](#)  
 © 2007 AT&T Intellectual Property. All rights reserved.

*Telcordia® and Common Language® are registered trademarks and iconectiv, CLCI, CLEI, CLFI, CLLI, USOC, FID, NC, NCI and NC/NCI, are trademarks of Telcordia Technologies, Inc. The Common Language codes identified herein are the proprietary information of Telcordia Technologies, Inc. dba as iconectiv ("iconectiv") and are licensed to AT&T Inc. The Common Language codes are provided herein solely for the purpose of this AT&T Wholesale application site and may not be reproduced, stored, or used for any other purpose without the express, written consent of iconectiv.*

[Hosted by AT&T.](#)