
BellSouth Interconnection Services

675 West Peachtree Street
Atlanta, Georgia 30375

Carrier Notification**SN91082608**

Date: September 14, 2001

To: Competitive Local Exchange Carriers (CLECs)

Subject: CLECs - Required Field Identifier (FID) Information

This is to advise that BellSouth Centrex Service has Standard Selectable Feature Uniform Service Order Codes (USOC) that require switch specific FID information for provisioning. CLECs ordering these services must provide this FID information with their initial request.

The attached table will be placed in CLEC Documentation. Once the date has been determined, notification will be provided regarding the date that the documentation will be posted at the BellSouth Interconnection Services' Web site at the following address:

<http://www.interconnection.bellsouth.com/guides/index.html>

Please contact your BellSouth account team representative with any questions.

Sincerely,

ORIGINAL SIGNED BY JIM BRINKLEY

Jim Brinkley – Senior Director
BellSouth Interconnection Services

Attachment

1A Require FID information

Feature	USOC	FID	Format
Automatic Line/ DirectConnect	M4BAC	HLN	Followed by a seven- or ten-digit number. If the number is long distance, the format should be a ten-digit number preceded by a 1.
Call Forward Don't Answer	M4NFC M4NFC CENLK M4NPF	CFND/RCYC	Consists of the actual digits the subscriber dials to reach the forward number
Call Forward Busy Line-Fixed	CENLA M4JFC	CFNB	Consists of the actual digits the subscriber dials to reach the forward number
Call Forwarding Multiple Simultaneous	M2JR4	SFG,GSZ information provided by BellSouth	Must provide number between 1 and 10, indicating the number of calls to be forwarded simultaneously. Maximum paths=10
Call Pickup	M4UBC	CPG	Indicates the Group Number

Feature	USOC	FID	Format
Call Pickup	M4UBC	CPG	Indicates the Group Number
Speed Calling Long	M3YAA M3Y30	SCG	Floated Group Numbers 1 to 99 may be used

5ESS required FID information

Feature	USOC	FID	Format
Automatic Line/ DirectConnect	M4BAC	HLN	Followed by 2 to 23 characters, consists of actual digits dialed. If the number is long distance, the format should be a ten-digit number preceded by a 1 and separated by a comma.
Call Forward Don't Answer	M4NFC M4NFC CENLK M4NPF	CFND/RCYC	Consists of the actual digits the subscriber dials to reach the forward number

Call Forward Busy Line-Fixed	CENLA M4JFC	CFNB	Consists of the actual digits the subscriber dials to reach the forward number
------------------------------	----------------	------	--

Feature	USOC	FID	Format
Call Forwarding Multiple Simultaneous	M2JR4	SFG, GSZ information provided by BellSouth	CLEC must provide number between 2 and 10, indicating the number of calls to be forwarded simultaneously. Maximum paths = 10
Call Pickup	M4UBC	CPG	Indicates Group Number. CPG can be a one or two digit number. When number is in more than one group, separate group by comma.
Call Pickup	M4UBC	CPG	Indicates the Group Number can be a one or two digit number. When number is in more than one group, separate group by comma.
Speed Calling Long	M3YAA M3Y30	SCG	Floated Group Numbers 1 to 99 may be used

DMS required FID information

Feature	USOC	FID	Format
Automatic Line/DirectConnect	M4BAC	AUL	FID AUL followed by the destination number. The destination number can be an internal or external number. The FID data can be 1 to 23 characters. Characters * and # are not allowed.
Call Forward Don't Answer	M4NFC M4NFC CENLK M4NPF	CFND/RCYC	Consists of the actual digits the subscriber dials to reach the forward number. RCYC can be 2-5
Call Forward Busy Line-Fixed	CENLA M4JFC	CFNB	Consists of the actual digits the subscriber dials to reach the forward number
Call Forwarding Multiple	M2JR4	SFG, GSZ information provided by BellSouth	The FID CFSD is required. The values that will follow

Simultaneous			<p>this FID is one of the code sets below:</p> <p>NCFU: Number of Calls to be forwarded through call forwarding variable.</p> <p>NCFB: Number of Calls to be forwarded through call forwarding busy.</p> <p>NCFD: Number of Calls to be forwarded through call forwarding doesn't answer.</p>
--------------	--	--	---

Feature	USOC	FID	Format
Call Pickup	M4UBC	CPG	Indicates Group Number. CPG can be a one or two digit number. When number is in more than one group, separate group by comma.
Call Pickup	M4UBC	CPG	Indicates Group Number can be a ten-digit number.
Speed Calling Long	M3YAA M3Y30	SCG	The data following will include the telephone number of the controlling station link.
Call Transfer	CENDS	CXRO (originating) CXRT (terminating)	Data following both FIDs are: AC: Calls to attendant Inter: Intergroup. Intra: Intragroup Trater: Inter or Intragroup NOCXFER: No Call Transfer

Feature	USOC	FID	Format
Call Transfer	CENDS	CXRR	The code set following this FID is: Y = Yes N = No 12 to 120 = number of seconds
Calling Name Display	M2NDD	CNDI	First 1 to 15 characters represent the calling Name

DCO require FID information

Feature	USOC	FID	Format
Automatic Line/ DirectConnect	M4BAC	HLN	Followed by a seven- or ten-digit number.

			If the number is long distance, the format should be a ten-digit number preceded by a 1.
Call Forward Don't Answer	M4NFC M4NFC CENLK M4NPF	CFND/RCYC	Consists of the actual digits the subscriber dials to reach the forward number
Call Forward Busy Line-Fixed	CENLA M4JFC	CFNB	Consists of the actual digits the subscriber dials to reach the forward number

Feature	USOC	FID	Format
Call Forwarding Multiple Simultaneous	M2JR4	SFG,GSZ information provided by BellSouth	Must provide number between 1 and 10, indicating the number of calls to be forwarded simultaneously. Maximum paths = 10
Call Pickup	M4UBC	CPG	Indicates the Group Number
Call Pickup	M4UBC	CPG	Indicates the Group Number
Speed Calling Long	M3YAA M3Y30	SCG	Floated Group Numbers 1 to 99 may be used

EWSD required FID information

Feature	USOC	FID	Format
Automatic Line/ DirectConnect	M4BAC	HLN	<p>Data following is actual digits dialed, 2 to 23 characters.</p> <p>The pound sign (#) is allowed when a customer has assumed dial 9 and the number is within the Centrex.</p> <p>A space must be between the # and TN following the FID HLN.</p> <p>A seven-digit TN is allowed within the Centrex.</p> <p>Where 9+1 is required to dial a long distance number, the data must be</p>

			separated by a comma following the Fid HLN.
Call Forward Don't Answer	M4NFC M4NFC CENLK M4NPF	CFND/RCYC	Data following must be minimum of 2 characters, maximum of 23 Must be a ten-digit number (Area Code, NPA, NXX) * and # are allowed to indicate intra-system dialing Must be terminal 1 in a multilane hunt group.

Feature	USOC	FID	Format
Call Forward Busy Line-Fixed	CENLA M4JFC	CFNB	Data following must be minimum of 2 characters, maximum of 23 Must be a ten-digit number (Area Code, NPA, NXX) * and # are allowed to indicate intra-system dialing Must be terminal 1 in a multilane hunt group. In a multilane hunt group allowed on terminal 1 only.
Call Forwarding Multiple Simultaneous	M2JR4	SFG,GSZ information provided by BellSouth	The GSZ is followed by a numeric character between 1 and 10, indicating the number of calls to be simultaneously forwarded. Maximum number of paths allowed is 10.
Call Pickup	M4UBC	CPG	Indicates Group Number in a multilane hunt group. Call pickup is allowed on terminal 1 only.

Feature	USOC	FID	Format
Speed Calling Long	M3YAA M3Y30	SCG	The data following SCG should be seven to ten digit TN (no hyphen)