
BellSouth Interconnection Services

675 West Peachtree Street
Atlanta, Georgia 30375

Carrier Notification**SN91083857**

Date: October 17, 2003

To: Competitive Local Exchange Carriers (CLEC) and Wireless Service Providers (WSP)

Subject: CLECs and WSP – (Documentation/Guides) - Update to the BellSouth Local Ordering Handbook (LOH) 14.0a for New Local Service Ordering Guide 6 (LSOG6) and EDI Local Mechanization Specifications 6 (ELMS6) for Release 14.0

This is to advise that BellSouth has identified the following documentation defects in the LOH 14.0a for ELMS 6 Release 14.0.

CCP Number	Description Of The Change
1103	Modifications to CCNA and CUST fields for WLNP. Also delete a business rule in the LOH under WLNP Product, Restrictions and Limitations section. Stating "Wireless Type 1 provider may not request a port from another Wireless Type 1 or BST Wireline providers's account."

Please refer to the attachments for specific details of the changes listed above.

These changes will be reflected in the next update of the TCIF9 Release 14.0/LOH Version 14.0b, scheduled to be posted November 24, 2003.

A summary of all changes within this document will be listed in the **Summary of Changes Section**. This update can be found on the BellSouth Interconnection Services' Web site in the Customer Guides Section at:

<http://www.interconnection.bellsouth.com/guides/html/leo.html>

Please contact your BellSouth Local Support Manager with any questions.

Sincerely,

ORIGINAL SIGNED BY JERRY HENDRIX

Jerry Hendrix – Assistant Vice President
BellSouth Interconnection Services

Attachments

CCP 1103 Attachment Listed Below**WLNP Modifications to the 14.0 and 15.0 LOH
Submitted by Rodney Strawter****Product Restrictions and Limitations:**

- *Directory Delivery is not applicable for WLNP*
- *If the WSP is ordering/requesting Foreign Listings associated with WLNP, they must submit a manual (faxed) LSR for processing (added 6-20-03)*
- A wireless directory number may be ported to a wireline service provider as long as the resulting wireline serving address is geographically located within the wireline rate center (TMRC) associated with the wireless directory number (NPA NXX)
- Porting from a wireless carrier to BST is limited to ports within existing TMRC as defined in the LERG (**Exception when porting from wireline to wireless Type 2 the TMRC will not be validated**).
- Wireless screening account TNs or Guide Numbers are not eligible to be ported.
- Wireless Service Request (WSR) forms are not valid when submitting a request to the LCSC. (WSR's should be submitted to the BellSouth Wireless Service Center)
- Existing LNP TN disconnect and TN reclaim industry procedures are applicable to WLNP and are found in the NPAC. (website www.npac.com)
- Wireline to Wireless-An LSR request from a wireless service provider to port out a BST wireline number authorizes BST to disconnect a wireline number (BST, Reseller or UNE-P)
- Wireless to Wireline- a request from a wireless end user customer to port into BST as a wireline number authorizes BST to disconnect the port-in number from the donor wireless carriers account.
- Wireless to wireline Port in-A request from a wireless end user customer to port into BST as a wireline number authorizes BST to establish a wireline account for the port in number (BST, Reseller or UNE-P)
- **Wireless Type 1 Provider may not request a port from another Wireless Type 1 or BST Wireline providers's account—[DELETE. This Rule 10-09-03]**

CCNA

Customer Carrier Name Abbreviation (LSR Page)

Definition Identifies the Common Language IAC code for the customer submitting the LSR and receiving confirmation.

Def Notes **NOTE1:** The format and structure of this field is defined by ANSI in document T1.251. Identification of Telecommunications Service Provider Codes for the North American Telecommunications system.

NOTE 2: For a occasional customer who has not and probably will not obtain a CCNA, enter "CUS" in this field.

NOTE 3: CCNA is not necessarily the customer to be billed for the service. The billed party should be specified in the ACNA field.

Valid Entries None

VE Notes None

Data Charact 3 alpha characters

Examples ZYX

CU Notes None

Bus Rules Rule 1: An entry of "CUS" requires an entry in the CC field.
Electronic:

Rule 2: [BULK] Required for UNE to UNE Bulk Migration.

Rule 3: When CCNA is populated with CUS, and the NNSP/CC is Wireless, then the CUST field must be populated with the Wireless Service Provider's name.

CUST

Customer Name (LSR Page)

Definition Identifies the name of the customer that originated this request when that customer has not been assigned a CCNA.

Def Notes None

Valid Entries None

VE Notes None

Data Charact Up to 25 alpha/numeric characters

Examples JOHN J SMITH CORP

CU Notes Note 1: Required when CCNA is "CUS", otherwise optional.

Bus Rules

Rule 1: When this field is populated, and the NNSP/CC field is Wireless, the data populated must be the wireless provider's name