



BellSouth Business Markets

675 West Peachtree Street
Atlanta, Georgia 30375

**Carrier Notification
SN91086194**

Date: August 30, 2006

To: Competitive Local Exchange Carriers (CLEC)

Subject: CLECs – (Documentation/Guides) - Update to the BellSouth Local Ordering Handbook (LOH) Version 23.0A, New Local Service Ordering Guide 6 (LSOG 6) and EDI Local Mechanization Specifications 06 (ELMS 06) for Release 23.0

This is to advise that BellSouth will implement the following changes to update documentation in the LOH Version 23.0A ELMS 06 for Release 23.0.

CCP Number	Description Of The Change
2418	Remove 'Combining REQ TYP CB and BB when NPT = D' and add "Handling Accounts that contain numbers with and without facilities" information in the General Local Service Ordering Information chapter in Section 3: Ordering of the LOH.

Please refer to the attachments for specific details of the changes listed above.

These changes will be reflected in the next update of the ELMS 06 Release 23.0/LOH Version 23.0B, scheduled to be posted on Friday, September 29, 2006.

A summary of all changes within this document will be listed in the **Summary of Changes** section.

This update can be found on the BellSouth Interconnection Services Web site in the Local Exchange Ordering Guides (LEO) at:

http://interconnection.bellsouth.com/reference_library/guides/html/leo.html#loh

Please contact your BellSouth local support manager with any questions.

Sincerely,

ORIGINAL SIGNED BY KRISTEN E. SHORE

Kristen E. Shore – Director
BellSouth Business Markets

Attachments

ELMS 06, Release 23.0

CCP 2418 Attachment Listed Below***Handling Accounts that contain numbers with and without facilities
(Formerly Combining REQTY CB and BB when NPT = D)***

Combining REQTY CB and BB when NPT = D is no longer valid for ordering within BellSouth. See Carrier Notification [SN91086167](#) dated August 8, 2006 indicating that leading zeros are prohibited for the CHAN/PAIR and CHAN/PAIR 2 fields of the LSNP Form/Screen.

Definition:

This process provides information for Handling Accounts that contain numbers with and without facilities. The most common scenario is a request to port out an account that includes a Ringmaster number. Since there is not a loop associated with the Ringmaster, the porting request cannot be included on the LSR to port out the main telephone number with loop unless the CLEC wants to disconnect the Ringmaster number.

Due to porting situation in which TNs with no facilities (i.e. Ringmaster, Remote Call forwarding etc...) result in **leading zeros being prohibited for the CHAN/PAIR and CHAN/PAIR 2 fields of the LSNP Form/Screen.** A REQTY C must be sent in to handle the ringmaster portion and a subsequent REQTY B should be sent to port the Account Number with a UNE Loop as desired.

Ordering Considerations:

To Port Ringmaster:

- REQTY: C
- ACTTYP: V
- MI: A, B
- LNA: V
- R/C/O Tables: Follow and use the appropriate REQTY C Product Guidelines

For Porting the Main Account Telephone Number and requesting UNE Loop

- REQTY: B

- ACTTYP: V

- MI: C

- LNA: V

- R/C/O Tables: Follow and use the appropriate REQ TYP B Product Guidelines

Service Restrictions:

None

LSR Restrictions:

The following section provides detail information to assist you in filling out certain fields on LSR

The following information must be entered on the loop service with number portability tab:

Porting telephone number

LNA=V

Cable ID and Chan Pair for loop

Service Order Restrictions:

None

Tariff Reference:

None

USOC / FID References:

None

Situations / Exhibits:

None

Related Topics / Information:

None

Definition:

Provides a LNP work-around process for combining REQ TYP CB and BB using a single LSR when the NPT=D. The LNP GUI will not accept fax or electronic (EDI/TAG) Issue 9 or ELMS6 LSRs unless each LNUM includes cable ID and channel pair.

The most common scenario for combining REQ TYP CB and BB is a request

to port out an account that includes a Ringmaster number. Since there is not a loop associated with the Ringmaster, the porting request cannot be included on the LSR to port out the main telephone number with loop unless the CLEC wants to disconnect the Ringmaster number

Ordering Considerations:

- REQ TYP: B

- ACT TYP: V

- MI: A, B, C, D

- LNA: V

- R/C/O Tables: Follow and use the appropriate REQ TYP B Product Guidelines

Service Restrictions:

None

LSR Restrictions:

The following section provides detail information to assist you in filling out certain fields on LSR

The following information must be entered on the loop service with number portability tab:

Porting telephone number

LNA=V

Cable ID and Chan Pair for loop

The information for the telephone number porting out without loop is entered on the loop service with number portability tab:

Porting telephone number(Ringmaster)

LNA=V

Cable ID= P000 or V000

Chan Pair= 000

Service Order Restrictions:

None

Tariff Reference:

None

~~USOC / FID References:~~

None

~~Situations / Exhibits:~~

None

~~Related Topics / Information:~~

None