



675 West Peachtree Street
Atlanta, Georgia 30375

Carrier Notification
SN91087061

Date: April 12, 2007

To: Competitive Local Exchange Carriers (CLEC)

Subject: CLECs – (Documentation/Guides) - Update to the Local Ordering Handbook (LOH), Version 24.0C, New Local Service Ordering Guide 6 (LSOG 6) and EDI Local Mechanization Specifications 06 (ELMS 06) for Release 24.0

BellSouth Telecommunications, Inc. d/b/a AT&T Southeast (AT&T) will implement the following changes to update documentation in the LOH, Version 24.0C, ELMS 06 for Release 24.0.

CCP Number	Description Of The Change
2483	IWT & IWTQ fields: Update to remove the electronic-only indicator '(e)' in the R/C/O tables in the LOH-Ordering and remove any electronic-only field reference for the IWT and IWTQ fields in the LOH-Data Dictionary.
2484	ACT field (DL Form/Screen): Add Business Rule to LOH-Data Dictionary per UR [User requirement item] 38889.0100 (DACT field).
2485	AN and ATN fields (LSR Form/Screen): Update Conditional Usage Note 1 to read: "Excluding REQTYTYP = C, required when the ATN field is not populated" for the AN field; and "Excluding REQTYTYP = C, required when the AN field is not populated" for the ATN field. Also: Move AN & ATN fields from 'Required' to "Optional" for REQTYTYP C-INP R/C/O Tables. Move AN & ATN fields from 'Conditional' to "Optional" for REQTYTYP C-LNP & WLNP R/C/O Tables.
2486	LD1 LV1 fields Manual Business Rule (EU Form/Screen): Add manual business rule for EU address fields LD1 LD2 LD3 LV1 LV2 LV3: Rule 1: When REQTYTYP=J and ACT=N, or when REQTYTYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.

Please refer to the attachments for specific details of the changes listed above.

These changes will be reflected in the next update of the ELMS 06, Release 24.0/LOH Version 24.0D, scheduled to be posted on Friday, April 13, 2007.

A summary of all changes within this document will be listed in the **Summary of Changes** section.

This update can be found on the BellSouth Interconnection Services Web site in the Local Exchange Ordering (LEO) Guides at:

http://interconnection.bellsouth.com/reference_library/guides/html/leo.html#loh

Please contact your AT&T local support manager with any questions.

Sincerely,

ORIGINAL SIGNED BY KRISTEN E. SHORE

Kristen E. Shore – Director
AT&T Southeast

Attachments



CCP 2483 Attachment Listed Below

LOH-24.0-ELMS06

CRB: 5007

CCP: 2483

MAP: ELMS06

REL: 24

REQTYP A & B R/C/O Tables (where IWT & IWTQ fields appear)

Reqty	Product			Field	Status	Manual	Field	Status	Manual
A	Analog Non-Designed Loop	LNA	N	IWT	C	E	IWTQ	C	E
A	Analog Non-Designed Loop	LNA	C	IWT	C	E	IWTQ	C	E
A	Analog Non-Designed Loop	LNA	V	IWT	C	E	IWTQ	C	E
A	Analog Non-Designed Loop	LNA	T	IWT	C	E	IWTQ	C	E
A	Analog Designed Loop	LNA	C	IWT	C	E	IWTQ	C	E
A	Analog Designed Loop	LNA	N	IWT	C	E	IWTQ	C	E
A	Analog Designed Loop	LNA	V	IWT	C	E	IWTQ	C	E
A	Analog Designed Loop	LNA	T	IWT	C	E	IWTQ	C	E
A	Digital Data Designed Loop (DS0)	LNA	C	IWT	C	E	IWTQ	C	E
A	Digital Data Designed Loop (DS0)	LNA	N	IWT	C	E	IWTQ	C	E
A	Digital Data Designed	LNA	V	IWT	C	E	IWTQ	C	E



Reqtyp	Product			Field	Status	Manual	Field	Status	Manual
	Loop (DS0)								
A	Digital Data Designed Loop (DS0)	LNA	T	IWT	C	E	IWTQ	C	E
A	Digital Designed Loop (Basic Rate ISDN)	LNA	V	IWT	C	E	IWTQ	C	E
A	Digital Designed Loop (Basic Rate ISDN)	LNA	N	IWT	C	E	IWTQ	C	E
A	Digital Designed Loop (Basic Rate ISDN)	LNA	C	IWT	C	E	IWTQ	C	E
A	Digital Designed Loop (Basic Rate ISDN)	LNA	T	IWT	C	E	IWTQ	C	E
A	EELs - 2w BRI/ISDN	LNA	C	IWT	C	E	IWTQ	C	E
A	EELs - 2w BRI/ISDN	LNA	N	IWT	C	E	IWTQ	C	E
A	EELs - 2w VG	LNA	C	IWT	C	E	IWTQ	C	E
A	EELs - 2w VG	LNA	N	IWT	C	E	IWTQ	C	E
A	EELs - 4w VG	LNA	C	IWT	C	E	IWTQ	C	E
A	EELs - 4w VG	LNA	N	IWT	C	E	IWTQ	C	E
A	EELs - 56/64 kbps	LNA	C	IWT	C	E	IWTQ	C	E
A	EELs - 56/64 kbps	LNA	N	IWT	C	E	IWTQ	C	E
A	EELs - DS-1	LNA	N	IWT	C	E	IWTQ	C	E
A	EELs - DS-1	LNA	C	IWT	C	E	IWTQ	C	E
A	Unbundled Copper Loop – Designed (UCL)	LNA	C	IWT	C	E	IWTQ	C	E
A	Unbundled Copper	LNA	N	IWT	C	E	IWTQ	C	E



Reqtyp	Product			Field	Status	Manual	Field	Status	Manual
	Loop – Designed (UCL)								
A	Unbundled Copper Loop – Designed (UCL)	LNA	V	IWT	C	E	IWTQ	C	E
A	Unbundled Copper Loop – Designed (UCL)	LNA	T	IWT	C	E	IWTQ	C	E
A	Unbundled Copper Loop – Non- Designed (UCL-ND)	LNA	N	IWT	C	E	IWTQ	C	E
A	Unbundled Copper Loop – Non- Designed (UCL-ND)	LNA	V	IWT	C	E	IWTQ	C	E
A	Unbundled Copper Loop – Non- Designed (UCL-ND)	LNA	C	IWT	C	E	IWTQ	C	E
A	Unbundled Copper Loop – Non- Designed (UCL-ND)	LNA	T	IWT	C	E	IWTQ	C	E
A	Universal Digital Channel (UDC)	LNA	T	IWT	C	E	IWTQ	C	E
A	Universal Digital Channel (UDC)	LNA	N	IWT	C	E	IWTQ	C	E
A	xDSL Loops	LNA	C	IWT	C	E	IWTQ	C	E
A	xDSL Loops	LNA	V	IWT	C	E	IWTQ	C	E



Reqtyp	Product			Field	Status	Manual	Field	Status	Manual
A	xDSL Loops	LNA	N	IWT	C	E	IWTQ	C	E
A	xDSL Loops	LNA	T	IWT	C	E	IWTQ	C	E
B	LNP, Designed Analog Loop	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP, Designed Analog Loop	LNA	N	IWT	C	E	IWTQ	C	E
B	LNP, Non-Designed Analog Loop	LNA	N	IWT	C	E	IWTQ	C	E
B	LNP, Non-Designed Analog Loop	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP, Unbundled Copper Loop – Designed (UCL-D)	LNA	N	IWT	C	E	IWTQ	C	E
B	LNP, Unbundled Copper Loop – Designed (UCL-D)	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP, xDSL Loops	LNA	N	IWT	C	E	IWTQ	C	E
B	LNP, xDSL Loops	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP, Digital Designed Basic Rate ISDN	LNA	N	IWT	C	E	IWTQ	C	E
B	LNP, Digital Designed Basic Rate ISDN	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP, Unbundled Copper Loop – Non-Designed	LNA	N	IWT	C	E	IWTQ	C	E



Reqtyp	Product			Field	Status	Manual	Field	Status	Manual
	(UCL-ND)								
B	LNP, Unbundled Copper Loop – Non-Designed (UCL-ND)	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP, EELs	LNA	N	IWT	C	E	IWTQ	C	E
B	LNP, EELs	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP BSLA - Designed Analog Loop	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP BSLA - Non-Designed Analog Loop	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP BSLA - EELS	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP BSLA - UCL-ND	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP BSLA - UCL-D	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP BSLA - XDSL	LNA	V	IWT	C	E	IWTQ	C	E
B	LNP BSLA - ISDN	LNA	V	IWT	C	E	IWTQ	C	E
E	ISDN-BRI Resale Service	LNA	C	IWT	C	E	IWTQ	C	E
M	UNE-P/WLP Bus/Res (Switched Combo Bus/Res)	LNA	X	IWT	C		IWTQ	C	
M	UNE-P/WLP Bus/Res (Switched Combo Bus/Res)	LNA	C	IWT	C		IWTQ	C	
M	UNE-P/WLP	LNA	G	IWT	C		IWTQ	C	



Reqtyp	Product			Field	Status	Manual	Field	Status	Manual
	Bus/Res (Switched Combo Bus/Res)								
M	UNE- P/WLP Bus/Res (Switched Combo Bus/Res)	LNA	N	IWT	C		IWTQ	C	
M	UNE- P/WLP Bus/Res (Switched Combo Bus/Res)	LNA	P	IWT	C		IWTQ	C	
M	UNE- P/WLP Bus/Res (Switched Combo Bus/Res)	LNA	V	IWT	C		IWTQ	C	
M	UNE- P/WLP Bus/Res (Switched Combo Bus/Res)	LNA	T	IWT	C		IWTQ	C	
N	DID Resale Service - Trunk Service Detail Section	TACT	C	IWT	C	E	IWTQ	C	E
N	DID Resale Service - Trunk Service Detail Section	TACT	N	IWT	C	E	IWTQ	C	E
N	DID Resale Service - Trunk Service Detail Section	TACT	V	IWT	C	E	IWTQ	C	E
N	PBX Resale Service	TACT	C	IWT	C	E	IWTQ	C	E
N	PBX Resale Service	TACT	G	IWT	C	E	IWTQ	C	E



Reqty	Product			Field	Status	Manual	Field	Status	Manual
N	PBX Resale Service	TACT	N	IWT	C	€	IWTQ	C	€
N	PBX Resale Service	TACT	V	IWT	C	€	IWTQ	C	€



CRB: 5007
CCP: 2483
MAP: ELMS10
REL: 24

For the products / LNAs listed below, **delete** the IWT and IWTQ fields from the RCO tables.

Reqtyp	Product			Field	Status	Manual	Field	Status	Manual
M	UNE-P/WLP Bus/Res (Switched Combo Bus/Res)	LNA	X	IWT	C		IWTQ	C	
M	UNE-P/WLP Bus/Res (Switched Combo Bus/Res)	LNA	P	IWT	C		IWTQ	C	
E	ISDN-BRI Resale Service	LNA	C	IWT	C	E	IWTQ	C	E

CRB: 5007
CCP: 2483
MAP: ELMS6
REL: 24

For the products / LNAs listed below, **ADD** the IWT and IWTQ fields to the RCO tables

Reqtyp	Product			Field	Status	Manual	Field	Status	Manual
M	Resale Non Complex	LNA	C	IWT	C		IWTQ	C	
M	Resale Non Complex	LNA	G	IWT	C		IWTQ	C	
M	Resale Non Complex	LNA	N	IWT	C		IWTQ	C	
M	Resale Non Complex	LNA	V	IWT	C		IWTQ	C	
M	Resale Non Complex	LNA	T	IWT	C		IWTQ	C	
E	Coin	LNA	C	IWT	C		IWTQ	C	
E	Coin	LNA	G	IWT	C		IWTQ	C	
E	Coin	LNA	N	IWT	C		IWTQ	C	



E	Coin	LNA	V	IWT	C		IWTQ	C	
E	Coin	LNA	T	IWT	C		IWTQ	C	



CRB: 5007
CCP: 2483
MAP: ELMS06
REL: 24
DIDDODPBX.LSNP, PS, RS and EU (Form/Screen) Data Dictionary

IWT

Inside Wire Type
DIDDODPBX Form / Screen
LSOG10 / ELMS10

Definition

Identifies the type of inside wiring to be used.

Definition Notes

Note 1: This field is repeatable per RNUM in the Trunk Section.

~~Note 2: This field is valid for electronic ordering only.~~

Valid Entries

- A = Plenum 4 pair or less
- B = Non-Plenum 4 pair or less
- C = Plenum 25 pair
- D = Non Plenum 25 pair
- E = Reuse and test existing wiring

Valid Entry Notes

None

Data Characteristics

1 alpha character

Examples

- A
- C

Conditional Usage Notes

~~Electronic~~

Note 1: Required when the IWO field is populated.

Business Rules

None

***** End of definition for field IWT *****



IWTQ

Inside Wire Type Quantity
DIDDODPBX Form / Screen
LSOG10 / ELMS10

Definition

Identifies the quantity of inside wire types requested.

Definition Notes

Note 1: This field is repeatable per RNUM in the Trunk section.

Note 2: ~~This field is valid for electronic ordering only.~~

Valid Entries

01 - 99

Valid Entry Notes

~~Electronic~~

Note 1: When the entry in this field is 16 or greater the PROJECT field must also be populated.

Data Characteristics

2 numeric characters

Examples

02

Conditional Usage Notes

~~Electronic~~

Note 1: Required when the IWT field is populated

Business Rules

Rule 1: Per RNUM when both the IWTQ and IWJQ fields are populated this field must be equal to or greater than the IWJQ field.

***** End of definition for field IWTQ *****



IWT

Inside Wire Type
LS Form / Screen
LSOG10 / ELMS10

Definition

Identifies the type of inside wiring to be used.

Definition Notes

Note 1: This field is repeatable per LNUM.

Note 2: ~~This field is valid for electronic ordering only.~~

Valid Entries

- A = Plenum 4 pair or less
- B = Non-Plenum 4 pair or less
- C = Plenum 25 pair
- D = Non Plenum 25 pair
- E = Reuse and test existing wiring

Valid Entry Notes

None

Data Characteristics

1 alpha character

Examples

- A
- C

Conditional Usage Notes

Electronic

Note 1: Required when the IWO field is populated and the product is: Analog voice designed and non-designed; Digital Data Designed (DS0) and (DS1); Digital Data Basic Rate ISDN; ADSL (2W) designed; HDSL (2W) designed and (4W) designed; UCL-Short (2W) designed and (4W) designed; UCL-Long (2W) designed and (4W) designed; Enhanced Extended Links (EELS); UCL-ND; Universal Digital Channel (UDC)

Business Rules

None

***** End of definition for field IWT *****



IWTQ

Inside Wire Type Quantity
LS Form / Screen
LSOG10 / ELMS10

Definition

Identifies the quantity of inside wire types requested.

Definition Notes

Note 1: This field is repeatable per LNUM.

~~Note 2: This field is valid for electronic ordering only.~~

Valid Entries

01 - 99

Valid Entry Notes

Electronic

Note 1: When the entry in this field is 16 or greater the PROJECT field must also be populated.

Data Characteristics

2 numeric characters

Examples

02

Conditional Usage Notes

Electronic

Note 1: Required when the IWT is populated, otherwise prohibited.

Business Rules

None

***** End of definition for field IWTQ *****



IWT

Inside Wire Type
LSNP Form / Screen
24.0, LSOG10 / ELMS10

CRB Issues Included: None

Definition

Identifies the type of inside wiring to be used.

Definition Notes

Note 1: This field is repeatable per LNUM.

~~Note 2: This field is valid for electronic ordering only.~~

Valid Entries

- A = Plenum 4 pair or less
- B = Non-Plenum 4 pair or less
- C = Plenum 25 pair
- D = Non Plenum 25 pair
- E = Reuse and test existing wiring

Valid Entry Notes

None

Data Characteristics

1 alpha character

Examples

- A
- C

Conditional Usage Notes

Electronic

Note 1: Required when the IWO field is populated

Business Rules

Electronic

Rule 1: When this field is populated the NPT field must be D.

***** End of definition for field IWT *****



IWTQ

Inside Wire Type Quantity
LSNP Form / Screen
LSOG10 / ELMS10

Definition

Identifies the quantity of inside wire types requested.

Definition Notes

Note 1: This field is repeatable per LNUM.

~~Note 2: This field is valid for electronic ordering only.~~

Valid Entries

01 - 99

Valid Entry Notes

Electronic

Note 1: When the entry in this field is 16 or greater the PROJECT field must also be populated.

Data Characteristics

2 numeric characters

Examples

02

Conditional Usage Notes

Electronic

Note 1: Required when the IWT field is populated

Business Rules

Electronic

Rule 1: Per LNUM when both the IWTQ and IWJQ fields are populated this field must be equal to or greater than the IWJQ field.

Rule 2: When this field is populated the NPT must be D.

***** End of definition for field IWTQ *****



IWT

Inside Wire Type
PS Form / Screen
LSOG10 / ELMS10

CRB Issues Included: None

Definition

Identifies the type of inside wiring to be used.

Definition Notes

Note 1: This field is repeatable per LNUM.

Note 2: ~~This field is valid for electronic ordering only.~~

Valid Entries

C = Plenum 25 pair
D = Non Plenum 25 pair
E = Reuse and test existing wiring

Electronic

A = Plenum 4 pair or less
B = Non-Plenum 4 pair or less

Valid Entry Notes

None

Data Characteristics

1 alpha character

Examples

A
C

Conditional Usage Notes

Electronic

- Note 1: Required when the IWTQ field is populated.
Note 2: Prohibited when the TOS field is not 1AM- or 1BM-.
Note 3: Prohibited when the IWO field is not populated.
Note 4: For REQTYP = M, TOS = 1AM- or 1BM-, IWT is required when IWO = W.
Note 5: For REQTYP = M, TOS = 1AM- or 1BM-, IWT is prohibited when IWO = S or U.
Note 6: At least one IWT is required when the IWO field is populated with W.

Business Rules

None

***** End of definition for field IWT *****



IWTQ

PS Form / Screen
LSOG10 / ELMS10

Definition

Identifies the quantity of inside wire types requested.

Definition Notes

Note 1: This field is repeatable per LNUM.

~~Note 2: This field is valid for electronic ordering only.~~

Valid Entries

01 - 99

Valid Entry Notes

~~Electronic~~

Note 1: When the entry in this field is 16 or greater the PROJECT field must also be populated.

Data Characteristics

2 numeric characters

Examples

02

Conditional Usage Notes

~~Electronic~~

Note 1: Required when the IWT field is populated.

Note 2: Prohibited when the TOS field is not 1AM- or 1BM-.

Note 3: Prohibited when the IWT is not populated.

Business Rules

Rule 1: Per LNUM when both the IWTQ and IWJQ fields are populated this field must be equal to or greater but cannot be less than the IWJQ field.

***** End of definition for field IWTQ *****



IWT

Inside Wire Type
RS Form / Screen
LSOG10 / ELMS10

Definition

Identifies the type of inside wiring to be used.

Definition Notes

Note 1: This field is repeatable per LNUM.

Note 2: ~~This field is valid for electronic ordering only.~~

Valid Entries

- A = Plenum 4 pair or less
- B = Non-Plenum 4 pair or less
- C = Plenum 25 pair
- D = Non Plenum 25 pair
- E = Reuse and test existing wiring

Valid Entry Notes

None

Data Characteristics

1 alpha character

Examples

- A
- C

Conditional Usage Notes

Electronic

Note 1: Required when the IWO field is populated and the 2nd character of the TOS is H.

Note 2: Prohibited when the 2nd character of the TOS is not H.

Note 3: Prohibited when the IWO field is not populated.

Business Rules

None

***** End of definition for field IWT *****



IWTQ

Inside Wire Type Quantity
RS Form / Screen
LSOG10 / ELMS10

Definition

Identifies the quantity of inside wire types requested.

Definition Notes

Note 1: This field is repeatable per LNUM.

Note 2: ~~This field is valid for electronic ordering only.~~

Valid Entries

01 - 99

Valid Entry Notes

Electronic

Note 1: When the entry in this field is 16 or greater the PROJECT field must also be populated.

Data Characteristics

2 numeric characters

Examples

02

Conditional Usage Notes

Electronic

Note 1: Required when the IWT field is populated and the 2nd character of the TOS is H.

Note 2: Prohibited when the 2nd character of the TOS is not H.

Note 3: Prohibited when the IWT is not populated.

Business Rules

Electronic

Rule 1: Per LNUM when both the IWTQ and IWJQ fields are populated this field must be equal to or greater but cannot be less than the IWJQ field.

***** End of definition for field IWTQ *****



IWO

Inside Wiring Options
EU Form / Screen
LSOG10 / ELMS10

Definition

Identifies the requirement for inside wire services.

Definition Notes

None

Valid Entries

- S = Provide wiring repair plan.
- U = Provide wiring and repair plan.
- W = Provide wiring.

Valid Entry Notes

- Note 1: IWO of W is the only valid entry when the REQ TYP is A.
- Note 2: IWO of W is the only valid entry when the REQ TYP is B and the NPT is D.
- Note 3: IWO of W is the only valid entry when the REQ TYP is E and the 2nd character of the TOS is H.
- Note 4: IWO of W is the only valid entry when the REQ TYP is N and the 2nd character of the TOS is J or Q.
- Note 5: The valid entries for IWO are S, U, and W when the REQ TYP is M.
- Note 6: When REQ TYP is M and the ACT=C/LNA=N, X or C, ACT=N/LNA=N, ACT=V/LNA=N, X, V or G, or , ACT=T/LNA=N or T, and the USOC=SEQ1X is populated in the FEATURE field of the LSR for any LNUM when FEATURE ACTIVITY is N, IWO must be populated with S or U.
- Note 7: When the REQ TYP is M and TOS = 1AM- or 1BM- the only valid entry for IWO is W, when at least one IWT is populated.

Data Characteristics

1 alpha character

Examples

S

Conditional Usage Notes

- Note 1: Prohibited when the REQ TYP is C, F or J.
- Note 2: Prohibited when the REQ TYP is B and the NPT is not D.
- Note 3: Required when the JR field is populated with Y.
- Note 4: Required when the IWCON field is populated.
- Note 5: When the REQ TYP is M (Non-Complex), the TOS is 1AM- or 1BM-, and Non-Basic Wiring USOCs are populated, the IWO is required when IWT is populated.

Electronic

Note 6: Required when the IWT field is populated.

Business Rules

None

***** End of definition for field IWO *****



CCP 2484 Attachment Listed Below

LOH-24.0-ELMS06

DACT

Delivery Activity
DL Form / Screen
LSOG6 / ELMS6

Definition

Identifies the delivery activity for this request.

Definition Notes

None

Valid Entries

N = New Directory Delivery

Valid Entry Notes

None

Data Characteristics

1 alpha character

Examples

N

Conditional Usage Notes

- Note 1: Prohibited when the CC or the NNSP field is populated with a wireless OCN.
- Note 2: Required when any other field in the Delivery Address/Information section is populated.
- Note 3: Prohibited when the 4th character of the TOS is R.
- Note 4: DACT is required when ACT=V and an N order will be generated, when the service address is unnumbered. (Example: Partial migration to a new account).
- Note 5: DACT is required when ACT=V and a C order will be generated, when the existing directory delivery address on the customer record is not fully formatted, and the service address is unnumbered. (Example: Full migration to a new account).

Business Rules

- Rule 1: DACT allowed once per LSR.
- Rule 2: When the DACT field is not populated ACT = N or T, then the directory delivery name and address will default from the fields on the EU form for end user name and service address.
- Rule 3: When ACT=V, and when an N order will be generated, and the existing directory delivery address on the customer record is not fully formatted, and the service address is not unnumbered, the name will default from the EU form and the address will default from the existing end user service address. (Example: Partial migration to a new account).
- Rule 4: When ACT=V, and a C order will be generated, and the existing directory delivery address on the customer record is not fully formatted, and the service address is not unnumbered, the name will default from the EU form and the address will default from the existing end user service address. (Example: Full migration to a new account).
- Rule 5: For REQ TYP "J", with ACT=R, when the DIRQTYA or DIRQTYNC field is populated the DACT must be "N".

Rule 6 When REQ TYP=J and ACT=R and EUMI is populated and DACT is not populated, the directory delivery name



and address will default from the fields on the EU form for the end user name and service address.

***** End of definition for field DACT *****



CCP 2485 Attachment Listed Below

LOH-24.0-ELMS06

**Reqtyp C
INP**

Product Listing

Number Portability (NP) is a part of local competition that provides end users with the ability to retain their phone numbers when they change service providers, change from one type of service to another, or move from one physical location to another. There are two types of number portability:

Interim Number Portability (INP)

This is a temporary solution for porting numbers which involves two telephone numbers to route calls to the serving wire center using one of the following methods:

- Remote Call Forwarding
- Direct Inward Dialing
- Route Index Hubbing.

Local Number Portability (LNP)

This is the long-range solution and includes the following characteristics:

Uses only one telephone number

Requires significant network architecture hardware and software upgrades

Uses the Advanced Intelligent Network (AIN) requires new routing methodology to send calls to the wire center of the company currently providing the local service.

- Ordering Forms/Screens
- The following chart illustrates the required, conditional and optional forms/screens for ordering this service. Detailed information will follow to assist you in filling out each of these forms/screens.
-

Forms/Screens Number Portability – INP										
LSR	Hunting	EU	DL	RS	DRS	PS	NP	LS	LSNP	RPL
R		R	O				C [1]			
R = Required C = Conditional O = Optional										

[1] - The NP form/screen is required only when ACT = C, or V. Otherwise, the NP form/screen is not required.

Completing the DL Form/Screen

If directory listings are required, refer to **REQTYP J** for more information on completing the DL form/screen.



Completing the LSR and EU Forms/Screens

Account level activities (ACT) apply to the entire account. A complete list of ACTs and their definition can be found in the Data Dictionary entry for ACT.

The following chart shows all of the valid account level activities for this service.

Valid Account Level Activities Number Portability – INP										
N	C	D	T	R	V	S	B	W	L	Y
-	X	X	-	-	X	-	-	-	-	-
Note: "X" denotes valid account level activities. A dash (-) indicates a non-valid account level activity.										

The Required, Conditional and Optional (R/C/O) fields on the LSR and EU forms/screens will be given for every valid ACT code in the **ACT Tables** section.

Completing the NP Form/Screen

The Number Portability (NP) form/screen may be required or invalid depending on the account level activity. Each account level activity has valid Line Level Activities (LNAs). These LNAs determine how, or if, the NP form/screen should be populated. A complete list of LNAs and their definition can be found in the Data Dictionary entry for LNA.

The following chart gives the valid LNAs for each account level activity (ACT) and the associated NP form/screen usage for this service.

If REQ TYP is:	And ACT is:	Then LNA is:	And NP form/screen is:
C (INP)	C	C, D	Required
C (INP)	D	Prohibited	Not Require
C (INP)	V	D, V	Required

The Required, Conditional and Optional (R/C/O) fields for the Number Portability (NP) form/screen are listed according to the Line Level Activity (LNA) in the **LNA Tables** Section.



RCO Tables

The following tables show the Required, Conditional and Optional (R/C/O) fields on the valid forms/screens for this product. All unmentioned fields are either invalid, not applicable, prohibited or not supported. When fields are populated which are not supported by BellSouth, these not supported fields will be ignored. Populating any other fields may result in a fatal reject or a clarification of the service request.

Please note the following codes:

- Optional fields marked with an asterisk (*) force at least one of the conditional fields to become required when populated.
- Fields used only for manual orders are followed by (M).
- Fields used only for electronic orders are followed by (E).
- For fields marked with a DOUBLE asterisk (**) please refer to the Data Dictionary for clarification.

See the Data Dictionary Section for additional information on each field.

ACT Tables: Reqtyp C, INP

ACT= C: LSR

Required

ACT (M)	ATN (M)	BAN1 (M)
CC (M)	CCNA (M)	CIC (M)
D/TSENT (M)	DDD (M)	INIT (M)
INIT-FAX NO. (M)	INIT-TEL NO. (M)	PG_OF_ (M)
PON (M)	REQTYP (M)	SC (M)
TOS (M)		

Conditional

BH1 (M)	CUST (M)	IMPCON-TEL NO. (M)
LSCP (M)	MEU (M)	NOR (M)
PROJECT (M)	PROJINDR (M)	RPON (M)
SUP (M)	VER (M)	

Optional

ATN (M)	CNO (M)	IMPCON* (M)
REMARKS (M)	VTA (M)	

ACT= C: EU

Required

ATN (M)	NAME (M)	PG_OF_ (M)
PON (M)		



ACT Tables: Reqtvp C, INP

Conditional

DISC NBR (M)	DNUM (M)	DQTY (M)
EAN (M)	EATN (M)	VER (M)

Optional

ATN (M)

ACT= D: LSR

Required

ACT (M)	ATN (M)	BAN1 (M)
CC (M)	CCNA (M)	CIC (M)
D/TSENT (M)	DDD (M)	PG_OF_ (M)
PON (M)	REQTYP (M)	SC (M)
TOS (M)		

Conditional

CUST (M)	IMPCON-TEL NO. (M)	NOR (M)
PROJECT (M)	PROJINDR (M)	RPON (M)
SUP (M)	VER (M)	

Optional

ATN (M)	IMPCON* (M)	REMARKS (M)
----------------	-------------	-------------

ACT= D: EU

Required

ATN (M)	NAME (M)	PG_OF_ (M)
PON (M)		

Conditional

DISC NBR (M)	DNUM (M)	DQTY (M)
EAN (M)	EATN (M)	TC NAME (M)
TC PER (M)	TC TO PRI (M)	TC TO SEC (M)
TCID (M)	VER (M)	

Optional

ATN (M)	TC OPT* (M)	TER (M)
----------------	-------------	---------



ACT Tables: Reqtvp C, INP

ACT= V: LSR

Required

ACT (M)	ATN (M)	CC (M)
CCNA (M)	CIC (M)	D/TSENT (M)
DDD (M)	INIT (M)	INIT-FAX NO. (M)
INIT-TEL NO. (M)	MI (M)	PG_OF_ (M)
PON (M)	REQTYP (M)	SC (M)
TOS (M)		

Conditional

ALT-IMP CON-TEL NO. (M)	BAN1 (M)	BII (M)
CUST (M)	IMP CON-TEL NO. (M)	NOR (M)
PROJINDR (M)	RPON (M)	SUP (M)
VER (M)		

Optional

ATN (M)	ALT-IMP CON* (M)	CNO (M)
IMP CON* (M)	PROJECT (M)	REMARKS (M)
VTA (M)		

ACT= V: EU

Required

ATN (M)	CITY (M)	ELT (M)
NAME (M)	PG_OF_ (M)	PON (M)
SASN (M)	STATE (M)	ZIP (M)

Conditional

AAI (M)	EAN (M)	EATN (M)
FB-BILLCON (M)	FB-BILLCON TEL NO. (M)	FB-BILLNM (M)
FB-CITY (M)	FB-FLOOR (M)	FB-ROOM (M)
FB-SBILLNM (M)	FB-STATE (M)	FB-STREET (M)
FB-ZIP (M)	LD1 (M)	LD2 (M)
LD3 (M)	LV1 (M)	LV2 (M)
LV3 (M)	SANO (M)	SASD (M)
SASF (M)	SASS (M)	SATH (M)
VER (M)		

Optional

ATN (M)	FBI* (M)
----------------	----------



LNA Tables: Reqtvp C, INP

LNA= C: NP

Required

ATN (M)	LNA (M)	LNUM (M)
NPQTY (M)	NPT (M)	PG_OF_ (M)
PON (M)	PORTED NBR (M)	

Conditional

CFTN (M)	TNP (M)	VER (M)
----------	---------	---------

Optional

ATN (M)	NPI (M)	
--------------------	---------	--

LNA= D: NP

Required

ATN (M)	LNA (M)	LNUM (M)
NPQTY (M)	NPT (M)	PG_OF_ (M)
PON (M)	PORTED NBR (M)	

Conditional

VER (M)		
---------	--	--

Optional

ATN (M)	NPI (M)	
--------------------	---------	--

LNA= V: NP

Required

ATN (M)	LNA (M)	LNUM (M)
NPQTY (M)	NPT (M)	PG_OF_ (M)
PON (M)	PORTED NBR (M)	

Conditional

CFTN (M)	LEATN (M)	NPTG (M)
RTI (M)	TNP (M)	VER (M)

Optional

ATN (M)	NPI (M)	
--------------------	---------	--



LNP

Product Listing

Number Portability (NP) is a part of local competition that provides end users with the ability to retain their phone numbers when they change service providers, change from one type of service to another, or move from one physical location to another. There are two types of number portability:

Interim Number Portability (INP)

This is a temporary solution for porting numbers which involves two telephone numbers to route calls to the serving wire center using one of the following methods:

- Remote Call Forwarding
- Direct Inward Dialing
- Route Index Hubbing.

Local Number Portability (LNP)

This is the long-range solution and includes the following characteristics:

- Uses only one telephone number
- Requires significant network architecture hardware and software upgrades
- Uses the Advanced Intelligent Network (AIN) requires new routing methodology to send calls to the wire center of the company currently providing the local service.

Ordering Forms/Screens

The following chart illustrates the required, conditional and optional forms/screens for ordering this service. Detailed information will follow to assist you in filling out each of these forms/screens.

Forms/Screens Number Portability – LNP										
LSR	Hunting	EU	DL	RS	DRS	PS	NP	LS	LSNP	RPL
R		R	O				R			

Completing the DL Form/Screen

If directory listings are required, refer to **REQTYP J** for more information on completing the DL form/screen.

Completing the LSR and EU Forms/Screens

Account level activities (ACT) apply to the entire account. A complete list of ACTs and their definition can be found in the Data Dictionary entry for ACT.

The following chart shows all of the valid account level activities for this service.

Valid Account Level Activities Number Portability – LNP
--



N	C	D	T	R	V	S	B	W	L	Y
-	-	-	-	-	X	-	-	-	-	-

Note: "X" denotes valid account level activities. A dash (-) indicates a non-valid account level activity.

The Required, Conditional and Optional (R/C/O) fields on the LSR and EU forms/screens will be given for every valid ACT code in the **ACT Tables** section.

Completing the NP Form/Screen

The Number Portability (NP) form/screen may be required or invalid depending on the account level activity. Each account level activity has valid Line Level Activities (LNAs). These LNAs determine how, or if, the NP form/screen should be populated. A complete list of LNAs and their definition can be found in the Data Dictionary entry for LNA.

The following chart gives the valid LNAs for each account level activity (ACT) and the associated NP form/screen usage for this service.

If REQTYP is:	And ACT is:	Then LNA is:	And NP form/screen is:
C (LNP)	V	V	Required

The Required, Conditional and Optional (R/C/O) fields for the Number Portability (NP) form/screen are listed according to the Line Level Activity (LNA) in the **LNA Tables** Section.



RCO Tables

The following tables show the Required, Conditional and Optional (R/C/O) fields on the valid forms/screens for this product. All unmentioned fields are either invalid, not applicable, prohibited or not supported. When fields are populated which are not supported by BellSouth, these not supported fields will be ignored. Populating any other fields may result in a fatal reject or a clarification of the service request.

Please note the following codes:

- Optional fields marked with an asterisk (*) force at least one of the conditional fields to become required when populated.
- Fields used only for manual orders are followed by (M).
- Fields used only for electronic orders are followed by (E).
- For fields marked with a DOUBLE asterisk (**) please refer to the Data Dictionary for clarification.

See the Data Dictionary Section for additional information on each field.

ACT Tables: Reqtyp C, LNP

ACT= V: LSR

Required

ACT	CC	CCNA
CIC	D/TSENT	DDD
INIT	INIT-FAX NO.	INIT-TEL NO.
MI	PG_OF_ (M)	PON
REQTYP	SC	TOS

Conditional

AN	ATN	BAN1
BII	CUST	LOCQTY
NNSP	NOR	PROJECT
PROJINDR	RPON	SUP
VER		

Optional

AN	ATN	CNO
EXP	REMARKS	VTA

ACT= V: EU

Required

CITY	ELT	NAME
PG_OF_ (M)	PON (M)	SASN
STATE	ZIP	



ACT Tables: Reqtvp C, LNP

Conditional

AAI	ACC (M)	AN (M)
ATN (M)	DISC NBR	DNUM
DQTY	EAN	EATN
EUMI	FB-BILLCON	FB-BILLCON TEL NO.
FB-BILLNM	FB-CITY	FB-FLOOR
FBI	FB-ROOM	FB-SBILLNM
FB-STATE	FB-STREET	FB-ZIP
LD1	LD2	LD3
LOCNUM DETAIL (E)	LV1	LV2
LV3	SANO	SASD
SASF	SASS	SATH
TC NAME	TC OPT	TC PER
TC TO PRI	TC TO SEC	TCID
VER (M)		

Optional

AN (M)	ATN (M)	LCON-NAME
LCON-TEL NO.	LOCNUM (M)	LOCNUM HEADER (E)
TER		



LNA Tables: Reqtvp C, LNP

LNA= V: NP

Required

LNA	LNUM	NPQTY
NPT	PG_OF_(M)	PON (M)
PORTED NBR		

Conditional

<u>AN (M)</u>	<u>ATN (M)</u>	LEAN
LEATN	VER (M)	

Optional

<u>AN (M)</u>	<u>ATN (M)</u>	LOCNUM
NPI		



Wireless LNP (WLNP)

LSR Restrictions and Limitations:

The following information is applicable to WLNP

- REQTYP = CB
- ACT = V
- LNA = V
- NPT = D

LSR's may be submitted via the following methods:

- LENS
- TAG-XML
- EDI
- FAX (Manual Ordering only)

Restrictions:

Unless specific business rules are documented in the data dictionary, WLNP will use current REQTYP C business for applicable fields.

Ordering Forms

REQTYP CB WLNP	LSR	EU	NP	DL
ACT = V	R	R	R	C*

*The Directory Listing (DL) form/screen may be submitted when adding, deleting or making changes to directory listings on a request accompanied by a request to port a wireless or wireline service.

(LSR) Package Entry Screens:

The following chart illustrates the required, conditional and optional forms/screens for ordering this service. Detailed information will follow to assist you in filling out each of these forms/screens.

REQTYP / SERVICE TYPE	Account level*	Line level**
C Wireless Local Number Portability	R	R

R = Required C = Conditional O = optional

* = per EATN

** = per PORTED TN

Completing the (LSR) Package Entry Screen:

The Required, Conditional and Optional (R/C/O) fields on the (LSR) Package Entries will be given for the valid REQTYP/ACT combination in the Section.

The following chart shows all of the valid account level activities for this requisition type.



REQTYP	ACTIVITY LEVEL
C Wireless Local Number Portability	V

ONLY VALID ACT is V

Account level activities (ACT) apply to the entire account. The ACTs are defined below:

V = Conversion of service as specified to new Local Service Provider (LSP), includes Wireless Local Number Portability

Line level activities (LNA) apply to the specified line only. The valid LNAs are listed below:

V = Conversion or Migration to new LSP as specified (specify only those changes from existing service), includes Wireless Local Number Portability

The following chart gives the valid LNAs for each account level activity (ACT) and the associated LS form/screen usage.

If ACT is:	Then LNA is	Line Level (Entries) :
V	V	Required

The Required, Conditional and Optional (R/C/O) fields for the **Wireless Local Number Portability (LSR) Package** is listed according to the LINE Level in the **Line Level Table(s)**.



RCO Tables

The following tables show the Required, Conditional and Optional (R/C/O) fields on the valid forms/screens for this product. All unmentioned fields are either invalid, not applicable, prohibited or not supported. When fields are populated which are not supported by BellSouth, these not supported fields will be ignored. Populating any other fields may result in a fatal reject or a clarification of the service request.

Please note the following codes:

- Optional fields marked with an asterisk (*) force at least one of the conditional fields to become required when populated.
- Fields used only for manual orders are followed by (M).
- Fields used only for electronic orders are followed by (E).
- For fields marked with a DOUBLE asterisk (**) please refer to the Data Dictionary for clarification.

See the Data Dictionary Section for additional information on each field.

ACT Tables: Reqtyp C, Wireless LNP (WLNP)

ACT= V: LSR

Required

ACT	CC	D/TSENT
DDD	INIT	INIT-FAX NO.
INIT-TEL NO.	MI	NPDI
PG_OF_ (M)	PON	REQTYP
SC	TOS	

Conditional

AN (M)	ATN	BAN1
CUST	LOCQTY	NNSP
NOR	PROJECT	PROJINDR
SUP	VER	

Optional

AN (M)	ATN	CCNA
CIC	CNO	EXP
REMARKS	RPON	

ACT= V: EU

Required

CITY	ELT	NAME
PG_OF_ (M)	PON (M)	SASN
STATE	ZIP	



ACT Tables: Reqtvp C, Wireless LNP (WLNP)

Conditional

AAI	ACC (M)	AN (M)
ATN (M)	DQTY (M)	EAN
EATN	LD1	LD2
LD3	LOCNUM DETAIL (E)	LV1
LV2	LV3	SANO
SASD	SASF	SASS
SATH	VER (M)	

Optional

AN (M)	ATN (M)	LCON-NAME
LCON-TEL NO.	LOCNUM (M)	LOCNUM HEADER (E)



LNA Tables: Reqtvp C, Wireless LNP (WLNP)

LNA= V: NP

Required

LNA	LNUM	NPQTY
NPT	PG_OF_(M)	PON (M)
PORTED NBR		

Conditional

AN (M)	ATN (M)	LEATN
VER (M)		

Optional

AN (M)	ATN (M)	NPI
--------	---------	-----



LOH-24.0D-ELMS06

AN

Account Number
LSR Form / Screen
LSOG6 / ELMS6

Definition

Identifies the main account number assigned by the NSP.

Definition Notes

- Note 1: Identifies a non-standard account number.
Note 2: Identifies an account number that is not a dialable number (e.g., miscellaneous account number).
Note 3: Use this field when listing request is for an 800 service listing or an interstate foreign listing or foreign listings in independent territories.

Valid Entries

Electronic

valid Miscellaneous Account Number or Billing Account Number

Manual

N = New Account Number

valid Miscellaneous Account Number or Billing Account Number

Valid Entry Notes

- Note 1: Hyphens are automatically inserted by the BellSouth electronic interface system.
Manual
Note 2: When REQ TYP B or C, NPT is D (LNP); the valid entry of N is prohibited.

Data Characteristics

Electronic

10 alpha/numeric or 13 alpha/numeric characters

Manual

1 alpha or up to 20 alpha/numeric characters (excluding optional hyphens)

Examples

Electronic

404M231234

404M231234123

Manual

404M231234123

404-M23-1234-123

N

Conditional Usage Notes

- Note 1: **Excluding REQ TYP=C, R** required when the ATN field is not populated.
Note 2: Prohibited when the REQ TYP is J with ACT of R and the EATN field is populated.

Business Rules



- Rule 1: A CABS billing account number is valid only when the REQ TYP is A or B.
- Rule 2: For REQ TYP J, with ACT of D, when this field is populated the class of service on the Customer Service Record (CSR) must be MSA or MHT.
- Rule 3: The same Miscellaneous Account number cannot be assigned for different end users.
- Rule 4: When REQ TYP is A or B (Designed Loops) the AN and BAN1 fields must match.
- Rule 5: When the REQ TYP is A or B (designed) loops, this field is to be populated with the CABS account number.
- Rule 6: When the REQ TYP is A or B (non-designed) loops, this field is to be populated with a CRIS miscellaneous account number.
- Rule 7: When the REQ TYP= A (Designed Loops) and the ACT = W, the data in the AN field cannot match the data in the EAN field.
- Rule 8: When the REQ TYP= A (Designed Loops) and the ACT = W, the system will validate that the first 10 characters of the AN field is a valid working CABS account.
- Rule 9: When the REQ TYP= A (Non-Designed Loops) and the ACT = W, the system will validate that the first 10 characters of the AN field is a valid working CRIS account.
- Rule 10: When the REQ TYP= A (Non-Designed Loops) and the ACT = W, then the first 10 characters of the AN field must match the first 10 characters of the EAN field regardless of the total number of characters.

Electronic

- Rule 11: [BULK Option 1 and Bulk Single LSR Arrangement Option 2] For LSRs with a BOPI, the Account Number is required once for each EATN.

Manual

- Rule 12: (ULUE)-For LSRs with a BOPI, the AN field is required once for each ECCKT.

***** End of definition for field AN *****



ATN

Account Telephone Number
LSR Form / Screen
LSOG6 / ELMS6

Definition

Identifies the account telephone number assigned by the NSP.

Definition Notes

Note 1: The ATN is a dialable telephone number.

Valid Entries

Electronic

a valid Account Telephone Number

Manual

N = New Account Telephone Number or a valid Account Telephone Number

Valid Entry Notes

Note 1: Hyphens are automatically inserted by the BellSouth electronic interface system.

Data Characteristics

Electronic

10 numeric characters

Manual

1 alpha or 10 numeric characters (excluding optional hyphens)

Examples

Electronic

2015551212

Manual

2015551212

201-555-1212

N

Conditional Usage Notes

Note 1: **Excluding REQ TYP=C, R** required when the AN field is not populated.

Note 2: Excluding REQ TYP B, PROHIBITED when the AN field is populated.

Note 3: When the REQ TYP is B, NPT is D (LNP) and LNLN field is populated, this field is required.

Note 4: When the REQ TYP is C, NPT is D (LNP) and the LNLN field is populated, this field is required.

Note 5: Required when the REQ TYP is J with ACT of R and the EATN field is populated.

Manual

Note 6: Prohibited when the REQ TYP is E and the 4th character of TOS is S or W.

Business Rules

Rule 1: When (NON-COMPLEX) REQ TYP is E or M / ACT is T this field is used to indicate the MAIN ACCOUNT NUMBER for the service at the NEW LOCATION. This field does not have to match the existing account number shown on the current Customer Service Record (CSR).



- Rule 2: When the ATN is changing (ATN differs from existing account number), a DL page is required for any additional listings that include the existing account number (including foreign listings, alternate calls, etc.).
- Rule 3: When the REQTYP is J and the ACT is R, and the EATN field is populated, the EATN and ATN fields cannot match.
- Rule 4: When the REQTYP is E (Non-Complex) or M (Switched Combination RES/BUS) with ACT of C and the request is changing from business to residence the existing main account telephone number must change in all states except Florida and North Carolina.
- Rule 5: When the REQTYP is E (Non-Complex) or M (Switched Combination RES/BUS) with ACT of C and the request is to change from a business class of service to a residence class of service and the request is being generated for order activity in the state of North Carolina, the existing main account telephone number must change only when the following conditions occur: YPH data on the existing CSR is anything other than 999001 Listing Instruction Code (LIC) data on the existing CSR is anything other than LNR.
- Rule 6: For REQTYP J, with ACT of D, when this field is populated the class of service on the Customer Service Record (CSR) must be LNPBL, or LNPRL.
- Rule 7: When REQTYP = J and ACT = V or W, the ATN must match the EATN.

Electronic

- Rule 8: When the ATN and NATN fields are both populated, the ATN and NATN fields must contain different Telephone Numbers.

Manual

- Rule 9: When REQTYP is E or M (Non-Complex) and ACT is C or V and LNA is G, V, or X and the main account number is changing, the ATN field is populated with the new MAIN ACCOUNT TELEPHONE NUMBER.
- Rule 10: When a Wireless Type 1 Provider requests a Port In on a REQTYP C, NPT = D , and the NPDI is populated , the ATN will be the Wireless Type 1 Provider's 10 digit account number where the Port In number will migrate.
- Rule 11: When a request is received for REQTYP J ACT N and a live account is found, where the first ten digits of the Account Telephone Number exactly match the data in the ATN Field, and the existing class of service is not LNPBL or LNPRL, the request will be returned to the originator as invalid.
- Rule 12: When a request is received for REQTYP J ACT N and a live account is found, where the first ten digits of the Account Telephone Number exactly match the data in the ATN Field, and the existing class of service is LNPBL or LNPRL and the originator of the request owns the existing account the request will be returned to the originator as invalid.
- Rule 13: When a request is received for REQTYP J, ACT N and a live account is found, where the first ten digits of the Account Telephone Number exactly match the data in the ATN Field, and the existing class of service is LNPBL or LNPRL and the originator of the request does not own the account, BellSouth will disconnect the old listing account and establish a new listing account.

***** End of definition for field ATN *****



CCP 2486 Attachment Listed Below

LOH-24.0-ELMS06

CRB: 5011
CCP: 2486
MAP: ELMS6
REL: 24
DL Data Dictionary

LD1

Location Designator 1
DL Form / Screen
LSOG6 / ELMS6

Definition

Identifies additional specific information related to the directory delivery address (e.g. bldg).

Definition Notes

None

Valid Entries

BLDG = Building
WNG = Wing
PIER = Pier

Valid Entry Notes

None

Data Characteristics

Up to 4 alpha characters

Examples

BLDG
WNG

Conditional Usage Notes

- Note 1: Optional when the DDASN field is populated, otherwise prohibited.
- Note 2: Required when the LV1 field is populated.
- Note 3: Prohibited when the LV1 field is not populated.
- Note 4: Prohibited when the CC or the NNSP field is populated with a wireless OCN.

Business Rules

Manual

~~Rule 1: When REQTYP=J and ACT=N, or when REQTYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.~~

None



LD2

Location Designator 2
DL Form / Screen
LSOG6 / ELMS6

Definition

Identifies additional specific information related to the directory delivery address (e.g. floor).

Definition Notes

None

Valid Entries

FLR = Floor

Valid Entry Notes

Note 1: When populated the only valid entry is FLR.

Data Characteristics

Up to 4 alpha characters

Examples

FLR

Conditional Usage Notes

- Note 1: Optional when the DDASN field is populated, otherwise prohibited.
- Note 2: Required when the LV2 field is populated.
- Note 3: Prohibited when the LV2 field is not populated.
- Note 4: Prohibited when the CC or the NNSP field is populated with a wireless OCN.

Business Rules

Manual

~~Rule 1: When REQTYP=J and ACT=N, or when REQTYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.~~

None

***** End of definition for field LD2 *****



LD3

Location Designator 3
DL Form / Screen
LSOG6 / ELMS6

Definition

Identifies additional specific information related to the directory delivery address (e.g. room).

Definition Notes

None

Valid Entries

APT = Apartment
RM = Room
LOT = Lot
SLIP = Slip
SUITE = Suite
UNIT = Unit

Valid Entry Notes

None

Data Characteristics

Up to 4 alpha characters

Examples

RM

Conditional Usage Notes

- Note 1: Optional when the DDASN field is populated, otherwise prohibited.
- Note 2: Required when the LV3 field is populated.
- Note 3: Prohibited when the LV3 field is not populated.
- Note 4: Prohibited when the CC or the NNSP field is populated with a wireless OCN.

Business Rules

Manual

Rule 1: When REQ TYP=J and ACT=N, or when REQ TYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.

None

***** End of definition for field LD3 *****



LV1

Location Value 1
DL Form / Screen
LSOG6 / ELMS6

Definition

Identifies the value associated with the first location designator (LD1) of the directory delivery address.

Definition Notes

None

Valid Entries

None

Valid Entry Notes

None

Data Characteristics

Up to 10 alpha/numeric characters

Examples

12

Conditional Usage Notes

- Note 1: Required when the LD1 field is populated.
- Note 2: Prohibited when the LD1 field is not populated.
- Note 3: Prohibited when the CC or the NNSP field is populated with a wireless OCN.

Business Rules

Manual

Rule 1: When REQTYP=J and ACT=N, or when REQTYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.

None

***** End of definition for field LV1 *****



LV2

Location Value 2
DL Form / Screen
LSOG6 / ELMS6

Definition

Identifies the value associated with second **location** designator (LD2) of the directory delivery address.

Definition Notes

None

Valid Entries

None

Valid Entry Notes

None

Data Characteristics

Up to 10 alpha/**numeric** characters

Examples

2

Conditional Usage Notes

Note 1: Required when the LD2 field is populated.

Note 2: Prohibited when the LD2 field is not populated.

Note 3: Prohibited when the CC or the NNSP field is populated with a wireless OCN.

Business Rules

Manual

~~Rule 1: When REQ TYP=J and ACT=N, or when REQ TYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.~~

None

***** End of definition for field LV2 *****



LV3

Location Value 3
DL Form / Screen
LSOG6 / ELMS6

Definition

Identifies the value associated with the third location designator (LD3) of the directory delivery address.

Definition Notes

None

Valid Entries

None

Valid Entry Notes

None

Data Characteristics

Up to 10 alpha/numeric characters

Examples

2B

Conditional Usage Notes

- Note 1: Required when the LD3 field is populated.
- Note 2: Prohibited when the LD3 field is not populated.
- Note 3: Prohibited when the CC or the NNSP field is populated with a wireless OCN.

Business Rules

Manual

Rule 1: When REQTYP=J and ACT=N, or when REQTYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.

None

***** End of definition for field LV3 *****



CRB: 5011
CCP: 2486
MAP: ELMS6
REL: 24
EU Data Dictionary

LD1

Location Identifier 1
EU Form / Screen
LSOG6 / ELMS6

Definition

Identifies additional specific information related to the address (e.g. bldg)..

Definition Notes

None

Valid Entries

BLDG = Building
WNG = Wing
PIER = Pier

Valid Entry Notes

None

Data Characteristics

Up to 4 alpha characters

Examples

BLDG

Conditional Usage Notes

Note 1: Required when LV1 field is populated, otherwise prohibited.
Note 2: Prohibited when the 4th character of the TOS is R.

Business Rules

Rule 1: Must be RSAG valid.
Rule 2: When REQ TYP = J and ACT = V or W, and the EU address fields are populated on the LSR, the system will ignore the data input and will instead use the service address of the existing CSR for generation of the service order.

Manual

Rule 3: When REQ TYP=J and ACT=N, or when REQ TYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.

***** End of definition for field LD1 *****



LD2

Location Identifier 2
EU Form / Screen
LSOG6 / ELMS6

Definition

Identifies additional specific information related to the address (e.g. floor).

Definition Notes

None

Valid Entries

FLR = Floor

Valid Entry Notes

Note 1: BellSouth allows only one valid value for this field.

Data Characteristics

Up to 4 alpha characters

Examples

FLR

Conditional Usage Notes

Note 1: Required when LV2 field is populated, otherwise prohibited.

Note 2: Prohibited when the 4th character of the TOS is R.

Business Rules

Rule 1: Must be RSAG valid.

Rule 2: When REQ TYP = J and ACT = V or W, and the EU address fields are populated on the LSR, the system will ignore the data input and will instead use the service address of the existing CSR for generation of the service order.

Manual

Rule 3: When REQ TYP=J and ACT=N, or when REQ TYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.

***** End of definition for field LD2 *****



LD3

Location Identifier 3
EU Form / Screen
LSOG6 / ELMS6

Definition

Identifies additional specific information related to the address (e.g. room).

Definition Notes

None

Valid Entries

APT = Apartment
RM = Room
LOT = Lot
SLIP = Slip
SUITE = Suite
UNIT = Unit

Valid Entry Notes

None

Data Characteristics

Up to 4 alpha characters

Examples

APT
RM
SUITE

Conditional Usage Notes

Note 1: Required when LV3 field is populated, otherwise prohibited.
Note 2: Prohibited when the 4th character of the TOS is R.

Business Rules

Rule 1: Must be RSAG valid.
Rule 2: When REQ TYP = J and ACT = V or W, and the EU address fields are populated on the LSR, the system will ignore the data input and will instead use the service address of the existing CSR for generation of the service order.

Manual

Rule 3: When REQ TYP=J and ACT=N, or when REQ TYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.

***** End of definition for field LD3 *****



LV1

Location Value 1
LSOG6 / ELMS6

Definition

Identifies the value associated with the first location designator (LD1) of the address.

Definition Notes

None

Valid Entries

None

Valid Entry Notes

None

Data Characteristics

Up to 10 alpha/numerics characters

Examples

12

Conditional Usage Notes

Note 1: Required when LD1 field is populated, otherwise prohibited.

Note 2: Prohibited when the 4th character of the TOS is R.

Business Rules

Rule 1: Must be RSAG valid.

Rule 2: When REQ TYP = J and ACT = V or W, and the EU address fields are populated on the LSR, the system will ignore the data input and will instead use the service address of the existing CSR for generation of the service order.

Manual

Rule 3: When REQ TYP=J and ACT=N, or when REQ TYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.

***** End of definition for field LV1 *****



LV2

Location Value 2
EU Form / Screen
LSOG6 / ELMS6

Definition

Identifies the value associated with the second location designator (LD2) of the address.

Definition Notes

None

Valid Entries

None

Valid Entry Notes

None

Data Characteristics

Up to 10 alpha/numerics characters

Examples

2

Conditional Usage Notes

- Note 1: Required when LD2 field is populated, otherwise prohibited.
- Note 2: Prohibited when the 4th character of the TOS is R.

Business Rules

- Rule 1: Must be RSAG valid.
- Rule 2: When REQ TYP = J and ACT = V or W, and the EU address fields are populated on the LSR, the system will ignore the data input and will instead use the service address of the existing CSR for generation of the service order.

Manual

Rule 3: When REQ TYP=J and ACT=N, or when REQ TYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.

***** End of definition for field LV2 *****



LV3

Location Value 3
EU Form / Screen
LSOG6 / ELMS6

Definition

Identifies the value associated with the third location designator (LD3) of the address.

Definition Notes

None

Valid Entries

None

Valid Entry Notes

None

Data Characteristics

Up to 10 alpha/numerics characters (BellSouth allows a maximum of 4 alphanumeric characters)

Examples

2B

Conditional Usage Notes

- Note 1: Required when LD3 field is populated, otherwise prohibited.
- Note 2: Prohibited when the 4th character of the TOS is R.

Business Rules

- Rule 1: Must be RSAG valid.
- Rule 2: When REQ TYP = J and ACT = V or W, and the EU address fields are populated on the LSR, the system will ignore the data input and will instead use the service address of the existing CSR for generation of the service order.

Manual

Rule 4: When REQ TYP=J and ACT=N, or when REQ TYP=J and EUMI is populated, if the main address on the EU form is RSAG valid and the supplemental address is not valid, then the LSR must be submitted manually.

***** End of definition for field LV3 *****